

# Tapered roller bearings: size chart

Searchable nominal dimensions from verified catalogue records

**2,346 dimension rows | 2,346 distinct model records | FAG, KOYO, SKF**

## Use the table

Choose the correct construction section, then use the PDF search for the complete designation. Compare the brand and all suffixes. Rows are ordered by inside, outside and axial dimensions, then brand and designation. Click a designation to open its existing BearingScope product record.

## Read the symbols, not just three numbers

All numeric table entries are in millimetres. Preserve the printed symbol: an inner-ring bore, a roller-complement diameter, ring width and complete assembly height are different quantities. Section notes identify special construction and seat conditions.

## Limits of this reference

This is an original BearingScope compilation, not a manufacturer manual, full technical datasheet, engineering drawing, CAD file or exhaustive standard-size schedule. Complete source-labelled dimension triples are included; incomplete or conflicting records are withheld. Equal nominal dimensions do not prove fit, performance, suffix equivalence or safe interchange.

## Technical basis and data date

Values are retained manufacturer-catalogue facts from the matching FAG, KOYO, SKF records. Product captures predate this edition; reviewed source snapshots were assembled on 2-3 October 2026. Each linked model record identifies its manufacturer. Primary-source addresses, collection dates and dimension-property evidence are retained privately. Explanations and layout are original; no installation limits, vehicle fitment, load ratings or tolerances are inferred.

## Sections in this download

Tapered roller bearings - 2,346 rows - page 2

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 30202-A              | d = 15      | D = 35       | T = 11.75  | Tapered roller bearing                |
| FAG   | 30202-A-S1           | d = 15      | D = 35       | T = 11.75  | Tapered roller bearing                |
| FAG   | 30202-A>A            | d = 15      | D = 35       | T = 11.75  | Tapered roller bearing                |
| FAG   | 30302-A              | d = 15      | D = 42       | T = 14.25  | Tapered roller bearing                |
| FAG   | 30302-H              | d = 15      | D = 42       | T = 14.25  | Tapered roller bearing                |
| FAG   | 30302-XL             | d = 15      | D = 42       | T = 14.25  | Tapered roller bearing                |
| FAG   | KL21549-L21511       | d = 15.875  | D = 34.989   | T = 10.998 | Tapered roller bearing                |
| FAG   | K03062-03162         | d = 15.875  | D = 41.275   | T = 14.288 | Tapered roller bearing                |
| FAG   | K21063-21212         | d = 15.875  | D = 53.975   | T = 22.225 | Tapered roller bearing                |
| FAG   | K21063-21213         | d = 15.875  | D = 53.975   | T = 22.225 | Tapered roller bearing                |
| FAG   | 30203-A              | d = 17      | D = 40       | T = 13.25  | Tapered roller bearing                |
| FAG   | 30203-A-TVP          | d = 17      | D = 40       | T = 13.25  | Tapered roller bearing                |
| FAG   | 30203-DY             | d = 17      | D = 40       | T = 13.25  | Tapered roller bearing                |
| FAG   | 30203-H              | d = 17      | D = 40       | T = 13.25  | Tapered roller bearing                |
| FAG   | 30203-XL             | d = 17      | D = 40       | T = 13.25  | Tapered roller bearing                |
| FAG   | 32203-A              | d = 17      | D = 40       | T = 17.25  | Tapered roller bearing                |
| FAG   | 32203-DY             | d = 17      | D = 40       | T = 17.25  | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 32203-XL             | d = 17      | D = 40       | T = 17.25  | Tapered roller bearing                |
| FAG   | 30303-A              | d = 17      | D = 47       | T = 15.25  | Tapered roller bearing                |
| FAG   | 30303-H              | d = 17      | D = 47       | T = 15.25  | Tapered roller bearing                |
| FAG   | 32303-A              | d = 17      | D = 47       | T = 20.25  | Tapered roller bearing                |
| FAG   | 32303-H              | d = 17      | D = 47       | T = 20.25  | Tapered roller bearing                |
| FAG   | KLM11749-LM11710     | d = 17.462  | D = 39.878   | T = 13.843 | Tapered roller bearing                |
| FAG   | KLM11749-LM11710-XL  | d = 17.462  | D = 39.878   | T = 13.843 | Tapered roller bearing                |
| FAG   | KLM11949-LM11910     | d = 19.05   | D = 45.237   | T = 15.494 | Tapered roller bearing                |
| FAG   | KLM11949-LM11910-TVP | d = 19.05   | D = 45.237   | T = 15.494 | Tapered roller bearing                |
| FAG   | K09067-09195         | d = 19.05   | D = 49.225   | T = 18.034 | Tapered roller bearing                |
| FAG   | K21075-21212         | d = 19.05   | D = 53.975   | T = 22.225 | Tapered roller bearing                |
| FAG   | 32904                | d = 20      | D = 37       | T = 12     | Tapered roller bearing                |
| FAG   | 32004-X              | d = 20      | D = 42       | T = 15     | Tapered roller bearing                |
| FAG   | 32004-X-H            | d = 20      | D = 42       | T = 15     | Tapered roller bearing                |
| FAG   | 32004-X-XL           | d = 20      | D = 42       | T = 15     | Tapered roller bearing                |
| FAG   | 32004-X>A            | d = 20      | D = 42       | T = 15     | Tapered roller bearing                |
| FAG   | T4DB020              | d = 20      | D = 45       | T = 14     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 30204-A              | d = 20      | D = 47       | T = 15.25  | Tapered roller bearing                |
| FAG   | 30204-A>A            | d = 20      | D = 47       | T = 15.25  | Tapered roller bearing                |
| FAG   | 30204-DY             | d = 20      | D = 47       | T = 15.25  | Tapered roller bearing                |
| FAG   | 30204-H              | d = 20      | D = 47       | T = 15.25  | Tapered roller bearing                |
| FAG   | 30204-XL             | d = 20      | D = 47       | T = 15.25  | Tapered roller bearing                |
| FAG   | 32204-A              | d = 20      | D = 47       | T = 19.25  | Tapered roller bearing                |
| FAG   | 32204-B              | d = 20      | D = 47       | T = 19.25  | Tapered roller bearing                |
| FAG   | 32204-B-XL           | d = 20      | D = 47       | T = 19.25  | Tapered roller bearing                |
| FAG   | 32204-H              | d = 20      | D = 47       | T = 19.25  | Tapered roller bearing                |
| FAG   | 32204-XL             | d = 20      | D = 47       | T = 19.25  | Tapered roller bearing                |
| FAG   | T2ED020              | d = 20      | D = 50       | T = 22     | Tapered roller bearing                |
| FAG   | K07079-07196         | d = 20      | D = 50.005   | T = 13.495 | Tapered roller bearing                |
| FAG   | 30304-A              | d = 20      | D = 52       | T = 16.25  | Tapered roller bearing                |
| FAG   | 30304-A-S1           | d = 20      | D = 52       | T = 16.25  | Tapered roller bearing                |
| FAG   | 30304-A>A            | d = 20      | D = 52       | T = 16.25  | Tapered roller bearing                |
| FAG   | 30304-H              | d = 20      | D = 52       | T = 16.25  | Tapered roller bearing                |
| FAG   | 31304                | d = 20      | D = 52       | T = 16.25  | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 32304-A              | d = 20      | D = 52       | T = 22.25  | Tapered roller bearing                |
| FAG   | 32304-H              | d = 20      | D = 52       | T = 22.25  | Tapered roller bearing                |
| FAG   | K09081-09195         | d = 20.625  | D = 49.225   | T = 19.845 | Tapered roller bearing                |
| FAG   | K09081-09196         | d = 20.625  | D = 49.225   | T = 23.02  | Tapered roller bearing                |
| FAG   | K12580-12520         | d = 20.638  | D = 49.225   | T = 19.845 | Tapered roller bearing                |
| FAG   | KM12649-M12610       | d = 21.43   | D = 50.005   | T = 17.526 | Tapered roller bearing                |
| FAG   | KLM12749-LM12710     | d = 21.986  | D = 45.237   | T = 15.494 | Tapered roller bearing                |
| FAG   | KLM12749-LM12710-XL  | d = 21.986  | D = 45.237   | T = 15.494 | Tapered roller bearing                |
| FAG   | KLM12749-LM12711     | d = 21.986  | D = 45.974   | T = 15.494 | Tapered roller bearing                |
| FAG   | 329/22               | d = 22      | D = 40       | T = 12     | Tapered roller bearing                |
| FAG   | 320/22-X             | d = 22      | D = 44       | T = 15     | Tapered roller bearing                |
| FAG   | 320/22-X-XL          | d = 22      | D = 44       | T = 15     | Tapered roller bearing                |
| FAG   | T4CB022              | d = 22      | D = 47       | T = 14     | Tapered roller bearing                |
| FAG   | T2CC022              | d = 22      | D = 47       | T = 17     | Tapered roller bearing                |
| FAG   | T2ED022              | d = 22      | D = 52       | T = 22     | Tapered roller bearing                |
| FAG   | AK1380-1328          | d = 22.225  | D = 52.388   | T = 19.368 | Tapered roller bearing                |
| FAG   | AK1380-1329          | d = 22.225  | D = 53.975   | T = 19.368 | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | K1280-1220           | d = 22.225  | D = 57.15    | T = 22.225 | Tapered roller bearing                |
| FAG   | KLM72849-LM72810     | d = 22.606  | D = 47       | T = 15.5   | Tapered roller bearing                |
| FAG   | K07093-07196         | d = 23.813  | D = 50.005   | T = 13.495 | Tapered roller bearing                |
| FAG   | K23092-23250-X       | d = 23.813  | D = 63.5     | T = 21.691 | Tapered roller bearing                |
| FAG   | K23092-23256         | d = 23.813  | D = 65.088   | T = 22.225 | Tapered roller bearing                |
| FAG   | K17098-17244         | d = 24.981  | D = 61.999   | T = 16.002 | Tapered roller bearing                |
| FAG   | 32905                | d = 25      | D = 42       | T = 12     | Tapered roller bearing                |
| FAG   | 32005-X              | d = 25      | D = 47       | T = 15     | Tapered roller bearing                |
| FAG   | 32005-X-H            | d = 25      | D = 47       | T = 15     | Tapered roller bearing                |
| FAG   | 32005-X-XL           | d = 25      | D = 47       | T = 15     | Tapered roller bearing                |
| FAG   | 32005-X-XL-P5        | d = 25      | D = 47       | T = 15     | Tapered roller bearing                |
| FAG   | 32005-XDY            | d = 25      | D = 47       | T = 15     | Tapered roller bearing                |
| FAG   | 33005                | d = 25      | D = 47       | T = 17     | Tapered roller bearing                |
| FAG   | 33005-H              | d = 25      | D = 47       | T = 17     | Tapered roller bearing                |
| FAG   | T4CB025              | d = 25      | D = 50       | T = 14     | Tapered roller bearing                |
| FAG   | T2CC025              | d = 25      | D = 50       | T = 17     | Tapered roller bearing                |
| FAG   | 30205-A              | d = 25      | D = 52       | T = 16.25  | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 30205-DY             | d = 25      | D = 52       | T = 16.25  | Tapered roller bearing                |
| FAG   | 30205-DY-W61C        | d = 25      | D = 52       | T = 16.25  | Tapered roller bearing                |
| FAG   | 30205-H              | d = 25      | D = 52       | T = 16.25  | Tapered roller bearing                |
| FAG   | 30205-H>R            | d = 25      | D = 52       | T = 16.25  | Tapered roller bearing                |
| FAG   | 30205-XL             | d = 25      | D = 52       | T = 16.25  | Tapered roller bearing                |
| FAG   | 30205-XL-P5          | d = 25      | D = 52       | T = 16.25  | Tapered roller bearing                |
| FAG   | 32205-B              | d = 25      | D = 52       | T = 19.25  | Tapered roller bearing                |
| FAG   | 32205-B-TVP          | d = 25      | D = 52       | T = 19.25  | Tapered roller bearing                |
| FAG   | 32205-B-XL           | d = 25      | D = 52       | T = 19.25  | Tapered roller bearing                |
| FAG   | 32205-H              | d = 25      | D = 52       | T = 19.25  | Tapered roller bearing                |
| FAG   | 32205-XL             | d = 25      | D = 52       | T = 19.25  | Tapered roller bearing                |
| FAG   | 33205                | d = 25      | D = 52       | T = 22     | Tapered roller bearing                |
| FAG   | 33205-DY             | d = 25      | D = 52       | T = 22     | Tapered roller bearing                |
| FAG   | 33205-H              | d = 25      | D = 52       | T = 22     | Tapered roller bearing                |
| FAG   | T2EE025              | d = 25      | D = 58       | T = 26     | Tapered roller bearing                |
| FAG   | 30305-A              | d = 25      | D = 62       | T = 18.25  | Tapered roller bearing                |
| FAG   | 30305-DY             | d = 25      | D = 62       | T = 18.25  | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 30305-H              | d = 25      | D = 62       | T = 18.25  | Tapered roller bearing                |
| FAG   | 31305-A              | d = 25      | D = 62       | T = 18.25  | Tapered roller bearing                |
| FAG   | 31305-A-TVP          | d = 25      | D = 62       | T = 18.25  | Tapered roller bearing                |
| FAG   | 31305-H              | d = 25      | D = 62       | T = 18.25  | Tapered roller bearing                |
| FAG   | 32305-A              | d = 25      | D = 62       | T = 25.25  | Tapered roller bearing                |
| FAG   | 32305-A>A            | d = 25      | D = 62       | T = 25.25  | Tapered roller bearing                |
| FAG   | 32305-B              | d = 25      | D = 62       | T = 25.25  | Tapered roller bearing                |
| FAG   | 32305-DY             | d = 25      | D = 62       | T = 25.25  | Tapered roller bearing                |
| FAG   | 32305-H              | d = 25      | D = 62       | T = 25.25  | Tapered roller bearing                |
| KOYO  | 46T30305DJR/29.5     | d = 25      | D = 62       | T = 40     | Tapered roller bearing                |
| FAG   | KL44642-L44610       | d = 25.4    | D = 50.292   | T = 14.224 | Tapered roller bearing                |
| FAG   | KL44643-L44610       | d = 25.4    | D = 50.292   | T = 14.224 | Tapered roller bearing                |
| FAG   | K07100-07204         | d = 25.4    | D = 51.994   | T = 15.011 | Tapered roller bearing                |
| FAG   | K1780-1729           | d = 25.4    | D = 56.896   | T = 19.368 | Tapered roller bearing                |
| FAG   | K2382-2330           | d = 25.4    | D = 56.896   | T = 23.812 | Tapered roller bearing                |
| FAG   | K15578-15520         | d = 25.4    | D = 57.15    | T = 17.462 | Tapered roller bearing                |
| FAG   | K15578-15520-DY      | d = 25.4    | D = 57.15    | T = 17.462 | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | KM84548-M84510-DY    | d = 25.4    | D = 57.15    | T = 19.431 | Tapered roller bearing                |
| FAG   | KM86643-M86610       | d = 25.4    | D = 64.292   | T = 21.433 | Tapered roller bearing                |
| FAG   | K02473-02420         | d = 25.4    | D = 68.263   | T = 22.225 | Tapered roller bearing                |
| FAG   | K2682-2630           | d = 26.162  | D = 63.1     | T = 23.813 | Tapered roller bearing                |
| FAG   | KL44649-L44610       | d = 26.988  | D = 50.292   | T = 14.224 | Tapered roller bearing                |
| FAG   | KL44649-L44610-TVP   | d = 26.988  | D = 50.292   | T = 14.224 | Tapered roller bearing                |
| FAG   | KL44649-L44610-W215D | d = 26.988  | D = 50.292   | T = 14.224 | Tapered roller bearing                |
| FAG   | KL44649-L44610>A     | d = 26.988  | D = 50.292   | T = 14.224 | Tapered roller bearing                |
| FAG   | 329/28               | d = 28      | D = 45       | T = 12     | Tapered roller bearing                |
| FAG   | 320/28-X             | d = 28      | D = 52       | T = 16     | Tapered roller bearing                |
| FAG   | 320/28-X-P5          | d = 28      | D = 52       | T = 16     | Tapered roller bearing                |
| FAG   | 320/28-XDY           | d = 28      | D = 52       | T = 16     | Tapered roller bearing                |
| FAG   | 320/28-XDY-W60C      | d = 28      | D = 52       | T = 16     | Tapered roller bearing                |
| FAG   | T4CB028              | d = 28      | D = 55       | T = 15     | Tapered roller bearing                |
| FAG   | T2CD028              | d = 28      | D = 55       | T = 19     | Tapered roller bearing                |
| FAG   | 322/28-B             | d = 28      | D = 58       | T = 20.25  | Tapered roller bearing                |
| FAG   | 322/28-BDY           | d = 28      | D = 58       | T = 20.25  | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 332/28               | d = 28      | D = 58       | T = 24     | Tapered roller bearing                |
| FAG   | T2ED028              | d = 28      | D = 65       | T = 27     | Tapered roller bearing                |
| FAG   | K1985-1922           | d = 28.575  | D = 57.15    | T = 19.845 | Tapered roller bearing                |
| FAG   | K1985-1922-XL        | d = 28.575  | D = 57.15    | T = 19.845 | Tapered roller bearing                |
| FAG   | K1988-1922           | d = 28.575  | D = 57.15    | T = 19.845 | Tapered roller bearing                |
| FAG   | KLM67043-LM67010     | d = 28.575  | D = 59.131   | T = 15.875 | Tapered roller bearing                |
| FAG   | K1988-1931           | d = 28.575  | D = 60.325   | T = 19.845 | Tapered roller bearing                |
| FAG   | KM86647-M86610       | d = 28.575  | D = 64.292   | T = 21.433 | Tapered roller bearing                |
| FAG   | K2689-2631           | d = 28.575  | D = 66.421   | T = 23.812 | Tapered roller bearing                |
| FAG   | K26112-26283         | d = 28.575  | D = 71.999   | T = 18.999 | Tapered roller bearing                |
| FAG   | K43112-43312         | d = 28.575  | D = 79.375   | T = 25.4   | Tapered roller bearing                |
| FAG   | KL45449-L45410       | d = 29      | D = 50.292   | T = 14.224 | Tapered roller bearing                |
| FAG   | KL45449-L45410-DY    | d = 29      | D = 50.292   | T = 14.224 | Tapered roller bearing                |
| FAG   | AK2690-2631-XL-W60CS | d = 29.367  | D = 66.421   | T = 23.812 | Tapered roller bearing                |
| FAG   | 32906                | d = 30      | D = 47       | T = 12     | Tapered roller bearing                |
| FAG   | 32906-H              | d = 30      | D = 47       | T = 12     | Tapered roller bearing                |
| FAG   | 32006-X              | d = 30      | D = 55       | T = 17     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 32006-X-H            | d = 30      | D = 55       | T = 17     | Tapered roller bearing                |
| FAG   | 32006-X-P5           | d = 30      | D = 55       | T = 17     | Tapered roller bearing                |
| FAG   | 32006-X-TVP          | d = 30      | D = 55       | T = 17     | Tapered roller bearing                |
| FAG   | 32006-X-XL           | d = 30      | D = 55       | T = 17     | Tapered roller bearing                |
| FAG   | 32006-X-XL-P5        | d = 30      | D = 55       | T = 17     | Tapered roller bearing                |
| FAG   | 32006-XDY            | d = 30      | D = 55       | T = 17     | Tapered roller bearing                |
| FAG   | 33006                | d = 30      | D = 55       | T = 20     | Tapered roller bearing                |
| FAG   | 33006-H              | d = 30      | D = 55       | T = 20     | Tapered roller bearing                |
| FAG   | T2CD030              | d = 30      | D = 58       | T = 19     | Tapered roller bearing                |
| FAG   | T4CB030              | d = 30      | D = 60       | T = 17     | Tapered roller bearing                |
| FAG   | 30206-A              | d = 30      | D = 62       | T = 17.25  | Tapered roller bearing                |
| FAG   | 30206-A-P5           | d = 30      | D = 62       | T = 17.25  | Tapered roller bearing                |
| FAG   | 30206-A-TVP          | d = 30      | D = 62       | T = 17.25  | Tapered roller bearing                |
| FAG   | 30206-A-W60C         | d = 30      | D = 62       | T = 17.25  | Tapered roller bearing                |
| FAG   | 30206-DY             | d = 30      | D = 62       | T = 17.25  | Tapered roller bearing                |
| FAG   | 30206-H              | d = 30      | D = 62       | T = 17.25  | Tapered roller bearing                |
| FAG   | 30206-XL             | d = 30      | D = 62       | T = 17.25  | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | Z-543083.TR1         | d = 30      | D = 62       | T = 18     | Tapered roller bearing                |
| FAG   | 32206-A              | d = 30      | D = 62       | T = 21.25  | Tapered roller bearing                |
| FAG   | 32206-B-XL           | d = 30      | D = 62       | T = 21.25  | Tapered roller bearing                |
| FAG   | 32206-DY             | d = 30      | D = 62       | T = 21.25  | Tapered roller bearing                |
| FAG   | 32206-DY-W61C        | d = 30      | D = 62       | T = 21.25  | Tapered roller bearing                |
| FAG   | 32206-DY>A           | d = 30      | D = 62       | T = 21.25  | Tapered roller bearing                |
| FAG   | 32206-H              | d = 30      | D = 62       | T = 21.25  | Tapered roller bearing                |
| FAG   | 32206-XL             | d = 30      | D = 62       | T = 21.25  | Tapered roller bearing                |
| FAG   | 32206-XL-W60C        | d = 30      | D = 62       | T = 21.25  | Tapered roller bearing                |
| FAG   | 33206                | d = 30      | D = 62       | T = 25     | Tapered roller bearing                |
| FAG   | 33206-H              | d = 30      | D = 62       | T = 25     | Tapered roller bearing                |
| FAG   | 33206-XL             | d = 30      | D = 62       | T = 25     | Tapered roller bearing                |
| FAG   | T2EE030              | d = 30      | D = 68       | T = 29     | Tapered roller bearing                |
| FAG   | 30306-A              | d = 30      | D = 72       | T = 20.75  | Tapered roller bearing                |
| FAG   | 30306-A>A            | d = 30      | D = 72       | T = 20.75  | Tapered roller bearing                |
| FAG   | 30306-DY             | d = 30      | D = 72       | T = 20.75  | Tapered roller bearing                |
| FAG   | 30306-H              | d = 30      | D = 72       | T = 20.75  | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation  | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|-----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 30306-XL              | d = 30      | D = 72       | T = 20.75  | Tapered roller bearing                |
| FAG   | 31306-A               | d = 30      | D = 72       | T = 20.75  | Tapered roller bearing                |
| FAG   | 31306-H               | d = 30      | D = 72       | T = 20.75  | Tapered roller bearing                |
| FAG   | 32306-A               | d = 30      | D = 72       | T = 28.75  | Tapered roller bearing                |
| FAG   | 32306-B               | d = 30      | D = 72       | T = 28.75  | Tapered roller bearing                |
| FAG   | 32306-DY              | d = 30      | D = 72       | T = 28.75  | Tapered roller bearing                |
| FAG   | 32306-H               | d = 30      | D = 72       | T = 28.75  | Tapered roller bearing                |
| KOYO  | 46T30306DJR/31.5      | d = 30      | D = 72       | T = 45     | Tapered roller bearing                |
| FAG   | K14118-14283          | d = 30      | D = 72.085   | T = 22.385 | Tapered roller bearing                |
| FAG   | K08118-08231          | d = 30.162  | D = 58.738   | T = 14.684 | Tapered roller bearing                |
| FAG   | K08118-08231-XL       | d = 30.162  | D = 58.738   | T = 14.684 | Tapered roller bearing                |
| FAG   | KM86649-M86610        | d = 30.162  | D = 64.292   | T = 21.433 | Tapered roller bearing                |
| FAG   | KM86649-M86610-DY     | d = 30.162  | D = 64.292   | T = 21.433 | Tapered roller bearing                |
| FAG   | KM86649-M86610-W215FD | d = 30.162  | D = 64.292   | T = 21.433 | Tapered roller bearing                |
| FAG   | KM86649-M86610>A      | d = 30.162  | D = 64.292   | T = 21.433 | Tapered roller bearing                |
| FAG   | KM88043-M88010        | d = 30.162  | D = 68.262   | T = 22.225 | Tapered roller bearing                |
| FAG   | KM88043-M88010-DY     | d = 30.162  | D = 68.262   | T = 22.225 | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | KM88043-M88011       | d = 30.162  | D = 68.262   | T = 22.225 | Tapered roller bearing                |
| FAG   | K08125-08231         | d = 31.75   | D = 58.738   | T = 14.684 | Tapered roller bearing                |
| FAG   | KLM67047-LM67010     | d = 31.75   | D = 59.131   | T = 15.875 | Tapered roller bearing                |
| FAG   | KLM67048-LM67010     | d = 31.75   | D = 59.131   | T = 15.875 | Tapered roller bearing                |
| FAG   | KLM67048-LM67010>A   | d = 31.75   | D = 59.131   | T = 15.875 | Tapered roller bearing                |
| FAG   | KLM67049-A-LM67010   | d = 31.75   | D = 59.131   | T = 15.875 | Tapered roller bearing                |
| FAG   | KLM67048-LM67014     | d = 31.75   | D = 61.986   | T = 15.875 | Tapered roller bearing                |
| FAG   | AK2582-2520-XL-W60CS | d = 31.75   | D = 66.421   | T = 25.4   | Tapered roller bearing                |
| FAG   | KM88046-M88010-XL    | d = 31.75   | D = 68.262   | T = 22.225 | Tapered roller bearing                |
| FAG   | K2475-2420           | d = 31.75   | D = 68.263   | T = 22.225 | Tapered roller bearing                |
| FAG   | KHM88542-HM88510     | d = 31.75   | D = 73.025   | T = 29.37  | Tapered roller bearing                |
| FAG   | KHM88542-HM88510-TVP | d = 31.75   | D = 73.025   | T = 29.37  | Tapered roller bearing                |
| FAG   | KHM89440-HM89411     | d = 31.75   | D = 76.2     | T = 29.37  | Tapered roller bearing                |
| FAG   | KHM89440-HM89411-DY  | d = 31.75   | D = 76.2     | T = 29.37  | Tapered roller bearing                |
| FAG   | K43125-43312         | d = 31.75   | D = 79.375   | T = 25.4   | Tapered roller bearing                |
| FAG   | 329/32               | d = 32      | D = 52       | T = 14     | Tapered roller bearing                |
| FAG   | 320/32-X             | d = 32      | D = 58       | T = 17     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation   | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|------------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 320/32-X-XL            | d = 32      | D = 58       | T = 17     | Tapered roller bearing                |
| FAG   | 320/32-X>A             | d = 32      | D = 58       | T = 17     | Tapered roller bearing                |
| FAG   | T2CD032                | d = 32      | D = 62       | T = 21     | Tapered roller bearing                |
| FAG   | T4DB032                | d = 32      | D = 65       | T = 18     | Tapered roller bearing                |
| FAG   | 302/32                 | d = 32      | D = 65       | T = 18.25  | Tapered roller bearing                |
| FAG   | 332/32                 | d = 32      | D = 65       | T = 26     | Tapered roller bearing                |
| FAG   | T2ED032                | d = 32      | D = 72       | T = 29     | Tapered roller bearing                |
| FAG   | KM88048-M88010         | d = 33.338  | D = 68.262   | T = 22.225 | Tapered roller bearing                |
| FAG   | KM88048-M88010-DY-W61C | d = 33.338  | D = 68.262   | T = 22.225 | Tapered roller bearing                |
| FAG   | KM88048-M88010-XL      | d = 33.338  | D = 68.262   | T = 22.225 | Tapered roller bearing                |
| FAG   | KM88048-M88011         | d = 33.338  | D = 68.262   | T = 22.225 | Tapered roller bearing                |
| FAG   | KHM88547-HM88510       | d = 33.338  | D = 73.025   | T = 29.37  | Tapered roller bearing                |
| FAG   | K31590-31520           | d = 33.338  | D = 76.2     | T = 29.37  | Tapered roller bearing                |
| FAG   | K31590-31521           | d = 33.338  | D = 76.2     | T = 29.37  | Tapered roller bearing                |
| FAG   | KLM48548-A-LM48510     | d = 34.925  | D = 65.088   | T = 18.034 | Tapered roller bearing                |
| FAG   | KLM48548-LM48510       | d = 34.925  | D = 65.088   | T = 18.034 | Tapered roller bearing                |
| FAG   | KLM48548-LM48510-DY    | d = 34.925  | D = 65.088   | T = 18.034 | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | KLM48549-LM48510     | d = 34.925  | D = 65.088   | T = 18.034 | Tapered roller bearing                |
| FAG   | KLM48549-X-LM48510   | d = 34.925  | D = 65.088   | T = 18.034 | Tapered roller bearing                |
| FAG   | KLM48548-LM48511     | d = 34.925  | D = 65.088   | T = 20.32  | Tapered roller bearing                |
| FAG   | KM38549-M38510       | d = 34.925  | D = 66.675   | T = 20.638 | Tapered roller bearing                |
| FAG   | K14137-A-14276       | d = 34.925  | D = 69.012   | T = 19.845 | Tapered roller bearing                |
| FAG   | K14138-A-14274-DY    | d = 34.925  | D = 69.012   | T = 19.845 | Tapered roller bearing                |
| FAG   | K14138-A-14276       | d = 34.925  | D = 69.012   | T = 19.845 | Tapered roller bearing                |
| FAG   | KHM88649-HM88610     | d = 34.925  | D = 72.233   | T = 25.4   | Tapered roller bearing                |
| FAG   | K2878-2820           | d = 34.925  | D = 73.025   | T = 22.225 | Tapered roller bearing                |
| FAG   | K2878-2821           | d = 34.925  | D = 73.025   | T = 22.225 | Tapered roller bearing                |
| FAG   | K25877-25820-DY      | d = 34.925  | D = 73.025   | T = 23.812 | Tapered roller bearing                |
| FAG   | K25877-25821-DY      | d = 34.925  | D = 73.025   | T = 23.812 | Tapered roller bearing                |
| FAG   | K25877-25821-XL      | d = 34.925  | D = 73.025   | T = 23.812 | Tapered roller bearing                |
| FAG   | K25877-25820         | d = 34.925  | D = 73.025   | T = 23.813 | Tapered roller bearing                |
| FAG   | K25878-25820         | d = 34.925  | D = 73.025   | T = 23.813 | Tapered roller bearing                |
| FAG   | K23690-23620         | d = 34.925  | D = 73.025   | T = 26.988 | Tapered roller bearing                |
| FAG   | K28137-28300         | d = 34.925  | D = 76.2     | T = 20.635 | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation   | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|------------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | K31593-31520           | d = 34.925  | D = 76.2     | T = 29.37  | Tapered roller bearing                |
| FAG   | KHM89446-HM89410-DY    | d = 34.925  | D = 76.2     | T = 29.37  | Tapered roller bearing                |
| FAG   | K3379-3328             | d = 34.925  | D = 84.138   | T = 29.37  | Tapered roller bearing                |
| FAG   | AK3872-3820            | d = 34.925  | D = 85.725   | T = 30.162 | Tapered roller bearing                |
| FAG   | KLM78349-LM78310-A     | d = 34.987  | D = 61.973   | T = 16.7   | Tapered roller bearing                |
| FAG   | KLM78349-LM78310-A-TVP | d = 34.987  | D = 61.973   | T = 16.7   | Tapered roller bearing                |
| FAG   | KLM78349-LM78310-TVP   | d = 34.987  | D = 61.973   | T = 16.7   | Tapered roller bearing                |
| FAG   | KLM78349-A-LM78310-C   | d = 34.987  | D = 61.973   | T = 18     | Tapered roller bearing                |
| FAG   | KL68149-L68110         | d = 34.988  | D = 59.131   | T = 15.875 | Tapered roller bearing                |
| FAG   | KL68149-L68110-Q3      | d = 34.988  | D = 59.131   | T = 15.875 | Tapered roller bearing                |
| FAG   | KL68149-L68111         | d = 34.988  | D = 59.974   | T = 15.875 | Tapered roller bearing                |
| FAG   | 32907                  | d = 35      | D = 55       | T = 14     | Tapered roller bearing                |
| FAG   | 32907-H                | d = 35      | D = 55       | T = 14     | Tapered roller bearing                |
| FAG   | 32007-X                | d = 35      | D = 62       | T = 18     | Tapered roller bearing                |
| FAG   | 32007-X-H              | d = 35      | D = 62       | T = 18     | Tapered roller bearing                |
| FAG   | 32007-XDY              | d = 35      | D = 62       | T = 18     | Tapered roller bearing                |
| FAG   | 32007-XDY-XL           | d = 35      | D = 62       | T = 18     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 32007-XDY-XL-P5      | d = 35      | D = 62       | T = 18     | Tapered roller bearing                |
| FAG   | 33007                | d = 35      | D = 62       | T = 21     | Tapered roller bearing                |
| FAG   | 33007-H              | d = 35      | D = 62       | T = 21     | Tapered roller bearing                |
| FAG   | 33007-XL             | d = 35      | D = 62       | T = 21     | Tapered roller bearing                |
| FAG   | T2DD035              | d = 35      | D = 68       | T = 23     | Tapered roller bearing                |
| FAG   | T4DB035              | d = 35      | D = 70       | T = 19     | Tapered roller bearing                |
| FAG   | 30207-A              | d = 35      | D = 72       | T = 18.25  | Tapered roller bearing                |
| FAG   | 30207-DY             | d = 35      | D = 72       | T = 18.25  | Tapered roller bearing                |
| FAG   | 30207-H              | d = 35      | D = 72       | T = 18.25  | Tapered roller bearing                |
| FAG   | 30207-XL             | d = 35      | D = 72       | T = 18.25  | Tapered roller bearing                |
| FAG   | 32207-A              | d = 35      | D = 72       | T = 24.25  | Tapered roller bearing                |
| FAG   | 32207-B-XL           | d = 35      | D = 72       | T = 24.25  | Tapered roller bearing                |
| FAG   | 32207-DY             | d = 35      | D = 72       | T = 24.25  | Tapered roller bearing                |
| FAG   | 32207-H              | d = 35      | D = 72       | T = 24.25  | Tapered roller bearing                |
| FAG   | 32207-XL             | d = 35      | D = 72       | T = 24.25  | Tapered roller bearing                |
| FAG   | 33207                | d = 35      | D = 72       | T = 28     | Tapered roller bearing                |
| FAG   | 33207-DY             | d = 35      | D = 72       | T = 28     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 33207-H              | d = 35      | D = 72       | T = 28     | Tapered roller bearing                |
| FAG   | 33207-XL             | d = 35      | D = 72       | T = 28     | Tapered roller bearing                |
| FAG   | T2EE035              | d = 35      | D = 78       | T = 33     | Tapered roller bearing                |
| FAG   | AK339-332            | d = 35      | D = 80       | T = 21     | Tapered roller bearing                |
| FAG   | 30307-A              | d = 35      | D = 80       | T = 22.75  | Tapered roller bearing                |
| FAG   | 30307-A>A            | d = 35      | D = 80       | T = 22.75  | Tapered roller bearing                |
| FAG   | 30307-DY             | d = 35      | D = 80       | T = 22.75  | Tapered roller bearing                |
| FAG   | 30307-H              | d = 35      | D = 80       | T = 22.75  | Tapered roller bearing                |
| FAG   | 31307-A              | d = 35      | D = 80       | T = 22.75  | Tapered roller bearing                |
| FAG   | 31307-A>A            | d = 35      | D = 80       | T = 22.75  | Tapered roller bearing                |
| FAG   | 31307-DY             | d = 35      | D = 80       | T = 22.75  | Tapered roller bearing                |
| FAG   | 31307-DY-W60C        | d = 35      | D = 80       | T = 22.75  | Tapered roller bearing                |
| FAG   | 31307-H              | d = 35      | D = 80       | T = 22.75  | Tapered roller bearing                |
| FAG   | 32307-A              | d = 35      | D = 80       | T = 32.75  | Tapered roller bearing                |
| FAG   | 32307-A>B            | d = 35      | D = 80       | T = 32.75  | Tapered roller bearing                |
| FAG   | 32307-B              | d = 35      | D = 80       | T = 32.75  | Tapered roller bearing                |
| FAG   | 32307-B>A            | d = 35      | D = 80       | T = 32.75  | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 32307-DY             | d = 35      | D = 80       | T = 32.75  | Tapered roller bearing                |
| FAG   | 32307-H              | d = 35      | D = 80       | T = 32.75  | Tapered roller bearing                |
| FAG   | 32307-XL             | d = 35      | D = 80       | T = 32.75  | Tapered roller bearing                |
| KOYO  | 46T30307DJR/35.5     | d = 35      | D = 80       | T = 51     | Tapered roller bearing                |
| FAG   | KHM88648-HM88610     | d = 35.717  | D = 72.232   | T = 25.4   | Tapered roller bearing                |
| FAG   | K16143-16284         | d = 36.512  | D = 72.238   | T = 20.638 | Tapered roller bearing                |
| FAG   | KHM89448-HM89410     | d = 36.512  | D = 76.2     | T = 29.37  | Tapered roller bearing                |
| FAG   | K44143-44348         | d = 36.512  | D = 88.5     | T = 25.4   | Tapered roller bearing                |
| FAG   | K31597-31520         | d = 36.513  | D = 76.2     | T = 29.37  | Tapered roller bearing                |
| FAG   | KLM29748-LM29710     | d = 38.1    | D = 65.088   | T = 18.034 | Tapered roller bearing                |
| FAG   | KLM29749-LM29710     | d = 38.1    | D = 65.088   | T = 18.034 | Tapered roller bearing                |
| FAG   | K19150-19268         | d = 38.1    | D = 68.262   | T = 15.875 | Tapered roller bearing                |
| FAG   | K13685-13620         | d = 38.1    | D = 69.012   | T = 19.05  | Tapered roller bearing                |
| FAG   | K13685-13621         | d = 38.1    | D = 69.012   | T = 19.05  | Tapered roller bearing                |
| FAG   | K13687-13621         | d = 38.1    | D = 69.012   | T = 19.05  | Tapered roller bearing                |
| FAG   | K13687-13624         | d = 38.1    | D = 69.969   | T = 21.996 | Tapered roller bearing                |
| FAG   | K19150-19281         | d = 38.1    | D = 71.438   | T = 15.875 | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | K19150-19281-XL      | d = 38.1    | D = 71.438   | T = 15.875 | Tapered roller bearing                |
| FAG   | K16150-16282         | d = 38.1    | D = 72       | T = 19     | Tapered roller bearing                |
| FAG   | K16150-16284         | d = 38.1    | D = 72.238   | T = 20.638 | Tapered roller bearing                |
| FAG   | AK2776-2720          | d = 38.1    | D = 76.2     | T = 23.812 | Tapered roller bearing                |
| FAG   | AK2788-2720          | d = 38.1    | D = 76.2     | T = 23.812 | Tapered roller bearing                |
| FAG   | AK2788-2729-XL       | d = 38.1    | D = 76.2     | T = 23.812 | Tapered roller bearing                |
| FAG   | K3490-3420           | d = 38.1    | D = 79.375   | T = 29.37  | Tapered roller bearing                |
| FAG   | K27880-27820         | d = 38.1    | D = 80.035   | T = 24.608 | Tapered roller bearing                |
| FAG   | K25572-25520         | d = 38.1    | D = 82.931   | T = 23.812 | Tapered roller bearing                |
| FAG   | AK3876-3820          | d = 38.1    | D = 85.725   | T = 30.162 | Tapered roller bearing                |
| FAG   | K4375-4335           | d = 38.1    | D = 90.488   | T = 39.688 | Tapered roller bearing                |
| FAG   | K53150-53375         | d = 38.1    | D = 95.25    | T = 30.958 | Tapered roller bearing                |
| FAG   | AK2789-2729          | d = 39.688  | D = 76.2     | T = 23.812 | Tapered roller bearing                |
| FAG   | K3382-3325           | d = 39.688  | D = 79.974   | T = 29.37  | Tapered roller bearing                |
| FAG   | K3386-3325           | d = 39.688  | D = 79.974   | T = 29.37  | Tapered roller bearing                |
| FAG   | K3386-3320           | d = 39.688  | D = 80.167   | T = 29.37  | Tapered roller bearing                |
| FAG   | K44158-44348         | d = 39.688  | D = 88.5     | T = 25.4   | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 32908                | d = 40      | D = 62       | T = 15     | Tapered roller bearing                |
| FAG   | 32908-H              | d = 40      | D = 62       | T = 15     | Tapered roller bearing                |
| FAG   | 32008-X-H            | d = 40      | D = 68       | T = 19     | Tapered roller bearing                |
| FAG   | 32008-X-XL           | d = 40      | D = 68       | T = 19     | Tapered roller bearing                |
| FAG   | 32008-X-XL-P5        | d = 40      | D = 68       | T = 19     | Tapered roller bearing                |
| FAG   | 32008-X-XL-S1        | d = 40      | D = 68       | T = 19     | Tapered roller bearing                |
| FAG   | 32008-X-XL-W215FD    | d = 40      | D = 68       | T = 19     | Tapered roller bearing                |
| FAG   | 32008-XA             | d = 40      | D = 68       | T = 19     | Tapered roller bearing                |
| FAG   | 32008-XA-TVP         | d = 40      | D = 68       | T = 19     | Tapered roller bearing                |
| FAG   | 32008-XDY            | d = 40      | D = 68       | T = 19     | Tapered roller bearing                |
| FAG   | 33008                | d = 40      | D = 68       | T = 22     | Tapered roller bearing                |
| FAG   | 33008-H              | d = 40      | D = 68       | T = 22     | Tapered roller bearing                |
| FAG   | 33008-XL             | d = 40      | D = 68       | T = 22     | Tapered roller bearing                |
| FAG   | T4CB040              | d = 40      | D = 75       | T = 19     | Tapered roller bearing                |
| FAG   | T2CD040              | d = 40      | D = 75       | T = 24     | Tapered roller bearing                |
| FAG   | 33108                | d = 40      | D = 75       | T = 26     | Tapered roller bearing                |
| FAG   | 33108-DY             | d = 40      | D = 75       | T = 26     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 33108-H              | d = 40      | D = 75       | T = 26     | Tapered roller bearing                |
| FAG   | 33108-W60C           | d = 40      | D = 75       | T = 26     | Tapered roller bearing                |
| FAG   | 33108-XL             | d = 40      | D = 75       | T = 26     | Tapered roller bearing                |
| FAG   | 30208-A              | d = 40      | D = 80       | T = 19.75  | Tapered roller bearing                |
| FAG   | 30208-A-P5           | d = 40      | D = 80       | T = 19.75  | Tapered roller bearing                |
| FAG   | 30208-A>A            | d = 40      | D = 80       | T = 19.75  | Tapered roller bearing                |
| FAG   | 30208-DY             | d = 40      | D = 80       | T = 19.75  | Tapered roller bearing                |
| FAG   | 30208-H              | d = 40      | D = 80       | T = 19.75  | Tapered roller bearing                |
| FAG   | 30208-XL             | d = 40      | D = 80       | T = 19.75  | Tapered roller bearing                |
| FAG   | 32208-B              | d = 40      | D = 80       | T = 24.75  | Tapered roller bearing                |
| FAG   | 32208-B-XL           | d = 40      | D = 80       | T = 24.75  | Tapered roller bearing                |
| FAG   | 32208-DY             | d = 40      | D = 80       | T = 24.75  | Tapered roller bearing                |
| FAG   | 32208-H              | d = 40      | D = 80       | T = 24.75  | Tapered roller bearing                |
| FAG   | 32208-XL             | d = 40      | D = 80       | T = 24.75  | Tapered roller bearing                |
| FAG   | T5DD040              | d = 40      | D = 80       | T = 27     | Tapered roller bearing                |
| FAG   | 33208                | d = 40      | D = 80       | T = 32     | Tapered roller bearing                |
| FAG   | 33208-H              | d = 40      | D = 80       | T = 32     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 33208-XL             | d = 40      | D = 80       | T = 32     | Tapered roller bearing                |
| KOYO  | 46T30208JR/37.5      | d = 40      | D = 80       | T = 45     | Tapered roller bearing                |
| KOYO  | 46T32208JR/43.5      | d = 40      | D = 80       | T = 55     | Tapered roller bearing                |
| FAG   | T2EE040              | d = 40      | D = 85       | T = 33     | Tapered roller bearing                |
| FAG   | 30308-A              | d = 40      | D = 90       | T = 25.25  | Tapered roller bearing                |
| FAG   | 30308-A-TVP          | d = 40      | D = 90       | T = 25.25  | Tapered roller bearing                |
| FAG   | 30308-DY             | d = 40      | D = 90       | T = 25.25  | Tapered roller bearing                |
| FAG   | 30308-H              | d = 40      | D = 90       | T = 25.25  | Tapered roller bearing                |
| FAG   | 30308-XL             | d = 40      | D = 90       | T = 25.25  | Tapered roller bearing                |
| FAG   | 31308-A              | d = 40      | D = 90       | T = 25.25  | Tapered roller bearing                |
| FAG   | 31308-DY-XL          | d = 40      | D = 90       | T = 25.25  | Tapered roller bearing                |
| FAG   | 31308-H              | d = 40      | D = 90       | T = 25.25  | Tapered roller bearing                |
| FAG   | 31308-XL             | d = 40      | D = 90       | T = 25.25  | Tapered roller bearing                |
| FAG   | 31308-XL-W60B        | d = 40      | D = 90       | T = 25.25  | Tapered roller bearing                |
| FAG   | 32308-A              | d = 40      | D = 90       | T = 35.25  | Tapered roller bearing                |
| FAG   | 32308-B              | d = 40      | D = 90       | T = 35.25  | Tapered roller bearing                |
| FAG   | 32308-B-XL           | d = 40      | D = 90       | T = 35.25  | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation  | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|-----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 32308-DY              | d = 40      | D = 90       | T = 35.25  | Tapered roller bearing                |
| FAG   | 32308-H               | d = 40      | D = 90       | T = 35.25  | Tapered roller bearing                |
| FAG   | 32308-XL              | d = 40      | D = 90       | T = 35.25  | Tapered roller bearing                |
| KOYO  | 46T30308DJR/39.5      | d = 40      | D = 90       | T = 56     | Tapered roller bearing                |
| KOYO  | 46T30308JR/45.5       | d = 40      | D = 90       | T = 56     | Tapered roller bearing                |
| FAG   | KHM801349-HM801310    | d = 40.483  | D = 82.55    | T = 29.37  | Tapered roller bearing                |
| FAG   | KLM300849-LM300811    | d = 40.987  | D = 67.975   | T = 17.5   | Tapered roller bearing                |
| FAG   | KLM300849-LM300816    | d = 40.987  | D = 78       | T = 17.5   | Tapered roller bearing                |
| FAG   | KLM300848-LM300811-DY | d = 41.275  | D = 67.975   | T = 17.5   | Tapered roller bearing                |
| FAG   | KLM501349-LM501310    | d = 41.275  | D = 73.431   | T = 19.558 | Tapered roller bearing                |
| FAG   | KLM501349-LM501310-XL | d = 41.275  | D = 73.431   | T = 19.558 | Tapered roller bearing                |
| FAG   | K24780-24720          | d = 41.275  | D = 76.2     | T = 22.225 | Tapered roller bearing                |
| FAG   | K336-332-A            | d = 41.275  | D = 80       | T = 24.176 | Tapered roller bearing                |
| FAG   | K26882-26820          | d = 41.275  | D = 80.167   | T = 25.4   | Tapered roller bearing                |
| FAG   | K26882-26821          | d = 41.275  | D = 80.167   | T = 29.37  | Tapered roller bearing                |
| FAG   | AK3877-3820           | d = 41.275  | D = 85.725   | T = 30.162 | Tapered roller bearing                |
| FAG   | AK3880-3820           | d = 41.275  | D = 85.725   | T = 30.162 | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation       | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | K3585-3525-H               | d = 41.275  | D = 87.313   | T = 30.163 | Tapered roller bearing                |
| FAG   | K419-414                   | d = 41.275  | D = 88.5     | T = 26.988 | Tapered roller bearing                |
| FAG   | KHM803146-HM803110         | d = 41.275  | D = 88.9     | T = 30.162 | Tapered roller bearing                |
| FAG   | KHM803146-HM803110-DY      | d = 41.275  | D = 88.9     | T = 30.162 | Tapered roller bearing                |
| FAG   | KHM803146-HM803110-DY-W61C | d = 41.275  | D = 88.9     | T = 30.162 | Tapered roller bearing                |
| FAG   | K365-A-362                 | d = 41.275  | D = 90       | T = 20     | Tapered roller bearing                |
| FAG   | K46162-46368               | d = 41.275  | D = 93.662   | T = 31.75  | Tapered roller bearing                |
| FAG   | KHM804840-HM804810         | d = 41.275  | D = 95.25    | T = 30.162 | Tapered roller bearing                |
| FAG   | K59162-59412               | d = 41.275  | D = 104.775  | T = 36.512 | Tapered roller bearing                |
| FAG   | K22168-22325               | d = 42.862  | D = 82.55    | T = 19.842 | Tapered roller bearing                |
| FAG   | K22168-22325-XL            | d = 42.862  | D = 82.55    | T = 19.842 | Tapered roller bearing                |
| FAG   | K22780-22720               | d = 42.862  | D = 82.55    | T = 26.195 | Tapered roller bearing                |
| FAG   | K25577-25520               | d = 42.875  | D = 82.931   | T = 23.812 | Tapered roller bearing                |
| FAG   | KLL103049-LL103010         | d = 44.45   | D = 71.438   | T = 12.7   | Tapered roller bearing                |
| FAG   | KL102849-L102810           | d = 44.45   | D = 73.025   | T = 18.258 | Tapered roller bearing                |
| FAG   | K18685-18620               | d = 44.45   | D = 79.375   | T = 17.463 | Tapered roller bearing                |
| FAG   | K17888-17830               | d = 44.45   | D = 79.375   | T = 31.354 | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation  | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|-----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | K35176-35326          | d = 44.45   | D = 82.931   | T = 22.225 | Tapered roller bearing                |
| FAG   | K25580-25520          | d = 44.45   | D = 82.931   | T = 23.812 | Tapered roller bearing                |
| FAG   | K25580-25520-DY-XL    | d = 44.45   | D = 82.931   | T = 23.812 | Tapered roller bearing                |
| FAG   | K25581-25520-H        | d = 44.45   | D = 82.931   | T = 23.812 | Tapered roller bearing                |
| FAG   | K25580-25522-DY       | d = 44.45   | D = 83.058   | T = 23.876 | Tapered roller bearing                |
| FAG   | KHM803149-HM803110-H  | d = 44.45   | D = 88.9     | T = 30.162 | Tapered roller bearing                |
| FAG   | KHM803149-HM803110-XL | d = 44.45   | D = 88.9     | T = 30.162 | Tapered roller bearing                |
| FAG   | K3782-3720            | d = 44.45   | D = 93.264   | T = 30.162 | Tapered roller bearing                |
| FAG   | K3782-3720-DY         | d = 44.45   | D = 93.264   | T = 30.162 | Tapered roller bearing                |
| FAG   | K3782-3720-XL         | d = 44.45   | D = 93.264   | T = 30.162 | Tapered roller bearing                |
| FAG   | AK33885-33822-XL      | d = 44.45   | D = 95.25    | T = 27.783 | Tapered roller bearing                |
| FAG   | K33885-33821          | d = 44.45   | D = 95.25    | T = 27.783 | Tapered roller bearing                |
| FAG   | K33885-33822          | d = 44.45   | D = 95.25    | T = 27.783 | Tapered roller bearing                |
| FAG   | KHM804842-HM804810    | d = 44.45   | D = 95.25    | T = 30.162 | Tapered roller bearing                |
| FAG   | KHM804843-HM804810    | d = 44.45   | D = 95.25    | T = 30.162 | Tapered roller bearing                |
| FAG   | K53178-53377          | d = 44.45   | D = 95.25    | T = 30.958 | Tapered roller bearing                |
| FAG   | KHM903249-HM903210    | d = 44.45   | D = 95.25    | T = 30.958 | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | K49576-49520         | d = 44.45   | D = 101.6    | T = 31.75  | Tapered roller bearing                |
| FAG   | AK527-522            | d = 44.45   | D = 101.6    | T = 34.925 | Tapered roller bearing                |
| FAG   | K527-522             | d = 44.45   | D = 101.6    | T = 34.925 | Tapered roller bearing                |
| FAG   | K59175-59412         | d = 44.45   | D = 104.775  | T = 36.512 | Tapered roller bearing                |
| FAG   | K460-453-A           | d = 44.45   | D = 107.95   | T = 27.783 | Tapered roller bearing                |
| FAG   | K535-532-A           | d = 44.45   | D = 111.125  | T = 38.1   | Tapered roller bearing                |
| FAG   | K6277-6220           | d = 44.45   | D = 127      | T = 50.8   | Tapered roller bearing                |
| FAG   | K25584-25520-DY-W61C | d = 44.983  | D = 82.931   | T = 23.812 | Tapered roller bearing                |
| FAG   | 32909-H              | d = 45      | D = 68       | T = 15     | Tapered roller bearing                |
| FAG   | 32009-X-H            | d = 45      | D = 75       | T = 20     | Tapered roller bearing                |
| FAG   | 32009-X-H>R          | d = 45      | D = 75       | T = 20     | Tapered roller bearing                |
| FAG   | 32009-X-XL           | d = 45      | D = 75       | T = 20     | Tapered roller bearing                |
| FAG   | 32009-X-XL-P5        | d = 45      | D = 75       | T = 20     | Tapered roller bearing                |
| FAG   | 32009-X-XL-W60B      | d = 45      | D = 75       | T = 20     | Tapered roller bearing                |
| FAG   | 32009-X-XL-W60C      | d = 45      | D = 75       | T = 20     | Tapered roller bearing                |
| FAG   | 32009-XA             | d = 45      | D = 75       | T = 20     | Tapered roller bearing                |
| FAG   | 32009-XDY            | d = 45      | D = 75       | T = 20     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 33009                | d = 45      | D = 75       | T = 24     | Tapered roller bearing                |
| FAG   | 33009-H              | d = 45      | D = 75       | T = 24     | Tapered roller bearing                |
| FAG   | 33009-XL             | d = 45      | D = 75       | T = 24     | Tapered roller bearing                |
| FAG   | T2CD045              | d = 45      | D = 80       | T = 24     | Tapered roller bearing                |
| FAG   | 33109                | d = 45      | D = 80       | T = 26     | Tapered roller bearing                |
| FAG   | 33109-H              | d = 45      | D = 80       | T = 26     | Tapered roller bearing                |
| FAG   | 33109>A              | d = 45      | D = 80       | T = 26     | Tapered roller bearing                |
| FAG   | 30209-A              | d = 45      | D = 85       | T = 20.75  | Tapered roller bearing                |
| FAG   | 30209-DY             | d = 45      | D = 85       | T = 20.75  | Tapered roller bearing                |
| FAG   | 30209-H              | d = 45      | D = 85       | T = 20.75  | Tapered roller bearing                |
| FAG   | 30209-XL-P5          | d = 45      | D = 85       | T = 20.75  | Tapered roller bearing                |
| FAG   | T4DB045              | d = 45      | D = 85       | T = 21     | Tapered roller bearing                |
| FAG   | 32209-A              | d = 45      | D = 85       | T = 24.75  | Tapered roller bearing                |
| FAG   | 32209-B              | d = 45      | D = 85       | T = 24.75  | Tapered roller bearing                |
| FAG   | 32209-B-XL           | d = 45      | D = 85       | T = 24.75  | Tapered roller bearing                |
| FAG   | 32209-DY             | d = 45      | D = 85       | T = 24.75  | Tapered roller bearing                |
| FAG   | 32209-H              | d = 45      | D = 85       | T = 24.75  | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 32209-XL             | d = 45      | D = 85       | T = 24.75  | Tapered roller bearing                |
| FAG   | 32209-XL-W60C        | d = 45      | D = 85       | T = 24.75  | Tapered roller bearing                |
| FAG   | 33209                | d = 45      | D = 85       | T = 32     | Tapered roller bearing                |
| FAG   | 33209-H              | d = 45      | D = 85       | T = 32     | Tapered roller bearing                |
| FAG   | 33209>A              | d = 45      | D = 85       | T = 32     | Tapered roller bearing                |
| KOYO  | 46T30209JR/37.5      | d = 45      | D = 85       | T = 47     | Tapered roller bearing                |
| KOYO  | 46T32209JR-1/43.5    | d = 45      | D = 85       | T = 55     | Tapered roller bearing                |
| FAG   | T5ED045              | d = 45      | D = 90       | T = 32     | Tapered roller bearing                |
| FAG   | T7FC045-XL           | d = 45      | D = 95       | T = 29     | Tapered roller bearing                |
| FAG   | T7FC045-XL-S1        | d = 45      | D = 95       | T = 29     | Tapered roller bearing                |
| FAG   | T7FC045-XL>B         | d = 45      | D = 95       | T = 29     | Tapered roller bearing                |
| FAG   | T2ED045              | d = 45      | D = 95       | T = 36     | Tapered roller bearing                |
| FAG   | 30309-A              | d = 45      | D = 100      | T = 27.25  | Tapered roller bearing                |
| FAG   | 30309-A>A            | d = 45      | D = 100      | T = 27.25  | Tapered roller bearing                |
| FAG   | 30309-DY             | d = 45      | D = 100      | T = 27.25  | Tapered roller bearing                |
| FAG   | 30309-H              | d = 45      | D = 100      | T = 27.25  | Tapered roller bearing                |
| FAG   | 30309-XL             | d = 45      | D = 100      | T = 27.25  | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation  | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|-----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 31309-DY              | d = 45      | D = 100      | T = 27.25  | Tapered roller bearing                |
| FAG   | 31309-H               | d = 45      | D = 100      | T = 27.25  | Tapered roller bearing                |
| FAG   | 31309-XL              | d = 45      | D = 100      | T = 27.25  | Tapered roller bearing                |
| FAG   | 31309-XL-P5           | d = 45      | D = 100      | T = 27.25  | Tapered roller bearing                |
| FAG   | 31309-XL>B            | d = 45      | D = 100      | T = 27.25  | Tapered roller bearing                |
| FAG   | 32309-A               | d = 45      | D = 100      | T = 38.25  | Tapered roller bearing                |
| FAG   | 32309-A-P5            | d = 45      | D = 100      | T = 38.25  | Tapered roller bearing                |
| FAG   | 32309-B-XL            | d = 45      | D = 100      | T = 38.25  | Tapered roller bearing                |
| FAG   | 32309-BA              | d = 45      | D = 100      | T = 38.25  | Tapered roller bearing                |
| FAG   | 32309-BA>A            | d = 45      | D = 100      | T = 38.25  | Tapered roller bearing                |
| FAG   | 32309-H               | d = 45      | D = 100      | T = 38.25  | Tapered roller bearing                |
| KOYO  | 46T30309DJR/41.5      | d = 45      | D = 100      | T = 60     | Tapered roller bearing                |
| KOYO  | 46T30309JR/49.5       | d = 45      | D = 100      | T = 60     | Tapered roller bearing                |
| FAG   | K17887-17831          | d = 45.23   | D = 79.985   | T = 19.842 | Tapered roller bearing                |
| FAG   | K3586-3525            | d = 45.237  | D = 87.313   | T = 30.162 | Tapered roller bearing                |
| FAG   | KLM102949-LM102910    | d = 45.242  | D = 73.431   | T = 19.558 | Tapered roller bearing                |
| FAG   | KLM102949-LM102910-DY | d = 45.242  | D = 73.431   | T = 19.558 | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation  | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|-----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | KLM603049-AS-LM603011 | d = 45.242  | D = 77.788   | T = 19.842 | Tapered roller bearing                |
| FAG   | KLM603049-LM603011    | d = 45.242  | D = 77.788   | T = 19.842 | Tapered roller bearing                |
| FAG   | KLM603049-LM603011>A  | d = 45.242  | D = 77.788   | T = 19.842 | Tapered roller bearing                |
| FAG   | KLM603049-LM603012    | d = 45.242  | D = 77.788   | T = 21.43  | Tapered roller bearing                |
| FAG   | KLM603049-LM603014    | d = 45.242  | D = 80       | T = 19.842 | Tapered roller bearing                |
| FAG   | K25590-25520          | d = 45.618  | D = 82.931   | T = 23.812 | Tapered roller bearing                |
| FAG   | K25590-25520-H        | d = 45.618  | D = 82.931   | T = 23.812 | Tapered roller bearing                |
| FAG   | K25590-25520>A        | d = 45.618  | D = 82.931   | T = 23.812 | Tapered roller bearing                |
| FAG   | K25590-25523          | d = 45.618  | D = 82.931   | T = 26.988 | Tapered roller bearing                |
| FAG   | K25590-25522          | d = 45.618  | D = 83.058   | T = 23.877 | Tapered roller bearing                |
| FAG   | KLM503349-LM503310-DY | d = 45.987  | D = 74.975   | T = 18     | Tapered roller bearing                |
| FAG   | KLM503349-LM503310-Q3 | d = 45.987  | D = 74.975   | T = 18     | Tapered roller bearing                |
| FAG   | KLM503349-A-LM503310  | d = 45.987  | D = 74.985   | T = 18     | Tapered roller bearing                |
| FAG   | KLM503349-LM503310    | d = 45.987  | D = 74.985   | T = 18     | Tapered roller bearing                |
| FAG   | KHM204049-HM204010    | d = 45.987  | D = 90.975   | T = 32     | Tapered roller bearing                |
| FAG   | K18690-18620          | d = 46.038  | D = 79.375   | T = 17.463 | Tapered roller bearing                |
| FAG   | K13181-13318          | d = 46.038  | D = 80.963   | T = 19.05  | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation       | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | K2984-2924                 | d = 46.038  | D = 85.001   | T = 25.4   | Tapered roller bearing                |
| FAG   | K436-432                   | d = 46.038  | D = 95.25    | T = 27.783 | Tapered roller bearing                |
| FAG   | KM804048-M804010           | d = 47.625  | D = 88.9     | T = 25.4   | Tapered roller bearing                |
| FAG   | KM804049-M804010-XL-W215FD | d = 47.625  | D = 88.9     | T = 25.4   | Tapered roller bearing                |
| FAG   | KHM804846-HM804810         | d = 47.625  | D = 95.25    | T = 30.162 | Tapered roller bearing                |
| FAG   | K386-A-382-A               | d = 47.625  | D = 96.838   | T = 21     | Tapered roller bearing                |
| FAG   | K59187-59412               | d = 47.625  | D = 104.775  | T = 36.512 | Tapered roller bearing                |
| FAG   | K59188-59412               | d = 47.625  | D = 104.775  | T = 36.512 | Tapered roller bearing                |
| FAG   | K55187-55443               | d = 47.625  | D = 112.713  | T = 30.163 | Tapered roller bearing                |
| FAG   | KHM907639-HM907616         | d = 47.625  | D = 112.713  | T = 30.163 | Tapered roller bearing                |
| FAG   | KHM804848-HM804810         | d = 48.412  | D = 95.25    | T = 30.162 | Tapered roller bearing                |
| FAG   | KHM804849-HM804810         | d = 48.412  | D = 95.25    | T = 30.162 | Tapered roller bearing                |
| FAG   | KHM807044-HM807010         | d = 49.212  | D = 104.775  | T = 36.512 | Tapered roller bearing                |
| FAG   | KHH506348-HH506310         | d = 49.212  | D = 114.3    | T = 44.45  | Tapered roller bearing                |
| FAG   | KL305648-L305611           | d = 49.987  | D = 79.974   | T = 18.258 | Tapered roller bearing                |
| FAG   | 32910                      | d = 50      | D = 72       | T = 15     | Tapered roller bearing                |
| FAG   | 32910-H                    | d = 50      | D = 72       | T = 15     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 32910-XL             | d = 50      | D = 72       | T = 15     | Tapered roller bearing                |
| FAG   | 32010-X              | d = 50      | D = 80       | T = 20     | Tapered roller bearing                |
| FAG   | 32010-X-H            | d = 50      | D = 80       | T = 20     | Tapered roller bearing                |
| FAG   | 32010-X-P5           | d = 50      | D = 80       | T = 20     | Tapered roller bearing                |
| FAG   | 32010-X-TVP          | d = 50      | D = 80       | T = 20     | Tapered roller bearing                |
| FAG   | 32010-X-XL           | d = 50      | D = 80       | T = 20     | Tapered roller bearing                |
| FAG   | 32010-X-XL-J30PC     | d = 50      | D = 80       | T = 20     | Tapered roller bearing                |
| FAG   | 32010-X-XL-P5        | d = 50      | D = 80       | T = 20     | Tapered roller bearing                |
| FAG   | 32010-X-XL-S1        | d = 50      | D = 80       | T = 20     | Tapered roller bearing                |
| FAG   | 32010-X-XL-W215FD    | d = 50      | D = 80       | T = 20     | Tapered roller bearing                |
| FAG   | 32010-X-XL-W60C      | d = 50      | D = 80       | T = 20     | Tapered roller bearing                |
| FAG   | 32010-XDY            | d = 50      | D = 80       | T = 20     | Tapered roller bearing                |
| FAG   | 33010                | d = 50      | D = 80       | T = 24     | Tapered roller bearing                |
| FAG   | 33010-H              | d = 50      | D = 80       | T = 24     | Tapered roller bearing                |
| FAG   | 33010-XL             | d = 50      | D = 80       | T = 24     | Tapered roller bearing                |
| FAG   | T2CD050              | d = 50      | D = 85       | T = 24     | Tapered roller bearing                |
| FAG   | 33110                | d = 50      | D = 85       | T = 26     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 33110-H              | d = 50      | D = 85       | T = 26     | Tapered roller bearing                |
| FAG   | 33110>A              | d = 50      | D = 85       | T = 26     | Tapered roller bearing                |
| FAG   | 33110>B              | d = 50      | D = 85       | T = 26     | Tapered roller bearing                |
| FAG   | T4DB050              | d = 50      | D = 90       | T = 21     | Tapered roller bearing                |
| FAG   | 30210-A              | d = 50      | D = 90       | T = 21.75  | Tapered roller bearing                |
| FAG   | 30210-A-P5           | d = 50      | D = 90       | T = 21.75  | Tapered roller bearing                |
| FAG   | 30210-A>A            | d = 50      | D = 90       | T = 21.75  | Tapered roller bearing                |
| FAG   | 30210-A>B            | d = 50      | D = 90       | T = 21.75  | Tapered roller bearing                |
| FAG   | 30210-A>C            | d = 50      | D = 90       | T = 21.75  | Tapered roller bearing                |
| FAG   | 30210-DY             | d = 50      | D = 90       | T = 21.75  | Tapered roller bearing                |
| FAG   | 30210-H              | d = 50      | D = 90       | T = 21.75  | Tapered roller bearing                |
| FAG   | 30210-XL             | d = 50      | D = 90       | T = 21.75  | Tapered roller bearing                |
| FAG   | 32210-A              | d = 50      | D = 90       | T = 24.75  | Tapered roller bearing                |
| FAG   | 32210-A>A            | d = 50      | D = 90       | T = 24.75  | Tapered roller bearing                |
| FAG   | 32210-B-XL           | d = 50      | D = 90       | T = 24.75  | Tapered roller bearing                |
| FAG   | 32210-DY             | d = 50      | D = 90       | T = 24.75  | Tapered roller bearing                |
| FAG   | 32210-H              | d = 50      | D = 90       | T = 24.75  | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 33210                | d = 50      | D = 90       | T = 32     | Tapered roller bearing                |
| FAG   | 33210-H              | d = 50      | D = 90       | T = 32     | Tapered roller bearing                |
| FAG   | 33210-XL             | d = 50      | D = 90       | T = 32     | Tapered roller bearing                |
| FAG   | 33210>A              | d = 50      | D = 90       | T = 32     | Tapered roller bearing                |
| FAG   | 33210>B              | d = 50      | D = 90       | T = 32     | Tapered roller bearing                |
| KOYO  | 46T30210JR/39.5      | d = 50      | D = 90       | T = 49     | Tapered roller bearing                |
| KOYO  | 46T32210JR/43.5      | d = 50      | D = 90       | T = 55     | Tapered roller bearing                |
| FAG   | T2ED050              | d = 50      | D = 100      | T = 36     | Tapered roller bearing                |
| FAG   | T5ED050              | d = 50      | D = 100      | T = 36     | Tapered roller bearing                |
| FAG   | T7FC050-XL           | d = 50      | D = 105      | T = 32     | Tapered roller bearing                |
| FAG   | T7FC050-XL>A         | d = 50      | D = 105      | T = 32     | Tapered roller bearing                |
| FAG   | T7FC050-XL>B         | d = 50      | D = 105      | T = 32     | Tapered roller bearing                |
| FAG   | T4FE050              | d = 50      | D = 105      | T = 41     | Tapered roller bearing                |
| FAG   | 30310-A              | d = 50      | D = 110      | T = 29.25  | Tapered roller bearing                |
| FAG   | 30310-DY             | d = 50      | D = 110      | T = 29.25  | Tapered roller bearing                |
| FAG   | 30310-H              | d = 50      | D = 110      | T = 29.25  | Tapered roller bearing                |
| FAG   | 30310-XL             | d = 50      | D = 110      | T = 29.25  | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 30310-XL-S1          | d = 50      | D = 110      | T = 29.25  | Tapered roller bearing                |
| FAG   | 31310-A              | d = 50      | D = 110      | T = 29.25  | Tapered roller bearing                |
| FAG   | 31310-A-S1           | d = 50      | D = 110      | T = 29.25  | Tapered roller bearing                |
| FAG   | 31310-A>A            | d = 50      | D = 110      | T = 29.25  | Tapered roller bearing                |
| FAG   | 31310-DY             | d = 50      | D = 110      | T = 29.25  | Tapered roller bearing                |
| FAG   | 31310-DY-W60B        | d = 50      | D = 110      | T = 29.25  | Tapered roller bearing                |
| FAG   | 31310-H              | d = 50      | D = 110      | T = 29.25  | Tapered roller bearing                |
| FAG   | 32310-A              | d = 50      | D = 110      | T = 42.25  | Tapered roller bearing                |
| FAG   | 32310-A>A            | d = 50      | D = 110      | T = 42.25  | Tapered roller bearing                |
| FAG   | 32310-B              | d = 50      | D = 110      | T = 42.25  | Tapered roller bearing                |
| FAG   | 32310-B-S1           | d = 50      | D = 110      | T = 42.25  | Tapered roller bearing                |
| FAG   | 32310-B-XL           | d = 50      | D = 110      | T = 42.25  | Tapered roller bearing                |
| FAG   | 32310-DY             | d = 50      | D = 110      | T = 42.25  | Tapered roller bearing                |
| FAG   | 32310-H              | d = 50      | D = 110      | T = 42.25  | Tapered roller bearing                |
| FAG   | 32310-XL-J30PC       | d = 50      | D = 110      | T = 42.25  | Tapered roller bearing                |
| KOYO  | 46T30310JR/51.5      | d = 50      | D = 110      | T = 64     | Tapered roller bearing                |
| KOYO  | 46T30310DJR/52.5     | d = 50      | D = 110      | T = 73     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation       | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------------|-------------|--------------|------------|---------------------------------------|
| KOYO  | 46T32310JR/71.5            | d = 50      | D = 110      | T = 90     | Tapered roller bearing                |
| FAG   | KL305649-L305610           | d = 50.8    | D = 80.962   | T = 18.258 | Tapered roller bearing                |
| FAG   | KLM104949-LM104911-DY-W61C | d = 50.8    | D = 82.55    | T = 21.59  | Tapered roller bearing                |
| FAG   | K368-362-A                 | d = 50.8    | D = 88.9     | T = 20.637 | Tapered roller bearing                |
| FAG   | K368-A-362-A               | d = 50.8    | D = 88.9     | T = 20.637 | Tapered roller bearing                |
| FAG   | K368-A-362-A-XL            | d = 50.8    | D = 88.9     | T = 20.637 | Tapered roller bearing                |
| FAG   | K28580-28521               | d = 50.8    | D = 92.075   | T = 24.608 | Tapered roller bearing                |
| FAG   | K3775-3720                 | d = 50.8    | D = 93.264   | T = 30.162 | Tapered roller bearing                |
| FAG   | K3784-3720                 | d = 50.8    | D = 93.264   | T = 30.162 | Tapered roller bearing                |
| FAG   | K3784-3720-DY              | d = 50.8    | D = 93.264   | T = 30.162 | Tapered roller bearing                |
| FAG   | K33889-33822               | d = 50.8    | D = 95.25    | T = 27.783 | Tapered roller bearing                |
| FAG   | K49585-49520               | d = 50.8    | D = 101.6    | T = 31.75  | Tapered roller bearing                |
| FAG   | AK529-522-W60C             | d = 50.8    | D = 101.6    | T = 34.925 | Tapered roller bearing                |
| FAG   | AK529-X-522-XL             | d = 50.8    | D = 101.6    | T = 34.925 | Tapered roller bearing                |
| FAG   | K45285-45220               | d = 50.8    | D = 104.775  | T = 30.162 | Tapered roller bearing                |
| FAG   | K45285-45221               | d = 50.8    | D = 104.775  | T = 30.162 | Tapered roller bearing                |
| FAG   | K45285-A-45221             | d = 50.8    | D = 104.775  | T = 30.162 | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation     | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|--------------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | K59200-59412             | d = 50.8    | D = 104.775  | T = 36.512 | Tapered roller bearing                |
| FAG   | KHM807046-HM807011       | d = 50.8    | D = 104.775  | T = 36.512 | Tapered roller bearing                |
| FAG   | K4580-4535               | d = 50.8    | D = 104.775  | T = 39.688 | Tapered roller bearing                |
| FAG   | K4580-4535-XL            | d = 50.8    | D = 104.775  | T = 39.688 | Tapered roller bearing                |
| FAG   | K455-453-A               | d = 50.8    | D = 107.95   | T = 27.783 | Tapered roller bearing                |
| FAG   | K537-532-X               | d = 50.8    | D = 107.95   | T = 36.512 | Tapered roller bearing                |
| FAG   | K55200-55437             | d = 50.8    | D = 111.125  | T = 30.162 | Tapered roller bearing                |
| FAG   | K55200-C-55437           | d = 50.8    | D = 111.125  | T = 30.162 | Tapered roller bearing                |
| FAG   | K619-612                 | d = 50.8    | D = 120.65   | T = 41.275 | Tapered roller bearing                |
| FAG   | K72200-72487             | d = 50.8    | D = 123.825  | T = 36.512 | Tapered roller bearing                |
| FAG   | K65200-65500             | d = 50.8    | D = 127      | T = 44.45  | Tapered roller bearing                |
| FAG   | K18204-X-18335-X         | d = 51.999  | D = 85.001   | T = 19.05  | Tapered roller bearing                |
| FAG   | K28584-28521             | d = 52.388  | D = 92.075   | T = 24.608 | Tapered roller bearing                |
| FAG   | K55206-C-55437           | d = 52.388  | D = 111.125  | T = 30.162 | Tapered roller bearing                |
| FAG   | K55206-C-55437-XL        | d = 52.388  | D = 111.125  | T = 30.162 | Tapered roller bearing                |
| FAG   | K55206-C-55437-XL-W215FD | d = 52.388  | D = 111.125  | T = 30.162 | Tapered roller bearing                |
| FAG   | KLM806649-LM806610       | d = 53.975  | D = 88.9     | T = 19.05  | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation  | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|-----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | KLM806649-LM806610-XL | d = 53.975  | D = 88.9     | T = 19.05  | Tapered roller bearing                |
| FAG   | K389-A-382            | d = 53.975  | D = 98.425   | T = 21     | Tapered roller bearing                |
| FAG   | KHM807049-HM807010    | d = 53.975  | D = 104.775  | T = 36.512 | Tapered roller bearing                |
| FAG   | K66584-66520          | d = 53.975  | D = 122.238  | T = 33.338 | Tapered roller bearing                |
| FAG   | K5578-5535            | d = 53.975  | D = 122.238  | T = 43.658 | Tapered roller bearing                |
| FAG   | K72212-72487          | d = 53.975  | D = 123.825  | T = 36.512 | Tapered roller bearing                |
| FAG   | K72212-C-72487        | d = 53.975  | D = 123.825  | T = 36.512 | Tapered roller bearing                |
| FAG   | K557-S-552-A          | d = 53.975  | D = 123.825  | T = 38.1   | Tapered roller bearing                |
| FAG   | K78215-C-78551        | d = 53.975  | D = 140.03   | T = 36.512 | Tapered roller bearing                |
| FAG   | KHM807048-HM807010    | d = 54.488  | D = 104.775  | T = 36.512 | Tapered roller bearing                |
| FAG   | 32911                 | d = 55      | D = 80       | T = 17     | Tapered roller bearing                |
| FAG   | 32911-DY              | d = 55      | D = 80       | T = 17     | Tapered roller bearing                |
| FAG   | 32911-H               | d = 55      | D = 80       | T = 17     | Tapered roller bearing                |
| FAG   | T2CC055               | d = 55      | D = 85       | T = 18     | Tapered roller bearing                |
| FAG   | 32011-X               | d = 55      | D = 90       | T = 23     | Tapered roller bearing                |
| FAG   | 32011-X-H             | d = 55      | D = 90       | T = 23     | Tapered roller bearing                |
| FAG   | 32011-X-S1            | d = 55      | D = 90       | T = 23     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 32011-X-XL           | d = 55      | D = 90       | T = 23     | Tapered roller bearing                |
| FAG   | 32011-X-XL-J30PC     | d = 55      | D = 90       | T = 23     | Tapered roller bearing                |
| FAG   | 32011-X-XL-P5        | d = 55      | D = 90       | T = 23     | Tapered roller bearing                |
| FAG   | 32011-X-XL-W215FD    | d = 55      | D = 90       | T = 23     | Tapered roller bearing                |
| FAG   | 32011-X-XL-W60C      | d = 55      | D = 90       | T = 23     | Tapered roller bearing                |
| FAG   | 32011-X-XL>A         | d = 55      | D = 90       | T = 23     | Tapered roller bearing                |
| FAG   | 32011-XDY            | d = 55      | D = 90       | T = 23     | Tapered roller bearing                |
| FAG   | 33011                | d = 55      | D = 90       | T = 27     | Tapered roller bearing                |
| FAG   | 33011-H              | d = 55      | D = 90       | T = 27     | Tapered roller bearing                |
| FAG   | 33011-XL             | d = 55      | D = 90       | T = 27     | Tapered roller bearing                |
| FAG   | T4CB055              | d = 55      | D = 95       | T = 21     | Tapered roller bearing                |
| FAG   | T2CD055              | d = 55      | D = 95       | T = 27     | Tapered roller bearing                |
| FAG   | 33111                | d = 55      | D = 95       | T = 30     | Tapered roller bearing                |
| FAG   | 33111-H              | d = 55      | D = 95       | T = 30     | Tapered roller bearing                |
| FAG   | 33111>A              | d = 55      | D = 95       | T = 30     | Tapered roller bearing                |
| FAG   | K385-X-382-A         | d = 55      | D = 96.838   | T = 21     | Tapered roller bearing                |
| FAG   | 30211-A              | d = 55      | D = 100      | T = 22.75  | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 30211-A-P5           | d = 55      | D = 100      | T = 22.75  | Tapered roller bearing                |
| FAG   | 30211-A>A            | d = 55      | D = 100      | T = 22.75  | Tapered roller bearing                |
| FAG   | 30211-DY             | d = 55      | D = 100      | T = 22.75  | Tapered roller bearing                |
| FAG   | 30211-H              | d = 55      | D = 100      | T = 22.75  | Tapered roller bearing                |
| FAG   | 30211-XL             | d = 55      | D = 100      | T = 22.75  | Tapered roller bearing                |
| FAG   | 32211-A              | d = 55      | D = 100      | T = 26.75  | Tapered roller bearing                |
| FAG   | 32211-A-P5           | d = 55      | D = 100      | T = 26.75  | Tapered roller bearing                |
| FAG   | 32211-A>A            | d = 55      | D = 100      | T = 26.75  | Tapered roller bearing                |
| FAG   | 32211-B              | d = 55      | D = 100      | T = 26.75  | Tapered roller bearing                |
| FAG   | 32211-B-XL           | d = 55      | D = 100      | T = 26.75  | Tapered roller bearing                |
| FAG   | 32211-DY             | d = 55      | D = 100      | T = 26.75  | Tapered roller bearing                |
| FAG   | 32211-H              | d = 55      | D = 100      | T = 26.75  | Tapered roller bearing                |
| FAG   | 32211-XL             | d = 55      | D = 100      | T = 26.75  | Tapered roller bearing                |
| FAG   | T5DD055              | d = 55      | D = 100      | T = 30     | Tapered roller bearing                |
| FAG   | 33211                | d = 55      | D = 100      | T = 35     | Tapered roller bearing                |
| FAG   | 33211-H              | d = 55      | D = 100      | T = 35     | Tapered roller bearing                |
| FAG   | 33211-XL             | d = 55      | D = 100      | T = 35     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| KOYO  | 46T30211JR/41.5      | d = 55      | D = 100      | T = 51     | Tapered roller bearing                |
| KOYO  | 46T32211JR-1/48.5    | d = 55      | D = 100      | T = 60     | Tapered roller bearing                |
| FAG   | T5ED055              | d = 55      | D = 105      | T = 36     | Tapered roller bearing                |
| FAG   | T7FC055-XL           | d = 55      | D = 115      | T = 34     | Tapered roller bearing                |
| FAG   | T7FC055-XL-S1        | d = 55      | D = 115      | T = 34     | Tapered roller bearing                |
| FAG   | T7FC055-XL-S1>A      | d = 55      | D = 115      | T = 34     | Tapered roller bearing                |
| FAG   | T7FC055-XL-W215FD    | d = 55      | D = 115      | T = 34     | Tapered roller bearing                |
| FAG   | T7FC055-XL-W60C      | d = 55      | D = 115      | T = 34     | Tapered roller bearing                |
| FAG   | T7FC055-XL-W60E      | d = 55      | D = 115      | T = 34     | Tapered roller bearing                |
| FAG   | T7FC055-XL>A         | d = 55      | D = 115      | T = 34     | Tapered roller bearing                |
| FAG   | T4FE055              | d = 55      | D = 115      | T = 44     | Tapered roller bearing                |
| FAG   | K475-472             | d = 55      | D = 120      | T = 29.794 | Tapered roller bearing                |
| FAG   | 30311-A              | d = 55      | D = 120      | T = 31.5   | Tapered roller bearing                |
| FAG   | 30311-DY             | d = 55      | D = 120      | T = 31.5   | Tapered roller bearing                |
| FAG   | 30311-H              | d = 55      | D = 120      | T = 31.5   | Tapered roller bearing                |
| FAG   | 30311-XL             | d = 55      | D = 120      | T = 31.5   | Tapered roller bearing                |
| FAG   | 31311-A              | d = 55      | D = 120      | T = 31.5   | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 31311-H              | d = 55      | D = 120      | T = 31.5   | Tapered roller bearing                |
| FAG   | 32311-A              | d = 55      | D = 120      | T = 45.5   | Tapered roller bearing                |
| FAG   | 32311-A>A            | d = 55      | D = 120      | T = 45.5   | Tapered roller bearing                |
| FAG   | 32311-B              | d = 55      | D = 120      | T = 45.5   | Tapered roller bearing                |
| FAG   | 32311-B-P6X          | d = 55      | D = 120      | T = 45.5   | Tapered roller bearing                |
| FAG   | 32311-B-P6X>A        | d = 55      | D = 120      | T = 45.5   | Tapered roller bearing                |
| FAG   | 32311-B-XL           | d = 55      | D = 120      | T = 45.5   | Tapered roller bearing                |
| FAG   | 32311-B>A            | d = 55      | D = 120      | T = 45.5   | Tapered roller bearing                |
| FAG   | 32311-H              | d = 55      | D = 120      | T = 45.5   | Tapered roller bearing                |
| KOYO  | 46T30311DJR/49       | d = 55      | D = 120      | T = 70     | Tapered roller bearing                |
| KOYO  | 46T30311JR/57        | d = 55      | D = 120      | T = 70     | Tapered roller bearing                |
| KOYO  | 46T32311JR/76        | d = 55      | D = 120      | T = 97     | Tapered roller bearing                |
| FAG   | KL507949-L507910     | d = 57.15   | D = 87.312   | T = 18.258 | Tapered roller bearing                |
| FAG   | KL507949-L507910-DY  | d = 57.15   | D = 87.312   | T = 18.258 | Tapered roller bearing                |
| FAG   | K387-382-A-XL        | d = 57.15   | D = 96.838   | T = 21     | Tapered roller bearing                |
| FAG   | K387-A-382-A-DY-W61C | d = 57.15   | D = 96.838   | T = 21     | Tapered roller bearing                |
| FAG   | K28682-28622         | d = 57.15   | D = 97.63    | T = 24.608 | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | K387-A-382           | d = 57.15   | D = 98.425   | T = 21     | Tapered roller bearing                |
| FAG   | K387-AS-382          | d = 57.15   | D = 98.425   | T = 21     | Tapered roller bearing                |
| FAG   | K387-A-383-A         | d = 57.15   | D = 100      | T = 21     | Tapered roller bearing                |
| FAG   | K387-S-383-A-DY      | d = 57.15   | D = 100      | T = 21     | Tapered roller bearing                |
| FAG   | K462-453-X           | d = 57.15   | D = 104.775  | T = 30.163 | Tapered roller bearing                |
| FAG   | K462-A-453-X         | d = 57.15   | D = 104.775  | T = 30.163 | Tapered roller bearing                |
| FAG   | K462-454             | d = 57.15   | D = 110      | T = 27.795 | Tapered roller bearing                |
| FAG   | K39580-39520         | d = 57.15   | D = 112.712  | T = 30.162 | Tapered roller bearing                |
| FAG   | K3979-3920           | d = 57.15   | D = 112.712  | T = 30.162 | Tapered roller bearing                |
| FAG   | K33225-33462         | d = 57.15   | D = 117.475  | T = 30.162 | Tapered roller bearing                |
| FAG   | K66225-66462         | d = 57.15   | D = 117.475  | T = 33.338 | Tapered roller bearing                |
| FAG   | K39580-39528         | d = 57.15   | D = 119.985  | T = 32.75  | Tapered roller bearing                |
| FAG   | K555-S-552-A         | d = 57.15   | D = 123.825  | T = 38.1   | Tapered roller bearing                |
| FAG   | K635-632             | d = 57.15   | D = 136.525  | T = 41.275 | Tapered roller bearing                |
| FAG   | K28980-28921         | d = 59.977  | D = 100      | T = 25.4   | Tapered roller bearing                |
| FAG   | 32912                | d = 60      | D = 85       | T = 17     | Tapered roller bearing                |
| FAG   | 32912-H              | d = 60      | D = 85       | T = 17     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 32012-X              | d = 60      | D = 95       | T = 23     | Tapered roller bearing                |
| FAG   | 32012-X-H            | d = 60      | D = 95       | T = 23     | Tapered roller bearing                |
| FAG   | 32012-X-XL           | d = 60      | D = 95       | T = 23     | Tapered roller bearing                |
| FAG   | 32012-X-XL-P5        | d = 60      | D = 95       | T = 23     | Tapered roller bearing                |
| FAG   | 32012-X-XL-W215FD    | d = 60      | D = 95       | T = 23     | Tapered roller bearing                |
| FAG   | 32012-XDY            | d = 60      | D = 95       | T = 23     | Tapered roller bearing                |
| FAG   | 33012-DY             | d = 60      | D = 95       | T = 27     | Tapered roller bearing                |
| FAG   | 33012-H              | d = 60      | D = 95       | T = 27     | Tapered roller bearing                |
| FAG   | 33012-XL             | d = 60      | D = 95       | T = 27     | Tapered roller bearing                |
| FAG   | T4CB060              | d = 60      | D = 100      | T = 21     | Tapered roller bearing                |
| FAG   | T2CD060              | d = 60      | D = 100      | T = 27     | Tapered roller bearing                |
| FAG   | 33112                | d = 60      | D = 100      | T = 30     | Tapered roller bearing                |
| FAG   | 33112-DY             | d = 60      | D = 100      | T = 30     | Tapered roller bearing                |
| FAG   | 33112-H              | d = 60      | D = 100      | T = 30     | Tapered roller bearing                |
| FAG   | 33112-XL             | d = 60      | D = 100      | T = 30     | Tapered roller bearing                |
| FAG   | K39235-X-39412       | d = 60      | D = 104.775  | T = 21.433 | Tapered roller bearing                |
| FAG   | 30212-DY             | d = 60      | D = 110      | T = 23.75  | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 30212-H              | d = 60      | D = 110      | T = 23.75  | Tapered roller bearing                |
| FAG   | 30212-XL             | d = 60      | D = 110      | T = 23.75  | Tapered roller bearing                |
| FAG   | 30212-XL-P5          | d = 60      | D = 110      | T = 23.75  | Tapered roller bearing                |
| FAG   | 30212-XL-W60C        | d = 60      | D = 110      | T = 23.75  | Tapered roller bearing                |
| FAG   | 30212-XL-W60E        | d = 60      | D = 110      | T = 23.75  | Tapered roller bearing                |
| FAG   | 32212-A              | d = 60      | D = 110      | T = 29.75  | Tapered roller bearing                |
| FAG   | 32212-A-P5           | d = 60      | D = 110      | T = 29.75  | Tapered roller bearing                |
| FAG   | 32212-A>A            | d = 60      | D = 110      | T = 29.75  | Tapered roller bearing                |
| FAG   | 32212-B              | d = 60      | D = 110      | T = 29.75  | Tapered roller bearing                |
| FAG   | 32212-B-XL           | d = 60      | D = 110      | T = 29.75  | Tapered roller bearing                |
| FAG   | 32212-DY             | d = 60      | D = 110      | T = 29.75  | Tapered roller bearing                |
| FAG   | 32212-H              | d = 60      | D = 110      | T = 29.75  | Tapered roller bearing                |
| FAG   | 32212-XL             | d = 60      | D = 110      | T = 29.75  | Tapered roller bearing                |
| FAG   | T5DD060              | d = 60      | D = 110      | T = 34     | Tapered roller bearing                |
| FAG   | 33212                | d = 60      | D = 110      | T = 38     | Tapered roller bearing                |
| FAG   | 33212-H              | d = 60      | D = 110      | T = 38     | Tapered roller bearing                |
| FAG   | 33212-TVP            | d = 60      | D = 110      | T = 38     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 33212-XL             | d = 60      | D = 110      | T = 38     | Tapered roller bearing                |
| KOYO  | 46T30212JR/43.5      | d = 60      | D = 110      | T = 53     | Tapered roller bearing                |
| KOYO  | 46T32212JR/54.5      | d = 60      | D = 110      | T = 66     | Tapered roller bearing                |
| FAG   | K39236-39433         | d = 60      | D = 110.058  | T = 22     | Tapered roller bearing                |
| FAG   | T5ED060              | d = 60      | D = 115      | T = 39     | Tapered roller bearing                |
| FAG   | T2EE060              | d = 60      | D = 115      | T = 40     | Tapered roller bearing                |
| FAG   | T7FC060-XL           | d = 60      | D = 125      | T = 37     | Tapered roller bearing                |
| FAG   | T7FC060-XL-S1        | d = 60      | D = 125      | T = 37     | Tapered roller bearing                |
| FAG   | T7FC060-XL-W60E      | d = 60      | D = 125      | T = 37     | Tapered roller bearing                |
| FAG   | T7FC060-XL>A         | d = 60      | D = 125      | T = 37     | Tapered roller bearing                |
| FAG   | T4FE060              | d = 60      | D = 125      | T = 48     | Tapered roller bearing                |
| FAG   | 30312-A              | d = 60      | D = 130      | T = 33.5   | Tapered roller bearing                |
| FAG   | 30312-DY             | d = 60      | D = 130      | T = 33.5   | Tapered roller bearing                |
| FAG   | 30312-H              | d = 60      | D = 130      | T = 33.5   | Tapered roller bearing                |
| FAG   | 30312-XL             | d = 60      | D = 130      | T = 33.5   | Tapered roller bearing                |
| FAG   | 31312-A              | d = 60      | D = 130      | T = 33.5   | Tapered roller bearing                |
| FAG   | 31312-H              | d = 60      | D = 130      | T = 33.5   | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 31312-XL             | d = 60      | D = 130      | T = 33.5   | Tapered roller bearing                |
| FAG   | 31312-XL-S1          | d = 60      | D = 130      | T = 33.5   | Tapered roller bearing                |
| FAG   | 31312-XL>A           | d = 60      | D = 130      | T = 33.5   | Tapered roller bearing                |
| FAG   | 32312-A              | d = 60      | D = 130      | T = 48.5   | Tapered roller bearing                |
| FAG   | 32312-B-XL           | d = 60      | D = 130      | T = 48.5   | Tapered roller bearing                |
| FAG   | 32312-BA             | d = 60      | D = 130      | T = 48.5   | Tapered roller bearing                |
| FAG   | 32312-BA>A           | d = 60      | D = 130      | T = 48.5   | Tapered roller bearing                |
| FAG   | 32312-H              | d = 60      | D = 130      | T = 48.5   | Tapered roller bearing                |
| KOYO  | 46T30312DJR/51       | d = 60      | D = 130      | T = 74     | Tapered roller bearing                |
| KOYO  | 46T30312JR/59        | d = 60      | D = 130      | T = 74     | Tapered roller bearing                |
| KOYO  | 46T32312JR/81        | d = 60      | D = 130      | T = 104    | Tapered roller bearing                |
| FAG   | K28985-28921         | d = 60.325  | D = 100      | T = 25.4   | Tapered roller bearing                |
| FAG   | K28985-28921-DY      | d = 60.325  | D = 100      | T = 25.4   | Tapered roller bearing                |
| FAG   | K3980-3920           | d = 60.325  | D = 112.712  | T = 30.162 | Tapered roller bearing                |
| FAG   | AKHM813841-HM813810  | d = 60.325  | D = 127      | T = 36.512 | Tapered roller bearing                |
| FAG   | K65237-65500         | d = 60.325  | D = 127      | T = 44.45  | Tapered roller bearing                |
| FAG   | K78238-C-78537       | d = 60.325  | D = 136.525  | T = 36.513 | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation   | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|------------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | K78238-C-78551         | d = 60.325  | D = 140.03   | T = 36.513 | Tapered roller bearing                |
| FAG   | KH913842-H913810       | d = 61.912  | D = 146.05   | T = 41.275 | Tapered roller bearing                |
| FAG   | K392-394-A             | d = 61.913  | D = 110      | T = 22     | Tapered roller bearing                |
| FAG   | K392-394-A-DY-W60C     | d = 61.913  | D = 110      | T = 22     | Tapered roller bearing                |
| FAG   | K554-552-A             | d = 61.913  | D = 123.825  | T = 38.1   | Tapered roller bearing                |
| FAG   | KH715334-H715311       | d = 61.913  | D = 136.525  | T = 46.038 | Tapered roller bearing                |
| FAG   | K28995-28920           | d = 62.738  | D = 101.6    | T = 25.4   | Tapered roller bearing                |
| FAG   | K28995-28920-XL-W215FD | d = 62.738  | D = 101.6    | T = 25.4   | Tapered roller bearing                |
| FAG   | KL910349-L910310       | d = 63.487  | D = 94.976   | T = 17     | Tapered roller bearing                |
| FAG   | KLL510749-LL510710     | d = 63.5    | D = 92.075   | T = 13.495 | Tapered roller bearing                |
| FAG   | KL610549-L610510       | d = 63.5    | D = 94.458   | T = 19.05  | Tapered roller bearing                |
| FAG   | K39250-39412           | d = 63.5    | D = 104.775  | T = 21.433 | Tapered roller bearing                |
| FAG   | K39250-39412-XL        | d = 63.5    | D = 104.775  | T = 21.433 | Tapered roller bearing                |
| FAG   | K29585-29522           | d = 63.5    | D = 107.95   | T = 25.4   | Tapered roller bearing                |
| FAG   | K29586-29520           | d = 63.5    | D = 107.95   | T = 25.4   | Tapered roller bearing                |
| FAG   | K390-A-394-A           | d = 63.5    | D = 110      | T = 22     | Tapered roller bearing                |
| FAG   | K390-A-394-A-DY-W60C   | d = 63.5    | D = 110      | T = 22     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation         | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|------------------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | K395-394-A-DY-W60C           | d = 63.5    | D = 110      | T = 22     | Tapered roller bearing                |
| FAG   | K395-3920                    | d = 63.5    | D = 112.712  | T = 26.967 | Tapered roller bearing                |
| FAG   | K39585-39520                 | d = 63.5    | D = 112.712  | T = 30.162 | Tapered roller bearing                |
| FAG   | K39585-39520-XL              | d = 63.5    | D = 112.712  | T = 30.162 | Tapered roller bearing                |
| FAG   | K39585-A-39520-XL            | d = 63.5    | D = 112.712  | T = 30.162 | Tapered roller bearing                |
| FAG   | K3982-3920                   | d = 63.5    | D = 112.712  | T = 30.162 | Tapered roller bearing                |
| FAG   | KHM212046-HM212011           | d = 63.5    | D = 122.238  | T = 38.1   | Tapered roller bearing                |
| FAG   | KHM212047-HM212011-XL        | d = 63.5    | D = 122.238  | T = 38.1   | Tapered roller bearing                |
| FAG   | KHM212047-HM212011-XL-W215FD | d = 63.5    | D = 122.238  | T = 38.1   | Tapered roller bearing                |
| FAG   | K559-552-A                   | d = 63.5    | D = 123.825  | T = 38.1   | Tapered roller bearing                |
| FAG   | AKHM813842-HM813811          | d = 63.5    | D = 127      | T = 36.512 | Tapered roller bearing                |
| FAG   | K78250-78537-W215D           | d = 63.5    | D = 136.525  | T = 36.512 | Tapered roller bearing                |
| FAG   | KH715336-H715311             | d = 63.5    | D = 136.525  | T = 46.038 | Tapered roller bearing                |
| FAG   | 32913                        | d = 65      | D = 90       | T = 17     | Tapered roller bearing                |
| FAG   | 32913-H                      | d = 65      | D = 90       | T = 17     | Tapered roller bearing                |
| FAG   | 32913-XL                     | d = 65      | D = 90       | T = 17     | Tapered roller bearing                |
| FAG   | 32913>A                      | d = 65      | D = 90       | T = 17     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | T2CC065              | d = 65      | D = 100      | T = 22     | Tapered roller bearing                |
| FAG   | 32013-X-H            | d = 65      | D = 100      | T = 23     | Tapered roller bearing                |
| FAG   | 32013-X-XL           | d = 65      | D = 100      | T = 23     | Tapered roller bearing                |
| FAG   | 32013-X-XL-P5        | d = 65      | D = 100      | T = 23     | Tapered roller bearing                |
| FAG   | 32013-XDY            | d = 65      | D = 100      | T = 23     | Tapered roller bearing                |
| FAG   | 33013                | d = 65      | D = 100      | T = 27     | Tapered roller bearing                |
| FAG   | 33013-DY             | d = 65      | D = 100      | T = 27     | Tapered roller bearing                |
| FAG   | 33013-DY-W61C        | d = 65      | D = 100      | T = 27     | Tapered roller bearing                |
| FAG   | 33013-H              | d = 65      | D = 100      | T = 27     | Tapered roller bearing                |
| FAG   | 33013-XL             | d = 65      | D = 100      | T = 27     | Tapered roller bearing                |
| FAG   | T4CB065              | d = 65      | D = 105      | T = 21     | Tapered roller bearing                |
| FAG   | T2DD065              | d = 65      | D = 110      | T = 31     | Tapered roller bearing                |
| FAG   | 33113                | d = 65      | D = 110      | T = 34     | Tapered roller bearing                |
| FAG   | 33113-H              | d = 65      | D = 110      | T = 34     | Tapered roller bearing                |
| FAG   | T5DD065              | d = 65      | D = 115      | T = 34     | Tapered roller bearing                |
| FAG   | 30213-A              | d = 65      | D = 120      | T = 24.75  | Tapered roller bearing                |
| FAG   | 30213-A-P5           | d = 65      | D = 120      | T = 24.75  | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 30213-A>A            | d = 65      | D = 120      | T = 24.75  | Tapered roller bearing                |
| FAG   | 30213-DY             | d = 65      | D = 120      | T = 24.75  | Tapered roller bearing                |
| FAG   | 30213-H              | d = 65      | D = 120      | T = 24.75  | Tapered roller bearing                |
| FAG   | 30213-XL             | d = 65      | D = 120      | T = 24.75  | Tapered roller bearing                |
| FAG   | 32213-A              | d = 65      | D = 120      | T = 32.75  | Tapered roller bearing                |
| FAG   | 32213-A-P5           | d = 65      | D = 120      | T = 32.75  | Tapered roller bearing                |
| FAG   | 32213-A>B            | d = 65      | D = 120      | T = 32.75  | Tapered roller bearing                |
| FAG   | 32213-B              | d = 65      | D = 120      | T = 32.75  | Tapered roller bearing                |
| FAG   | 32213-B-XL           | d = 65      | D = 120      | T = 32.75  | Tapered roller bearing                |
| FAG   | 32213-DY             | d = 65      | D = 120      | T = 32.75  | Tapered roller bearing                |
| FAG   | 32213-H              | d = 65      | D = 120      | T = 32.75  | Tapered roller bearing                |
| FAG   | 32213-XL             | d = 65      | D = 120      | T = 32.75  | Tapered roller bearing                |
| FAG   | T5ED065              | d = 65      | D = 120      | T = 39     | Tapered roller bearing                |
| FAG   | 33213                | d = 65      | D = 120      | T = 41     | Tapered roller bearing                |
| FAG   | 33213-H              | d = 65      | D = 120      | T = 41     | Tapered roller bearing                |
| FAG   | 33213-P5             | d = 65      | D = 120      | T = 41     | Tapered roller bearing                |
| KOYO  | 46T30213JR/46.5      | d = 65      | D = 120      | T = 56     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| KOYO  | 46T32213JR/61.5      | d = 65      | D = 120      | T = 73     | Tapered roller bearing                |
| FAG   | T7FC065-XL           | d = 65      | D = 130      | T = 37     | Tapered roller bearing                |
| FAG   | T7FC065-XL-S1        | d = 65      | D = 130      | T = 37     | Tapered roller bearing                |
| FAG   | T7FC065-XL>A         | d = 65      | D = 130      | T = 37     | Tapered roller bearing                |
| FAG   | T7FC065-XL>B         | d = 65      | D = 130      | T = 37     | Tapered roller bearing                |
| FAG   | T3FE065              | d = 65      | D = 135      | T = 52     | Tapered roller bearing                |
| FAG   | 30313-A              | d = 65      | D = 140      | T = 36     | Tapered roller bearing                |
| FAG   | 30313-A>A            | d = 65      | D = 140      | T = 36     | Tapered roller bearing                |
| FAG   | 30313-DY             | d = 65      | D = 140      | T = 36     | Tapered roller bearing                |
| FAG   | 30313-H              | d = 65      | D = 140      | T = 36     | Tapered roller bearing                |
| FAG   | 31313-A              | d = 65      | D = 140      | T = 36     | Tapered roller bearing                |
| FAG   | 31313-A-P5           | d = 65      | D = 140      | T = 36     | Tapered roller bearing                |
| FAG   | 31313-H              | d = 65      | D = 140      | T = 36     | Tapered roller bearing                |
| FAG   | 31313-XL             | d = 65      | D = 140      | T = 36     | Tapered roller bearing                |
| FAG   | 31313-XL>A           | d = 65      | D = 140      | T = 36     | Tapered roller bearing                |
| FAG   | 32313-A              | d = 65      | D = 140      | T = 51     | Tapered roller bearing                |
| FAG   | 32313-B-XL           | d = 65      | D = 140      | T = 51     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 32313-BA             | d = 65      | D = 140      | T = 51     | Tapered roller bearing                |
| FAG   | 32313-DY             | d = 65      | D = 140      | T = 51     | Tapered roller bearing                |
| FAG   | 32313-H              | d = 65      | D = 140      | T = 51     | Tapered roller bearing                |
| FAG   | 32313-XL             | d = 65      | D = 140      | T = 51     | Tapered roller bearing                |
| KOYO  | 46T30313DJR/53       | d = 65      | D = 140      | T = 79     | Tapered roller bearing                |
| KOYO  | 46T30313JR/63        | d = 65      | D = 140      | T = 79     | Tapered roller bearing                |
| KOYO  | 46T32313JR/84        | d = 65      | D = 140      | T = 108    | Tapered roller bearing                |
| FAG   | AK6379-6320          | d = 65.088  | D = 135.755  | T = 53.975 | Tapered roller bearing                |
| FAG   | KL812147-L812111     | d = 66.675  | D = 103.213  | T = 17.247 | Tapered roller bearing                |
| FAG   | KL812148-L812111     | d = 66.675  | D = 103.213  | T = 17.602 | Tapered roller bearing                |
| FAG   | K29590-29520         | d = 66.675  | D = 107.95   | T = 25.4   | Tapered roller bearing                |
| FAG   | K395-A-394-A         | d = 66.675  | D = 110      | T = 22     | Tapered roller bearing                |
| FAG   | K29590-29521         | d = 66.675  | D = 110      | T = 25.4   | Tapered roller bearing                |
| FAG   | K39590-39520         | d = 66.675  | D = 112.712  | T = 30.162 | Tapered roller bearing                |
| FAG   | K3984-3920           | d = 66.675  | D = 112.712  | T = 30.162 | Tapered roller bearing                |
| FAG   | K33262-33461         | d = 66.675  | D = 117.475  | T = 30.162 | Tapered roller bearing                |
| FAG   | KHM212049-HM212010   | d = 66.675  | D = 122.238  | T = 38.1   | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation       | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | KHM212049-HM212011         | d = 66.675  | D = 122.238  | T = 38.1   | Tapered roller bearing                |
| FAG   | KHM212049-HM212011-XL      | d = 66.675  | D = 122.238  | T = 38.1   | Tapered roller bearing                |
| FAG   | K560-552-A                 | d = 66.675  | D = 123.825  | T = 38.1   | Tapered roller bearing                |
| FAG   | AKHM813844-HM813811        | d = 66.675  | D = 127      | T = 36.512 | Tapered roller bearing                |
| FAG   | K641-633-XL-W215FD         | d = 66.675  | D = 130.175  | T = 41.275 | Tapered roller bearing                |
| FAG   | K6386-6320-XL-W215FD       | d = 66.675  | D = 135.755  | T = 53.975 | Tapered roller bearing                |
| FAG   | KH414242-H414210-XL        | d = 66.675  | D = 136.525  | T = 41.275 | Tapered roller bearing                |
| FAG   | KH414242-H414210-XL-W215FD | d = 66.675  | D = 136.525  | T = 41.275 | Tapered roller bearing                |
| FAG   | KH715341-H715311           | d = 66.675  | D = 136.525  | T = 46.038 | Tapered roller bearing                |
| FAG   | KHH814547-HH814510         | d = 66.675  | D = 152.4    | T = 53.975 | Tapered roller bearing                |
| FAG   | KHH914449-HH914412         | d = 66.675  | D = 177.8    | T = 57.15  | Tapered roller bearing                |
| FAG   | KHH914449-HH914412-XL      | d = 66.675  | D = 177.8    | T = 57.15  | Tapered roller bearing                |
| FAG   | K399-AS-394-A-DY-W60C      | d = 68.262  | D = 110      | T = 22     | Tapered roller bearing                |
| FAG   | KH414245-H414210           | d = 68.262  | D = 136.525  | T = 41.275 | Tapered roller bearing                |
| FAG   | KH715343-H715311           | d = 68.262  | D = 136.525  | T = 46.038 | Tapered roller bearing                |
| FAG   | K9185-9121                 | d = 68.262  | D = 152.4    | T = 47.625 | Tapered roller bearing                |
| FAG   | K9278-9220                 | d = 68.263  | D = 161.925  | T = 49.212 | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | KLL713049-LL713010   | d = 69.85   | D = 98.425   | T = 13.495 | Tapered roller bearing                |
| FAG   | KLL713149-LL713110   | d = 69.85   | D = 99.217   | T = 17     | Tapered roller bearing                |
| FAG   | KLM613449-LM613410   | d = 69.85   | D = 112.712  | T = 22.225 | Tapered roller bearing                |
| FAG   | K29675-29620         | d = 69.85   | D = 112.712  | T = 25.4   | Tapered roller bearing                |
| FAG   | K33275-33462         | d = 69.85   | D = 117.475  | T = 30.162 | Tapered roller bearing                |
| FAG   | K47487-47420         | d = 69.85   | D = 120      | T = 32.545 | Tapered roller bearing                |
| FAG   | K47487-47420-A       | d = 69.85   | D = 120      | T = 32.545 | Tapered roller bearing                |
| FAG   | AKHM813846-HM813810  | d = 69.85   | D = 127      | T = 36.512 | Tapered roller bearing                |
| FAG   | AKHM813846-HM813811  | d = 69.85   | D = 127      | T = 36.512 | Tapered roller bearing                |
| FAG   | K566-563             | d = 69.85   | D = 127      | T = 36.512 | Tapered roller bearing                |
| FAG   | K566-562-X           | d = 69.85   | D = 130      | T = 36.937 | Tapered roller bearing                |
| FAG   | K643-633             | d = 69.85   | D = 130.175  | T = 41.275 | Tapered roller bearing                |
| FAG   | KH913849-H913810     | d = 69.85   | D = 146.05   | T = 41.275 | Tapered roller bearing                |
| FAG   | K655-652-XL-W215FD   | d = 69.85   | D = 152.4    | T = 41.275 | Tapered roller bearing                |
| FAG   | K835-832             | d = 69.85   | D = 168.275  | T = 53.975 | Tapered roller bearing                |
| FAG   | KH916642-H916610     | d = 69.987  | D = 176.212  | T = 54.77  | Tapered roller bearing                |
| FAG   | 32914                | d = 70      | D = 100      | T = 20     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 32914-H              | d = 70      | D = 100      | T = 20     | Tapered roller bearing                |
| FAG   | 32914-XL             | d = 70      | D = 100      | T = 20     | Tapered roller bearing                |
| FAG   | T2CC070              | d = 70      | D = 105      | T = 22     | Tapered roller bearing                |
| FAG   | T4CB070              | d = 70      | D = 110      | T = 21     | Tapered roller bearing                |
| FAG   | 32014-X              | d = 70      | D = 110      | T = 25     | Tapered roller bearing                |
| FAG   | 32014-X-H            | d = 70      | D = 110      | T = 25     | Tapered roller bearing                |
| FAG   | 32014-X-S1           | d = 70      | D = 110      | T = 25     | Tapered roller bearing                |
| FAG   | 32014-X-XL           | d = 70      | D = 110      | T = 25     | Tapered roller bearing                |
| FAG   | 32014-X-XL-P5        | d = 70      | D = 110      | T = 25     | Tapered roller bearing                |
| FAG   | 33014                | d = 70      | D = 110      | T = 31     | Tapered roller bearing                |
| FAG   | 33014-H              | d = 70      | D = 110      | T = 31     | Tapered roller bearing                |
| FAG   | 33014-P5             | d = 70      | D = 110      | T = 31     | Tapered roller bearing                |
| FAG   | 33014>A              | d = 70      | D = 110      | T = 31     | Tapered roller bearing                |
| FAG   | T2DD070              | d = 70      | D = 120      | T = 34     | Tapered roller bearing                |
| FAG   | 33114                | d = 70      | D = 120      | T = 37     | Tapered roller bearing                |
| FAG   | 33114-H              | d = 70      | D = 120      | T = 37     | Tapered roller bearing                |
| FAG   | 33114-XL             | d = 70      | D = 120      | T = 37     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 30214-A              | d = 70      | D = 125      | T = 26.25  | Tapered roller bearing                |
| FAG   | 30214-A-P5           | d = 70      | D = 125      | T = 26.25  | Tapered roller bearing                |
| FAG   | 30214-DY             | d = 70      | D = 125      | T = 26.25  | Tapered roller bearing                |
| FAG   | 30214-H              | d = 70      | D = 125      | T = 26.25  | Tapered roller bearing                |
| FAG   | 30214-XL             | d = 70      | D = 125      | T = 26.25  | Tapered roller bearing                |
| FAG   | 30214-XL-P5          | d = 70      | D = 125      | T = 26.25  | Tapered roller bearing                |
| FAG   | 30214-XL-S1          | d = 70      | D = 125      | T = 26.25  | Tapered roller bearing                |
| FAG   | 32214-A              | d = 70      | D = 125      | T = 33.25  | Tapered roller bearing                |
| FAG   | 32214-A-P5           | d = 70      | D = 125      | T = 33.25  | Tapered roller bearing                |
| FAG   | 32214-A>A            | d = 70      | D = 125      | T = 33.25  | Tapered roller bearing                |
| FAG   | 32214-B              | d = 70      | D = 125      | T = 33.25  | Tapered roller bearing                |
| FAG   | 32214-B-XL           | d = 70      | D = 125      | T = 33.25  | Tapered roller bearing                |
| FAG   | 32214-DY             | d = 70      | D = 125      | T = 33.25  | Tapered roller bearing                |
| FAG   | 32214-H              | d = 70      | D = 125      | T = 33.25  | Tapered roller bearing                |
| FAG   | 32214-XL             | d = 70      | D = 125      | T = 33.25  | Tapered roller bearing                |
| FAG   | T5DD070              | d = 70      | D = 125      | T = 37     | Tapered roller bearing                |
| FAG   | 33214                | d = 70      | D = 125      | T = 41     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 33214-H              | d = 70      | D = 125      | T = 41     | Tapered roller bearing                |
| FAG   | 33214-TVP            | d = 70      | D = 125      | T = 41     | Tapered roller bearing                |
| KOYO  | 46T30214JR/48.5      | d = 70      | D = 125      | T = 59     | Tapered roller bearing                |
| KOYO  | 46T32214JR/61.5      | d = 70      | D = 125      | T = 74     | Tapered roller bearing                |
| FAG   | T5ED070              | d = 70      | D = 130      | T = 42     | Tapered roller bearing                |
| FAG   | T7FC070-XL           | d = 70      | D = 140      | T = 39     | Tapered roller bearing                |
| FAG   | T7FC070-XL-S1        | d = 70      | D = 140      | T = 39     | Tapered roller bearing                |
| FAG   | T7FC070-XL-S1>A      | d = 70      | D = 140      | T = 39     | Tapered roller bearing                |
| FAG   | T7FC070-XL>A         | d = 70      | D = 140      | T = 39     | Tapered roller bearing                |
| FAG   | T7FC070-XL>B         | d = 70      | D = 140      | T = 39     | Tapered roller bearing                |
| FAG   | T7FC070-XL>C         | d = 70      | D = 140      | T = 39     | Tapered roller bearing                |
| FAG   | T4FE070              | d = 70      | D = 140      | T = 52     | Tapered roller bearing                |
| FAG   | 30314-A              | d = 70      | D = 150      | T = 38     | Tapered roller bearing                |
| FAG   | 30314-DY             | d = 70      | D = 150      | T = 38     | Tapered roller bearing                |
| FAG   | 30314-H              | d = 70      | D = 150      | T = 38     | Tapered roller bearing                |
| FAG   | 31314-A              | d = 70      | D = 150      | T = 38     | Tapered roller bearing                |
| FAG   | 31314-H              | d = 70      | D = 150      | T = 38     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 31314-XL             | d = 70      | D = 150      | T = 38     | Tapered roller bearing                |
| FAG   | 31314-XL-S1          | d = 70      | D = 150      | T = 38     | Tapered roller bearing                |
| FAG   | 31314-XL>A           | d = 70      | D = 150      | T = 38     | Tapered roller bearing                |
| FAG   | 31314-XL>B           | d = 70      | D = 150      | T = 38     | Tapered roller bearing                |
| FAG   | 32314-A              | d = 70      | D = 150      | T = 54     | Tapered roller bearing                |
| FAG   | 32314-BA             | d = 70      | D = 150      | T = 54     | Tapered roller bearing                |
| FAG   | 32314-DY             | d = 70      | D = 150      | T = 54     | Tapered roller bearing                |
| FAG   | 32314-H              | d = 70      | D = 150      | T = 54     | Tapered roller bearing                |
| FAG   | 32314-XL             | d = 70      | D = 150      | T = 54     | Tapered roller bearing                |
| FAG   | 32314-XL-W215D       | d = 70      | D = 150      | T = 54     | Tapered roller bearing                |
| KOYO  | 46T30314DJR/57       | d = 70      | D = 150      | T = 83     | Tapered roller bearing                |
| KOYO  | 46T30314JR/67        | d = 70      | D = 150      | T = 83     | Tapered roller bearing                |
| KOYO  | 46T32314JR/92        | d = 70      | D = 150      | T = 116    | Tapered roller bearing                |
| FAG   | AKHM813849-HM813810  | d = 71.437  | D = 127      | T = 36.512 | Tapered roller bearing                |
| FAG   | K645-632             | d = 71.437  | D = 136.525  | T = 41.275 | Tapered roller bearing                |
| FAG   | K47490-47420         | d = 71.438  | D = 120      | T = 32.545 | Tapered roller bearing                |
| FAG   | KH715345-H715311     | d = 71.438  | D = 136.525  | T = 46.038 | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation       | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | KH715345-H715311-XL-W215FD | d = 71.438  | D = 136.525  | T = 46.038 | Tapered roller bearing                |
| FAG   | K29685-29620               | d = 73.025  | D = 112.712  | T = 25.4   | Tapered roller bearing                |
| FAG   | K33287-33462               | d = 73.025  | D = 117.475  | T = 30.162 | Tapered roller bearing                |
| FAG   | K33287-33462-W60C          | d = 73.025  | D = 117.475  | T = 30.162 | Tapered roller bearing                |
| FAG   | K567-563                   | d = 73.025  | D = 127      | T = 36.512 | Tapered roller bearing                |
| FAG   | K657-653                   | d = 73.025  | D = 146.05   | T = 41.275 | Tapered roller bearing                |
| FAG   | K6460-6420                 | d = 73.025  | D = 149.225  | T = 53.975 | Tapered roller bearing                |
| FAG   | AK744-742                  | d = 73.025  | D = 150.089  | T = 44.45  | Tapered roller bearing                |
| FAG   | K29688-29620               | d = 73.817  | D = 112.712  | T = 25.4   | Tapered roller bearing                |
| FAG   | K568-563                   | d = 73.817  | D = 127      | T = 36.512 | Tapered roller bearing                |
| FAG   | 32915                      | d = 75      | D = 105      | T = 20     | Tapered roller bearing                |
| FAG   | 32915-H                    | d = 75      | D = 105      | T = 20     | Tapered roller bearing                |
| FAG   | 32915-XL                   | d = 75      | D = 105      | T = 20     | Tapered roller bearing                |
| FAG   | T4CB075                    | d = 75      | D = 115      | T = 21     | Tapered roller bearing                |
| FAG   | 32015-X                    | d = 75      | D = 115      | T = 25     | Tapered roller bearing                |
| FAG   | 32015-X-H                  | d = 75      | D = 115      | T = 25     | Tapered roller bearing                |
| FAG   | 32015-X-XL                 | d = 75      | D = 115      | T = 25     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 32015-X-XL-P5        | d = 75      | D = 115      | T = 25     | Tapered roller bearing                |
| FAG   | 32015-X-XL-S1        | d = 75      | D = 115      | T = 25     | Tapered roller bearing                |
| FAG   | 32015-X>A            | d = 75      | D = 115      | T = 25     | Tapered roller bearing                |
| FAG   | T2CC075              | d = 75      | D = 115      | T = 25     | Tapered roller bearing                |
| KOYO  | 46215                | d = 75      | D = 115      | T = 30     | Tapered roller bearing                |
| FAG   | 33015                | d = 75      | D = 115      | T = 31     | Tapered roller bearing                |
| FAG   | 33015-H              | d = 75      | D = 115      | T = 31     | Tapered roller bearing                |
| FAG   | 33015-XL             | d = 75      | D = 115      | T = 31     | Tapered roller bearing                |
| KOYO  | 46215A               | d = 75      | D = 115      | T = 38     | Tapered roller bearing                |
| FAG   | T2DD075              | d = 75      | D = 125      | T = 34     | Tapered roller bearing                |
| FAG   | 33115                | d = 75      | D = 125      | T = 37     | Tapered roller bearing                |
| FAG   | 33115-H              | d = 75      | D = 125      | T = 37     | Tapered roller bearing                |
| FAG   | 33115>A              | d = 75      | D = 125      | T = 37     | Tapered roller bearing                |
| FAG   | 33115>B              | d = 75      | D = 125      | T = 37     | Tapered roller bearing                |
| FAG   | 30215-A              | d = 75      | D = 130      | T = 27.25  | Tapered roller bearing                |
| FAG   | 30215-A-P5           | d = 75      | D = 130      | T = 27.25  | Tapered roller bearing                |
| FAG   | 30215-A>A            | d = 75      | D = 130      | T = 27.25  | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 30215-H              | d = 75      | D = 130      | T = 27.25  | Tapered roller bearing                |
| FAG   | 30215-XL             | d = 75      | D = 130      | T = 27.25  | Tapered roller bearing                |
| FAG   | 30215-XL-S1          | d = 75      | D = 130      | T = 27.25  | Tapered roller bearing                |
| FAG   | 32215-A              | d = 75      | D = 130      | T = 33.25  | Tapered roller bearing                |
| FAG   | 32215-A-P5           | d = 75      | D = 130      | T = 33.25  | Tapered roller bearing                |
| FAG   | 32215-H              | d = 75      | D = 130      | T = 33.25  | Tapered roller bearing                |
| FAG   | 32215-XL             | d = 75      | D = 130      | T = 33.25  | Tapered roller bearing                |
| FAG   | T5DD075              | d = 75      | D = 130      | T = 37     | Tapered roller bearing                |
| FAG   | 33215-H              | d = 75      | D = 130      | T = 41     | Tapered roller bearing                |
| FAG   | 33215-XL             | d = 75      | D = 130      | T = 41     | Tapered roller bearing                |
| KOYO  | 46T30215JR/51.5      | d = 75      | D = 130      | T = 62     | Tapered roller bearing                |
| KOYO  | 46T32215JR/61.5      | d = 75      | D = 130      | T = 74     | Tapered roller bearing                |
| FAG   | T5ED075              | d = 75      | D = 135      | T = 42     | Tapered roller bearing                |
| FAG   | T2ED075              | d = 75      | D = 135      | T = 43     | Tapered roller bearing                |
| FAG   | T3FE075              | d = 75      | D = 145      | T = 52     | Tapered roller bearing                |
| FAG   | T7FC075-XL           | d = 75      | D = 150      | T = 42     | Tapered roller bearing                |
| FAG   | T7FC075-XL-S1        | d = 75      | D = 150      | T = 42     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 30315-A              | d = 75      | D = 160      | T = 40     | Tapered roller bearing                |
| FAG   | 30315-A>A            | d = 75      | D = 160      | T = 40     | Tapered roller bearing                |
| FAG   | 30315-H              | d = 75      | D = 160      | T = 40     | Tapered roller bearing                |
| FAG   | 31315                | d = 75      | D = 160      | T = 40     | Tapered roller bearing                |
| FAG   | 31315-H              | d = 75      | D = 160      | T = 40     | Tapered roller bearing                |
| FAG   | 31315-XL             | d = 75      | D = 160      | T = 40     | Tapered roller bearing                |
| FAG   | 31315-XL>A           | d = 75      | D = 160      | T = 40     | Tapered roller bearing                |
| FAG   | 31315-XL>B           | d = 75      | D = 160      | T = 40     | Tapered roller bearing                |
| FAG   | 32315-A              | d = 75      | D = 160      | T = 58     | Tapered roller bearing                |
| FAG   | 32315-B              | d = 75      | D = 160      | T = 58     | Tapered roller bearing                |
| FAG   | 32315-H              | d = 75      | D = 160      | T = 58     | Tapered roller bearing                |
| KOYO  | 46T30315JR/69        | d = 75      | D = 160      | T = 87     | Tapered roller bearing                |
| KOYO  | 46T32315JR/99        | d = 75      | D = 160      | T = 125    | Tapered roller bearing                |
| FAG   | KHM215249-HM215210   | d = 75.987  | D = 131.975  | T = 39     | Tapered roller bearing                |
| FAG   | KL814749-L814710     | d = 76.2    | D = 109.538  | T = 19.05  | Tapered roller bearing                |
| FAG   | K34300-34478         | d = 76.2    | D = 121.442  | T = 24.607 | Tapered roller bearing                |
| FAG   | K34300-34479         | d = 76.2    | D = 121.442  | T = 24.607 | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation       | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | K34301-34478               | d = 76.2    | D = 121.442  | T = 24.607 | Tapered roller bearing                |
| FAG   | K34300-34492-A             | d = 76.2    | D = 125.052  | T = 23.731 | Tapered roller bearing                |
| FAG   | K42687-42620               | d = 76.2    | D = 127      | T = 30.163 | Tapered roller bearing                |
| FAG   | AK495-A-492-A              | d = 76.2    | D = 133.35   | T = 30.163 | Tapered roller bearing                |
| FAG   | AK47679-47620              | d = 76.2    | D = 133.35   | T = 33.338 | Tapered roller bearing                |
| FAG   | KHM516442-HM516410         | d = 76.2    | D = 133.35   | T = 39.688 | Tapered roller bearing                |
| FAG   | K5760-5735                 | d = 76.2    | D = 135.733  | T = 44.45  | Tapered roller bearing                |
| FAG   | AK495-A-493                | d = 76.2    | D = 136.525  | T = 30.163 | Tapered roller bearing                |
| FAG   | KH715346-H715311-XL-W215FD | d = 76.2    | D = 136.525  | T = 46.038 | Tapered roller bearing                |
| FAG   | K575-572-X                 | d = 76.2    | D = 139.7    | T = 36.512 | Tapered roller bearing                |
| FAG   | K575-572                   | d = 76.2    | D = 139.992  | T = 36.512 | Tapered roller bearing                |
| FAG   | KHM515745-HM515716         | d = 76.2    | D = 142.138  | T = 44.45  | Tapered roller bearing                |
| FAG   | K6461-6420                 | d = 76.2    | D = 149.225  | T = 53.975 | Tapered roller bearing                |
| FAG   | K6466-6420                 | d = 76.2    | D = 149.225  | T = 53.975 | Tapered roller bearing                |
| FAG   | K9285-9220                 | d = 76.2    | D = 161.925  | T = 49.212 | Tapered roller bearing                |
| FAG   | K9285-9220-W215FD          | d = 76.2    | D = 161.925  | T = 49.212 | Tapered roller bearing                |
| FAG   | K9285-9220-XL              | d = 76.2    | D = 161.925  | T = 49.212 | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | K9285-9220-XL-W215FD | d = 76.2    | D = 161.925  | T = 49.212 | Tapered roller bearing                |
| FAG   | K6575-6535           | d = 76.2    | D = 161.925  | T = 53.975 | Tapered roller bearing                |
| FAG   | K6576-6535-XL-W215FD | d = 76.2    | D = 161.925  | T = 53.975 | Tapered roller bearing                |
| FAG   | K9380-9321           | d = 76.2    | D = 171.45   | T = 49.213 | Tapered roller bearing                |
| FAG   | KH917840-H917810     | d = 76.2    | D = 180.975  | T = 53.975 | Tapered roller bearing                |
| FAG   | KLM814849-LM814810   | d = 77.788  | D = 117.475  | T = 25.4   | Tapered roller bearing                |
| FAG   | K34306-34478         | d = 77.788  | D = 121.442  | T = 24.607 | Tapered roller bearing                |
| FAG   | K34306-34478-XL      | d = 77.788  | D = 121.442  | T = 24.607 | Tapered roller bearing                |
| FAG   | KH816249-H816210     | d = 77.788  | D = 165      | T = 49.5   | Tapered roller bearing                |
| FAG   | KHH221431-HH221410   | d = 79.375  | D = 190.5    | T = 57.15  | Tapered roller bearing                |
| FAG   | KHM218238-HM218210   | d = 79.974  | D = 146.975  | T = 40     | Tapered roller bearing                |
| FAG   | K578-572             | d = 79.985  | D = 139.992  | T = 36.512 | Tapered roller bearing                |
| FAG   | 32916                | d = 80      | D = 110      | T = 20     | Tapered roller bearing                |
| FAG   | 32916-H              | d = 80      | D = 110      | T = 20     | Tapered roller bearing                |
| FAG   | T2CC080              | d = 80      | D = 120      | T = 25     | Tapered roller bearing                |
| FAG   | T4CB080              | d = 80      | D = 125      | T = 24     | Tapered roller bearing                |
| FAG   | 32016-X-H            | d = 80      | D = 125      | T = 29     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 32016-X-TVP          | d = 80      | D = 125      | T = 29     | Tapered roller bearing                |
| FAG   | 32016-X-XL           | d = 80      | D = 125      | T = 29     | Tapered roller bearing                |
| FAG   | 32016-X-XL-J30PC     | d = 80      | D = 125      | T = 29     | Tapered roller bearing                |
| FAG   | 32016-X-XL-P5        | d = 80      | D = 125      | T = 29     | Tapered roller bearing                |
| FAG   | 32016-X-XL-S1        | d = 80      | D = 125      | T = 29     | Tapered roller bearing                |
| FAG   | 32016-X-XL>A         | d = 80      | D = 125      | T = 29     | Tapered roller bearing                |
| FAG   | 32016-XDY            | d = 80      | D = 125      | T = 29     | Tapered roller bearing                |
| KOYO  | 46216                | d = 80      | D = 125      | T = 34     | Tapered roller bearing                |
| FAG   | 33016                | d = 80      | D = 125      | T = 36     | Tapered roller bearing                |
| FAG   | 33016-H              | d = 80      | D = 125      | T = 36     | Tapered roller bearing                |
| FAG   | 33016-P5             | d = 80      | D = 125      | T = 36     | Tapered roller bearing                |
| FAG   | 33016-XL             | d = 80      | D = 125      | T = 36     | Tapered roller bearing                |
| FAG   | T2DD080              | d = 80      | D = 130      | T = 34     | Tapered roller bearing                |
| FAG   | 33116                | d = 80      | D = 130      | T = 37     | Tapered roller bearing                |
| FAG   | 33116-DY             | d = 80      | D = 130      | T = 37     | Tapered roller bearing                |
| FAG   | 33116-H              | d = 80      | D = 130      | T = 37     | Tapered roller bearing                |
| FAG   | T5DD080              | d = 80      | D = 135      | T = 37     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 30216-A              | d = 80      | D = 140      | T = 28.25  | Tapered roller bearing                |
| FAG   | 30216-A-P5           | d = 80      | D = 140      | T = 28.25  | Tapered roller bearing                |
| FAG   | 30216-A>A            | d = 80      | D = 140      | T = 28.25  | Tapered roller bearing                |
| FAG   | 30216-H              | d = 80      | D = 140      | T = 28.25  | Tapered roller bearing                |
| FAG   | 30216-XL             | d = 80      | D = 140      | T = 28.25  | Tapered roller bearing                |
| FAG   | 30216-XL-P5          | d = 80      | D = 140      | T = 28.25  | Tapered roller bearing                |
| FAG   | 30216-XL-S1          | d = 80      | D = 140      | T = 28.25  | Tapered roller bearing                |
| FAG   | 32216-A              | d = 80      | D = 140      | T = 35.25  | Tapered roller bearing                |
| FAG   | 32216-A-P5           | d = 80      | D = 140      | T = 35.25  | Tapered roller bearing                |
| FAG   | 32216-A>A            | d = 80      | D = 140      | T = 35.25  | Tapered roller bearing                |
| FAG   | 32216-H              | d = 80      | D = 140      | T = 35.25  | Tapered roller bearing                |
| FAG   | 32216-XL             | d = 80      | D = 140      | T = 35.25  | Tapered roller bearing                |
| FAG   | 32216-XL-P5          | d = 80      | D = 140      | T = 35.25  | Tapered roller bearing                |
| FAG   | 32216-XL-S1          | d = 80      | D = 140      | T = 35.25  | Tapered roller bearing                |
| FAG   | T5ED080              | d = 80      | D = 140      | T = 42     | Tapered roller bearing                |
| FAG   | 33216                | d = 80      | D = 140      | T = 46     | Tapered roller bearing                |
| FAG   | 33216-H              | d = 80      | D = 140      | T = 46     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 33216-XL             | d = 80      | D = 140      | T = 46     | Tapered roller bearing                |
| KOYO  | 46T30216JR/51.5      | d = 80      | D = 140      | T = 64     | Tapered roller bearing                |
| KOYO  | 46T32216JR/63.5      | d = 80      | D = 140      | T = 78     | Tapered roller bearing                |
| FAG   | T2ED080              | d = 80      | D = 145      | T = 46     | Tapered roller bearing                |
| FAG   | T4FE080              | d = 80      | D = 150      | T = 52     | Tapered roller bearing                |
| FAG   | T7FC080-XL           | d = 80      | D = 160      | T = 45     | Tapered roller bearing                |
| FAG   | T7FC080-XL-S1        | d = 80      | D = 160      | T = 45     | Tapered roller bearing                |
| FAG   | 30316-A              | d = 80      | D = 170      | T = 42.5   | Tapered roller bearing                |
| FAG   | 30316-H              | d = 80      | D = 170      | T = 42.5   | Tapered roller bearing                |
| FAG   | 31316                | d = 80      | D = 170      | T = 42.5   | Tapered roller bearing                |
| FAG   | 31316-H              | d = 80      | D = 170      | T = 42.5   | Tapered roller bearing                |
| FAG   | 31316-XL             | d = 80      | D = 170      | T = 42.5   | Tapered roller bearing                |
| FAG   | 31316-XL-S1          | d = 80      | D = 170      | T = 42.5   | Tapered roller bearing                |
| FAG   | 31316-XL>A           | d = 80      | D = 170      | T = 42.5   | Tapered roller bearing                |
| FAG   | 31316-XL>B           | d = 80      | D = 170      | T = 42.5   | Tapered roller bearing                |
| FAG   | 32316-A              | d = 80      | D = 170      | T = 61.5   | Tapered roller bearing                |
| FAG   | 32316-A>A            | d = 80      | D = 170      | T = 61.5   | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 32316-B              | d = 80      | D = 170      | T = 61.5   | Tapered roller bearing                |
| FAG   | 32316-B>A            | d = 80      | D = 170      | T = 61.5   | Tapered roller bearing                |
| FAG   | 32316-H              | d = 80      | D = 170      | T = 61.5   | Tapered roller bearing                |
| FAG   | 32316-XL             | d = 80      | D = 170      | T = 61.5   | Tapered roller bearing                |
| KOYO  | 46T30316JR/73        | d = 80      | D = 170      | T = 92     | Tapered roller bearing                |
| FAG   | AK496-493            | d = 80.962  | D = 136.525  | T = 30.163 | Tapered roller bearing                |
| FAG   | KHM516447-HM516410   | d = 80.963  | D = 133.35   | T = 39.688 | Tapered roller bearing                |
| FAG   | KLL116249-LL116210   | d = 82.55   | D = 114.3    | T = 15.083 | Tapered roller bearing                |
| FAG   | AK47686-47620        | d = 82.55   | D = 133.35   | T = 33.338 | Tapered roller bearing                |
| FAG   | AK47686-47620-XL     | d = 82.55   | D = 133.35   | T = 33.338 | Tapered roller bearing                |
| FAG   | AK495-493            | d = 82.55   | D = 136.525  | T = 30.163 | Tapered roller bearing                |
| FAG   | K580-572-X           | d = 82.55   | D = 139.7    | T = 36.512 | Tapered roller bearing                |
| FAG   | K580-572             | d = 82.55   | D = 139.992  | T = 36.512 | Tapered roller bearing                |
| FAG   | K595-592             | d = 82.55   | D = 152.4    | T = 39.688 | Tapered roller bearing                |
| FAG   | K6559-6535-XL-W215FD | d = 82.55   | D = 161.925  | T = 53.975 | Tapered roller bearing                |
| FAG   | K27690-27620-DY      | d = 83.345  | D = 125.412  | T = 25.4   | Tapered roller bearing                |
| FAG   | AK498-493            | d = 84.138  | D = 136.525  | T = 30.163 | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | KH919942-H919911     | d = 84.138  | D = 193.675  | T = 52     | Tapered roller bearing                |
| FAG   | K27695-27620         | d = 84.975  | D = 125.412  | T = 25.4   | Tapered roller bearing                |
| FAG   | K27695-27620-XL      | d = 84.975  | D = 125.412  | T = 25.4   | Tapered roller bearing                |
| FAG   | 32917                | d = 85      | D = 120      | T = 23     | Tapered roller bearing                |
| FAG   | 32917-H              | d = 85      | D = 120      | T = 23     | Tapered roller bearing                |
| FAG   | 32917-P5             | d = 85      | D = 120      | T = 23     | Tapered roller bearing                |
| FAG   | T2CC085              | d = 85      | D = 125      | T = 25     | Tapered roller bearing                |
| FAG   | T4CB085              | d = 85      | D = 130      | T = 24     | Tapered roller bearing                |
| FAG   | 32017-X-H            | d = 85      | D = 130      | T = 29     | Tapered roller bearing                |
| FAG   | 32017-X-XL           | d = 85      | D = 130      | T = 29     | Tapered roller bearing                |
| FAG   | 32017-X-XL-P5        | d = 85      | D = 130      | T = 29     | Tapered roller bearing                |
| FAG   | 32017-X-XL>A         | d = 85      | D = 130      | T = 29     | Tapered roller bearing                |
| FAG   | 33017                | d = 85      | D = 130      | T = 36     | Tapered roller bearing                |
| FAG   | 33017-H              | d = 85      | D = 130      | T = 36     | Tapered roller bearing                |
| FAG   | 33017>A              | d = 85      | D = 130      | T = 36     | Tapered roller bearing                |
| FAG   | T2DD085              | d = 85      | D = 135      | T = 34     | Tapered roller bearing                |
| FAG   | T5DD085              | d = 85      | D = 140      | T = 37     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 33117                | d = 85      | D = 140      | T = 41     | Tapered roller bearing                |
| FAG   | 33117-H              | d = 85      | D = 140      | T = 41     | Tapered roller bearing                |
| FAG   | 33117-XL             | d = 85      | D = 140      | T = 41     | Tapered roller bearing                |
| FAG   | T5ED085              | d = 85      | D = 145      | T = 42     | Tapered roller bearing                |
| FAG   | 30217-A              | d = 85      | D = 150      | T = 30.5   | Tapered roller bearing                |
| FAG   | 30217-A-P5           | d = 85      | D = 150      | T = 30.5   | Tapered roller bearing                |
| FAG   | 30217-A>A            | d = 85      | D = 150      | T = 30.5   | Tapered roller bearing                |
| FAG   | 30217-DY             | d = 85      | D = 150      | T = 30.5   | Tapered roller bearing                |
| FAG   | 30217-H              | d = 85      | D = 150      | T = 30.5   | Tapered roller bearing                |
| FAG   | 30217-XL-P5          | d = 85      | D = 150      | T = 30.5   | Tapered roller bearing                |
| FAG   | 30217-XL-S1          | d = 85      | D = 150      | T = 30.5   | Tapered roller bearing                |
| FAG   | 32217-A              | d = 85      | D = 150      | T = 38.5   | Tapered roller bearing                |
| FAG   | 32217-H              | d = 85      | D = 150      | T = 38.5   | Tapered roller bearing                |
| FAG   | 32217-XL             | d = 85      | D = 150      | T = 38.5   | Tapered roller bearing                |
| FAG   | 32217-XL-P5          | d = 85      | D = 150      | T = 38.5   | Tapered roller bearing                |
| FAG   | 32217-XL-S1          | d = 85      | D = 150      | T = 38.5   | Tapered roller bearing                |
| FAG   | 32217-XL>A           | d = 85      | D = 150      | T = 38.5   | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 32217-XL>B           | d = 85      | D = 150      | T = 38.5   | Tapered roller bearing                |
| FAG   | T2ED085              | d = 85      | D = 150      | T = 46     | Tapered roller bearing                |
| FAG   | T2ED085>A            | d = 85      | D = 150      | T = 46     | Tapered roller bearing                |
| FAG   | 33217                | d = 85      | D = 150      | T = 49     | Tapered roller bearing                |
| FAG   | 33217-H              | d = 85      | D = 150      | T = 49     | Tapered roller bearing                |
| FAG   | 33217-J30PC          | d = 85      | D = 150      | T = 49     | Tapered roller bearing                |
| FAG   | 33217-XL             | d = 85      | D = 150      | T = 49     | Tapered roller bearing                |
| FAG   | 33217-XL-S1          | d = 85      | D = 150      | T = 49     | Tapered roller bearing                |
| KOYO  | 46T30217JR/57        | d = 85      | D = 150      | T = 70     | Tapered roller bearing                |
| KOYO  | 46T32217JR/69        | d = 85      | D = 150      | T = 86     | Tapered roller bearing                |
| FAG   | T3FE085              | d = 85      | D = 160      | T = 55     | Tapered roller bearing                |
| FAG   | T7FC085-XL           | d = 85      | D = 170      | T = 48     | Tapered roller bearing                |
| FAG   | 30317-A              | d = 85      | D = 180      | T = 44.5   | Tapered roller bearing                |
| FAG   | 30317-H              | d = 85      | D = 180      | T = 44.5   | Tapered roller bearing                |
| FAG   | 31317                | d = 85      | D = 180      | T = 44.5   | Tapered roller bearing                |
| FAG   | 31317-H              | d = 85      | D = 180      | T = 44.5   | Tapered roller bearing                |
| FAG   | 31317-XL             | d = 85      | D = 180      | T = 44.5   | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 31317-XL>A           | d = 85      | D = 180      | T = 44.5   | Tapered roller bearing                |
| FAG   | 32317-A>A            | d = 85      | D = 180      | T = 63.5   | Tapered roller bearing                |
| FAG   | 32317-B-XL           | d = 85      | D = 180      | T = 63.5   | Tapered roller bearing                |
| FAG   | 32317-H              | d = 85      | D = 180      | T = 63.5   | Tapered roller bearing                |
| FAG   | 32317-XL             | d = 85      | D = 180      | T = 63.5   | Tapered roller bearing                |
| FAG   | 32317-XL>A           | d = 85      | D = 180      | T = 63.5   | Tapered roller bearing                |
| KOYO  | 46T30317JR/77        | d = 85      | D = 180      | T = 98     | Tapered roller bearing                |
| KOYO  | 46T32317JR/108       | d = 85      | D = 180      | T = 137    | Tapered roller bearing                |
| FAG   | K90334-90744         | d = 85      | D = 188.912  | T = 53.297 | Tapered roller bearing                |
| FAG   | K497-492-A           | d = 85.725  | D = 133.35   | T = 30.162 | Tapered roller bearing                |
| FAG   | KHM617049-HM617010   | d = 85.725  | D = 142.138  | T = 42.863 | Tapered roller bearing                |
| FAG   | K596-592-A           | d = 85.725  | D = 152.4    | T = 39.688 | Tapered roller bearing                |
| FAG   | KLL217849-LL217810   | d = 88.9    | D = 121.442  | T = 15.083 | Tapered roller bearing                |
| FAG   | KL217849-L217813     | d = 88.9    | D = 127      | T = 20.638 | Tapered roller bearing                |
| FAG   | K593-592-A           | d = 88.9    | D = 152.4    | T = 39.688 | Tapered roller bearing                |
| FAG   | K593-592-W215D       | d = 88.9    | D = 152.4    | T = 39.688 | Tapered roller bearing                |
| FAG   | K593-A-592-A         | d = 88.9    | D = 152.4    | T = 39.688 | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | K6580-6535           | d = 88.9    | D = 161.925  | T = 53.975 | Tapered roller bearing                |
| FAG   | K759-753             | d = 88.9    | D = 168.275  | T = 47.625 | Tapered roller bearing                |
| FAG   | K98350-98788-XL      | d = 88.9    | D = 200      | T = 52.761 | Tapered roller bearing                |
| FAG   | KHM218248-HM218210   | d = 89.975  | D = 146.975  | T = 40     | Tapered roller bearing                |
| FAG   | KHM218248-HM218210-H | d = 89.975  | D = 146.975  | T = 40     | Tapered roller bearing                |
| FAG   | K69354-69630         | d = 89.992  | D = 160.096  | T = 30.124 | Tapered roller bearing                |
| FAG   | 32918-H              | d = 90      | D = 125      | T = 23     | Tapered roller bearing                |
| FAG   | T4CB090              | d = 90      | D = 135      | T = 24     | Tapered roller bearing                |
| FAG   | 32018-X-H            | d = 90      | D = 140      | T = 32     | Tapered roller bearing                |
| FAG   | 32018-X-XL           | d = 90      | D = 140      | T = 32     | Tapered roller bearing                |
| FAG   | 32018-X-XL-P5        | d = 90      | D = 140      | T = 32     | Tapered roller bearing                |
| FAG   | 32018-X-XL-S1        | d = 90      | D = 140      | T = 32     | Tapered roller bearing                |
| FAG   | 32018-X-XL>A         | d = 90      | D = 140      | T = 32     | Tapered roller bearing                |
| FAG   | 32018-XA             | d = 90      | D = 140      | T = 32     | Tapered roller bearing                |
| FAG   | T2CD090              | d = 90      | D = 140      | T = 34     | Tapered roller bearing                |
| KOYO  | 46218                | d = 90      | D = 140      | T = 37     | Tapered roller bearing                |
| FAG   | 33018                | d = 90      | D = 140      | T = 39     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 33018-H              | d = 90      | D = 140      | T = 39     | Tapered roller bearing                |
| FAG   | 33018-P5             | d = 90      | D = 140      | T = 39     | Tapered roller bearing                |
| FAG   | 33018-XL             | d = 90      | D = 140      | T = 39     | Tapered roller bearing                |
| FAG   | 33018-XL-P5          | d = 90      | D = 140      | T = 39     | Tapered roller bearing                |
| FAG   | 33018>A              | d = 90      | D = 140      | T = 39     | Tapered roller bearing                |
| KOYO  | 46218A               | d = 90      | D = 140      | T = 46     | Tapered roller bearing                |
| FAG   | T5DD090              | d = 90      | D = 145      | T = 37     | Tapered roller bearing                |
| FAG   | T5ED090              | d = 90      | D = 150      | T = 42     | Tapered roller bearing                |
| FAG   | 33118                | d = 90      | D = 150      | T = 45     | Tapered roller bearing                |
| FAG   | 33118-H              | d = 90      | D = 150      | T = 45     | Tapered roller bearing                |
| FAG   | 33118-XL             | d = 90      | D = 150      | T = 45     | Tapered roller bearing                |
| FAG   | T2ED090              | d = 90      | D = 155      | T = 46     | Tapered roller bearing                |
| FAG   | 30218-A              | d = 90      | D = 160      | T = 32.5   | Tapered roller bearing                |
| FAG   | 30218-A-P5           | d = 90      | D = 160      | T = 32.5   | Tapered roller bearing                |
| FAG   | 30218-A>A            | d = 90      | D = 160      | T = 32.5   | Tapered roller bearing                |
| FAG   | 30218-H              | d = 90      | D = 160      | T = 32.5   | Tapered roller bearing                |
| FAG   | 30218-XL             | d = 90      | D = 160      | T = 32.5   | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 32218-A              | d = 90      | D = 160      | T = 42.5   | Tapered roller bearing                |
| FAG   | 32218-DY             | d = 90      | D = 160      | T = 42.5   | Tapered roller bearing                |
| FAG   | 32218-H              | d = 90      | D = 160      | T = 42.5   | Tapered roller bearing                |
| FAG   | 32218-XL             | d = 90      | D = 160      | T = 42.5   | Tapered roller bearing                |
| FAG   | 32218-XL-P5          | d = 90      | D = 160      | T = 42.5   | Tapered roller bearing                |
| FAG   | 32218-XL-S1          | d = 90      | D = 160      | T = 42.5   | Tapered roller bearing                |
| FAG   | 32218-XL>A           | d = 90      | D = 160      | T = 42.5   | Tapered roller bearing                |
| FAG   | K767-X-753-X         | d = 90      | D = 160      | T = 47.625 | Tapered roller bearing                |
| FAG   | 33218                | d = 90      | D = 160      | T = 55     | Tapered roller bearing                |
| FAG   | 33218-H              | d = 90      | D = 160      | T = 55     | Tapered roller bearing                |
| KOYO  | 46T30218JR/61        | d = 90      | D = 160      | T = 74     | Tapered roller bearing                |
| KOYO  | 46T32218JR/77        | d = 90      | D = 160      | T = 94     | Tapered roller bearing                |
| FAG   | K767-X-752           | d = 90      | D = 161.925  | T = 47.625 | Tapered roller bearing                |
| FAG   | T4FE090              | d = 90      | D = 165      | T = 55     | Tapered roller bearing                |
| FAG   | T7FC090-XL           | d = 90      | D = 175      | T = 48     | Tapered roller bearing                |
| FAG   | T7FC090-XL-S1        | d = 90      | D = 175      | T = 48     | Tapered roller bearing                |
| FAG   | 30318-A              | d = 90      | D = 190      | T = 46.5   | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 30318-H              | d = 90      | D = 190      | T = 46.5   | Tapered roller bearing                |
| FAG   | 31318                | d = 90      | D = 190      | T = 46.5   | Tapered roller bearing                |
| FAG   | 31318-H              | d = 90      | D = 190      | T = 46.5   | Tapered roller bearing                |
| FAG   | 31318-P5             | d = 90      | D = 190      | T = 46.5   | Tapered roller bearing                |
| FAG   | 31318-P5>A           | d = 90      | D = 190      | T = 46.5   | Tapered roller bearing                |
| FAG   | 31318-XL             | d = 90      | D = 190      | T = 46.5   | Tapered roller bearing                |
| FAG   | 31318-XL-P5          | d = 90      | D = 190      | T = 46.5   | Tapered roller bearing                |
| FAG   | 31318-XL-P5>A        | d = 90      | D = 190      | T = 46.5   | Tapered roller bearing                |
| FAG   | 31318-XL>A           | d = 90      | D = 190      | T = 46.5   | Tapered roller bearing                |
| FAG   | 31318>A              | d = 90      | D = 190      | T = 46.5   | Tapered roller bearing                |
| FAG   | 32318-A              | d = 90      | D = 190      | T = 67.5   | Tapered roller bearing                |
| FAG   | 32318-A-J20AA        | d = 90      | D = 190      | T = 67.5   | Tapered roller bearing                |
| FAG   | 32318-B              | d = 90      | D = 190      | T = 67.5   | Tapered roller bearing                |
| FAG   | 32318-H              | d = 90      | D = 190      | T = 67.5   | Tapered roller bearing                |
| FAG   | 32318-XL             | d = 90      | D = 190      | T = 67.5   | Tapered roller bearing                |
| KOYO  | 46T30318JR/81        | d = 90      | D = 190      | T = 102    | Tapered roller bearing                |
| KOYO  | 46T32318JR/115       | d = 90      | D = 190      | T = 144    | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | K47890-47820         | d = 92.075  | D = 146.05   | T = 33.338 | Tapered roller bearing                |
| FAG   | K42362-42584         | d = 92.075  | D = 148.43   | T = 28.575 | Tapered roller bearing                |
| FAG   | K598-A-593-X         | d = 92.075  | D = 150      | T = 35.992 | Tapered roller bearing                |
| FAG   | K598-592-A           | d = 92.075  | D = 152.4    | T = 39.688 | Tapered roller bearing                |
| FAG   | K598-592-A-XL        | d = 92.075  | D = 152.4    | T = 39.688 | Tapered roller bearing                |
| FAG   | K598-A-592-A         | d = 92.075  | D = 152.4    | T = 39.688 | Tapered roller bearing                |
| FAG   | K598-A-592-A-XL      | d = 92.075  | D = 152.4    | T = 39.688 | Tapered roller bearing                |
| FAG   | K681-672             | d = 92.075  | D = 168.275  | T = 41.275 | Tapered roller bearing                |
| FAG   | K778-772             | d = 92.075  | D = 180.975  | T = 47.625 | Tapered roller bearing                |
| FAG   | K42368-42584         | d = 93.662  | D = 148.43   | T = 28.575 | Tapered roller bearing                |
| FAG   | K42368-42584-XL      | d = 93.662  | D = 148.43   | T = 28.575 | Tapered roller bearing                |
| FAG   | 32919                | d = 95      | D = 130      | T = 23     | Tapered roller bearing                |
| FAG   | 32919-H              | d = 95      | D = 130      | T = 23     | Tapered roller bearing                |
| FAG   | 32919-P5             | d = 95      | D = 130      | T = 23     | Tapered roller bearing                |
| FAG   | 32919-XL             | d = 95      | D = 130      | T = 23     | Tapered roller bearing                |
| FAG   | T4CB095              | d = 95      | D = 140      | T = 24     | Tapered roller bearing                |
| FAG   | T2CC095              | d = 95      | D = 140      | T = 28     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 32019-X-H            | d = 95      | D = 145      | T = 32     | Tapered roller bearing                |
| FAG   | 32019-X-XL           | d = 95      | D = 145      | T = 32     | Tapered roller bearing                |
| FAG   | 32019-X-XL-P5        | d = 95      | D = 145      | T = 32     | Tapered roller bearing                |
| FAG   | 32019-X-XL>A         | d = 95      | D = 145      | T = 32     | Tapered roller bearing                |
| FAG   | T2CD095              | d = 95      | D = 145      | T = 34     | Tapered roller bearing                |
| FAG   | 33019                | d = 95      | D = 145      | T = 39     | Tapered roller bearing                |
| FAG   | 33019-H              | d = 95      | D = 145      | T = 39     | Tapered roller bearing                |
| FAG   | 33019-XL             | d = 95      | D = 145      | T = 39     | Tapered roller bearing                |
| FAG   | 33019>A              | d = 95      | D = 145      | T = 39     | Tapered roller bearing                |
| FAG   | T5DD095              | d = 95      | D = 150      | T = 37     | Tapered roller bearing                |
| FAG   | T5ED095              | d = 95      | D = 155      | T = 42     | Tapered roller bearing                |
| FAG   | 33119                | d = 95      | D = 160      | T = 49     | Tapered roller bearing                |
| FAG   | 33119-H              | d = 95      | D = 160      | T = 49     | Tapered roller bearing                |
| FAG   | 30219-A              | d = 95      | D = 170      | T = 34.5   | Tapered roller bearing                |
| FAG   | 30219-A-P5           | d = 95      | D = 170      | T = 34.5   | Tapered roller bearing                |
| FAG   | 30219-A>A            | d = 95      | D = 170      | T = 34.5   | Tapered roller bearing                |
| FAG   | 30219-H              | d = 95      | D = 170      | T = 34.5   | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 30219-XL             | d = 95      | D = 170      | T = 34.5   | Tapered roller bearing                |
| FAG   | 32219-A              | d = 95      | D = 170      | T = 45.5   | Tapered roller bearing                |
| FAG   | 32219-A-S1           | d = 95      | D = 170      | T = 45.5   | Tapered roller bearing                |
| FAG   | 32219-DY             | d = 95      | D = 170      | T = 45.5   | Tapered roller bearing                |
| FAG   | 32219-H              | d = 95      | D = 170      | T = 45.5   | Tapered roller bearing                |
| FAG   | 32219-XL             | d = 95      | D = 170      | T = 45.5   | Tapered roller bearing                |
| FAG   | 32219-XL-J30PC       | d = 95      | D = 170      | T = 45.5   | Tapered roller bearing                |
| FAG   | 32219-XL-S1          | d = 95      | D = 170      | T = 45.5   | Tapered roller bearing                |
| FAG   | 32219-XL>A           | d = 95      | D = 170      | T = 45.5   | Tapered roller bearing                |
| FAG   | T4FE095              | d = 95      | D = 170      | T = 55     | Tapered roller bearing                |
| FAG   | 33219                | d = 95      | D = 170      | T = 58     | Tapered roller bearing                |
| FAG   | 33219-H              | d = 95      | D = 170      | T = 58     | Tapered roller bearing                |
| FAG   | 33219>B              | d = 95      | D = 170      | T = 58     | Tapered roller bearing                |
| KOYO  | 46T30219JR/63        | d = 95      | D = 170      | T = 78     | Tapered roller bearing                |
| KOYO  | 46T32219JR/83        | d = 95      | D = 170      | T = 100    | Tapered roller bearing                |
| FAG   | T7FC095-XL           | d = 95      | D = 180      | T = 49     | Tapered roller bearing                |
| FAG   | T7FC095-XL-W60E      | d = 95      | D = 180      | T = 49     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation  | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|-----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 30319-A               | d = 95      | D = 200      | T = 49.5   | Tapered roller bearing                |
| FAG   | 30319-H               | d = 95      | D = 200      | T = 49.5   | Tapered roller bearing                |
| FAG   | 31319-A               | d = 95      | D = 200      | T = 49.5   | Tapered roller bearing                |
| FAG   | 31319-XL              | d = 95      | D = 200      | T = 49.5   | Tapered roller bearing                |
| FAG   | 31319-XL-S1           | d = 95      | D = 200      | T = 49.5   | Tapered roller bearing                |
| FAG   | 32319-A               | d = 95      | D = 200      | T = 71.5   | Tapered roller bearing                |
| FAG   | 32319-A-J30PC         | d = 95      | D = 200      | T = 71.5   | Tapered roller bearing                |
| FAG   | 32319-A-P5-J30PC      | d = 95      | D = 200      | T = 71.5   | Tapered roller bearing                |
| FAG   | 32319-B               | d = 95      | D = 200      | T = 71.5   | Tapered roller bearing                |
| FAG   | 32319-B-XL            | d = 95      | D = 200      | T = 71.5   | Tapered roller bearing                |
| FAG   | 32319-H               | d = 95      | D = 200      | T = 71.5   | Tapered roller bearing                |
| FAG   | 32319-XL              | d = 95      | D = 200      | T = 71.5   | Tapered roller bearing                |
| KOYO  | 46T30319JR/85         | d = 95      | D = 200      | T = 108    | Tapered roller bearing                |
| KOYO  | 46T32319JR/118        | d = 95      | D = 200      | T = 151    | Tapered roller bearing                |
| FAG   | KLL319349-LL319310    | d = 95.25   | D = 128.588  | T = 15.875 | Tapered roller bearing                |
| FAG   | KLL319349-LL319310-XL | d = 95.25   | D = 128.588  | T = 15.875 | Tapered roller bearing                |
| FAG   | KL319249-L319210      | d = 95.25   | D = 130.175  | T = 20.638 | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | K47896-47820         | d = 95.25   | D = 146.05   | T = 33.338 | Tapered roller bearing                |
| FAG   | K42375-42584         | d = 95.25   | D = 148.43   | T = 28.575 | Tapered roller bearing                |
| FAG   | K594-593-X           | d = 95.25   | D = 150      | T = 35.992 | Tapered roller bearing                |
| FAG   | K594-592-A           | d = 95.25   | D = 152.4    | T = 39.688 | Tapered roller bearing                |
| FAG   | K594-592-A-XL        | d = 95.25   | D = 152.4    | T = 39.688 | Tapered roller bearing                |
| FAG   | K594-A-592-A         | d = 95.25   | D = 152.4    | T = 39.688 | Tapered roller bearing                |
| FAG   | K594-A-592-A-XL      | d = 95.25   | D = 152.4    | T = 39.688 | Tapered roller bearing                |
| FAG   | K52375-52618         | d = 95.25   | D = 157.162  | T = 36.512 | Tapered roller bearing                |
| FAG   | K683-672             | d = 95.25   | D = 168.275  | T = 41.275 | Tapered roller bearing                |
| FAG   | K683-672-XL          | d = 95.25   | D = 168.275  | T = 41.275 | Tapered roller bearing                |
| FAG   | K77375-77675         | d = 95.25   | D = 171.45   | T = 47.625 | Tapered roller bearing                |
| FAG   | K864-854             | d = 95.25   | D = 190.5    | T = 57.15  | Tapered roller bearing                |
| FAG   | KHH221440-HH221410   | d = 95.25   | D = 190.5    | T = 57.15  | Tapered roller bearing                |
| FAG   | K90381-90744         | d = 96.838  | D = 188.912  | T = 50.8   | Tapered roller bearing                |
| FAG   | K52387-52618         | d = 98.425  | D = 157.162  | T = 36.512 | Tapered roller bearing                |
| FAG   | K685-672             | d = 98.425  | D = 168.275  | T = 41.275 | Tapered roller bearing                |
| FAG   | KHH421246-HH421210   | d = 98.425  | D = 184.15   | T = 63.5   | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | KHM220149-HM220110   | d = 99.975  | D = 156.975  | T = 42     | Tapered roller bearing                |
| FAG   | KHH224334-HH224310   | d = 99.975  | D = 212.725  | T = 66.675 | Tapered roller bearing                |
| FAG   | 32920                | d = 100     | D = 140      | T = 25     | Tapered roller bearing                |
| FAG   | 32920-H              | d = 100     | D = 140      | T = 25     | Tapered roller bearing                |
| FAG   | 32920-P5             | d = 100     | D = 140      | T = 25     | Tapered roller bearing                |
| FAG   | 32920>A              | d = 100     | D = 140      | T = 25     | Tapered roller bearing                |
| FAG   | T4CB100              | d = 100     | D = 145      | T = 24     | Tapered roller bearing                |
| FAG   | T4CB100-P5           | d = 100     | D = 145      | T = 24     | Tapered roller bearing                |
| FAG   | T4CB100-XL           | d = 100     | D = 145      | T = 24     | Tapered roller bearing                |
| FAG   | T2DC100              | d = 100     | D = 145      | T = 28     | Tapered roller bearing                |
| FAG   | 32020-X              | d = 100     | D = 150      | T = 32     | Tapered roller bearing                |
| FAG   | 32020-X-H            | d = 100     | D = 150      | T = 32     | Tapered roller bearing                |
| FAG   | 32020-X-XL           | d = 100     | D = 150      | T = 32     | Tapered roller bearing                |
| FAG   | 32020-X-XL-P5        | d = 100     | D = 150      | T = 32     | Tapered roller bearing                |
| FAG   | 32020-X-XL-P5>A      | d = 100     | D = 150      | T = 32     | Tapered roller bearing                |
| FAG   | 32020-X-XL>A         | d = 100     | D = 150      | T = 32     | Tapered roller bearing                |
| FAG   | 32020-X-XL>B         | d = 100     | D = 150      | T = 32     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 32020-X>A            | d = 100     | D = 150      | T = 32     | Tapered roller bearing                |
| FAG   | 32020-X>B            | d = 100     | D = 150      | T = 32     | Tapered roller bearing                |
| FAG   | T2CD100              | d = 100     | D = 150      | T = 34     | Tapered roller bearing                |
| FAG   | 33020                | d = 100     | D = 150      | T = 39     | Tapered roller bearing                |
| FAG   | 33020-H              | d = 100     | D = 150      | T = 39     | Tapered roller bearing                |
| FAG   | 33020-TVP            | d = 100     | D = 150      | T = 39     | Tapered roller bearing                |
| KOYO  | 46220A               | d = 100     | D = 150      | T = 46     | Tapered roller bearing                |
| FAG   | T5DD100              | d = 100     | D = 155      | T = 37     | Tapered roller bearing                |
| FAG   | K52394-X-52618       | d = 100     | D = 157.162  | T = 36.512 | Tapered roller bearing                |
| FAG   | T5ED100-XL           | d = 100     | D = 160      | T = 42     | Tapered roller bearing                |
| FAG   | T2EE100              | d = 100     | D = 165      | T = 47     | Tapered roller bearing                |
| FAG   | 33120                | d = 100     | D = 165      | T = 52     | Tapered roller bearing                |
| FAG   | 33120-H              | d = 100     | D = 165      | T = 52     | Tapered roller bearing                |
| KOYO  | 46320                | d = 100     | D = 165      | T = 52     | Tapered roller bearing                |
| KOYO  | 46320A               | d = 100     | D = 165      | T = 65     | Tapered roller bearing                |
| FAG   | T4FE100              | d = 100     | D = 175      | T = 55     | Tapered roller bearing                |
| FAG   | 30220-A              | d = 100     | D = 180      | T = 37     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 30220-A-P5           | d = 100     | D = 180      | T = 37     | Tapered roller bearing                |
| FAG   | 30220-A>A            | d = 100     | D = 180      | T = 37     | Tapered roller bearing                |
| FAG   | 30220-H              | d = 100     | D = 180      | T = 37     | Tapered roller bearing                |
| FAG   | 30220-XL             | d = 100     | D = 180      | T = 37     | Tapered roller bearing                |
| FAG   | 32220-A>A            | d = 100     | D = 180      | T = 49     | Tapered roller bearing                |
| FAG   | 32220-H              | d = 100     | D = 180      | T = 49     | Tapered roller bearing                |
| FAG   | 32220-H>R            | d = 100     | D = 180      | T = 49     | Tapered roller bearing                |
| FAG   | 32220-XL             | d = 100     | D = 180      | T = 49     | Tapered roller bearing                |
| FAG   | 32220-XL-J30PC       | d = 100     | D = 180      | T = 49     | Tapered roller bearing                |
| FAG   | 32220-XL-P5          | d = 100     | D = 180      | T = 49     | Tapered roller bearing                |
| FAG   | 32220-XL>A           | d = 100     | D = 180      | T = 49     | Tapered roller bearing                |
| FAG   | 33220                | d = 100     | D = 180      | T = 63     | Tapered roller bearing                |
| FAG   | 33220-H              | d = 100     | D = 180      | T = 63     | Tapered roller bearing                |
| FAG   | 33220-XL-S1          | d = 100     | D = 180      | T = 63     | Tapered roller bearing                |
| KOYO  | 46T30220JR/67        | d = 100     | D = 180      | T = 83     | Tapered roller bearing                |
| KOYO  | 46T32220JR/87        | d = 100     | D = 180      | T = 107    | Tapered roller bearing                |
| FAG   | 30320-A              | d = 100     | D = 215      | T = 51.5   | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 30320-H              | d = 100     | D = 215      | T = 51.5   | Tapered roller bearing                |
| FAG   | 30320-XL             | d = 100     | D = 215      | T = 51.5   | Tapered roller bearing                |
| FAG   | 31320-X              | d = 100     | D = 215      | T = 56.5   | Tapered roller bearing                |
| FAG   | 31320-X-H            | d = 100     | D = 215      | T = 56.5   | Tapered roller bearing                |
| FAG   | 31320-X-XL           | d = 100     | D = 215      | T = 56.5   | Tapered roller bearing                |
| FAG   | 32320-A              | d = 100     | D = 215      | T = 77.5   | Tapered roller bearing                |
| FAG   | 32320-A>A            | d = 100     | D = 215      | T = 77.5   | Tapered roller bearing                |
| FAG   | 32320-B-XL           | d = 100     | D = 215      | T = 77.5   | Tapered roller bearing                |
| FAG   | 32320-B-XL-S1        | d = 100     | D = 215      | T = 77.5   | Tapered roller bearing                |
| FAG   | 32320-H              | d = 100     | D = 215      | T = 77.5   | Tapered roller bearing                |
| FAG   | 32320-XL-S1          | d = 100     | D = 215      | T = 77.5   | Tapered roller bearing                |
| KOYO  | 46T30320JR/87        | d = 100     | D = 215      | T = 112    | Tapered roller bearing                |
| KOYO  | 46T32320JR/127       | d = 100     | D = 215      | T = 162    | Tapered roller bearing                |
| FAG   | KL420449-L420410     | d = 101.6   | D = 136.525  | T = 21.433 | Tapered roller bearing                |
| FAG   | K52400-52618         | d = 101.6   | D = 157.162  | T = 36.512 | Tapered roller bearing                |
| FAG   | K52401-52618         | d = 101.6   | D = 157.162  | T = 36.512 | Tapered roller bearing                |
| FAG   | K52400-52638         | d = 101.6   | D = 161.925  | T = 39.687 | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation         | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|------------------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | K52400-52638-XL              | d = 101.6   | D = 161.925  | T = 39.687 | Tapered roller bearing                |
| FAG   | K687-672                     | d = 101.6   | D = 168.275  | T = 41.275 | Tapered roller bearing                |
| FAG   | KHH221449-HH221410           | d = 101.6   | D = 190.5    | T = 57.15  | Tapered roller bearing                |
| FAG   | KHH221449-HH221410-XL        | d = 101.6   | D = 190.5    | T = 57.15  | Tapered roller bearing                |
| FAG   | KHH221449-HH221410-XL-W215FD | d = 101.6   | D = 190.5    | T = 57.15  | Tapered roller bearing                |
| FAG   | K941-932                     | d = 101.6   | D = 212.725  | T = 66.675 | Tapered roller bearing                |
| FAG   | K941-932-XL                  | d = 101.6   | D = 212.725  | T = 66.675 | Tapered roller bearing                |
| FAG   | KHH224335-HH224310           | d = 101.6   | D = 212.725  | T = 66.675 | Tapered roller bearing                |
| FAG   | K786-772                     | d = 104.775 | D = 180.975  | T = 47.625 | Tapered roller bearing                |
| FAG   | 32921                        | d = 105     | D = 145      | T = 25     | Tapered roller bearing                |
| FAG   | 32921-P5                     | d = 105     | D = 145      | T = 25     | Tapered roller bearing                |
| FAG   | 32921>A                      | d = 105     | D = 145      | T = 25     | Tapered roller bearing                |
| FAG   | T4CB105                      | d = 105     | D = 150      | T = 24     | Tapered roller bearing                |
| FAG   | T2CD105                      | d = 105     | D = 155      | T = 33     | Tapered roller bearing                |
| FAG   | 32021-X-H                    | d = 105     | D = 160      | T = 35     | Tapered roller bearing                |
| FAG   | 32021-X-XL                   | d = 105     | D = 160      | T = 35     | Tapered roller bearing                |
| FAG   | 32021-X-XL-P5                | d = 105     | D = 160      | T = 35     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 32021-X-XL-S1        | d = 105     | D = 160      | T = 35     | Tapered roller bearing                |
| FAG   | 32021-X-XL>A         | d = 105     | D = 160      | T = 35     | Tapered roller bearing                |
| FAG   | T5DD105              | d = 105     | D = 160      | T = 37     | Tapered roller bearing                |
| FAG   | T2DD105              | d = 105     | D = 160      | T = 38     | Tapered roller bearing                |
| FAG   | 33021                | d = 105     | D = 160      | T = 43     | Tapered roller bearing                |
| FAG   | 33021-TVP            | d = 105     | D = 160      | T = 43     | Tapered roller bearing                |
| FAG   | 33021-XL             | d = 105     | D = 160      | T = 43     | Tapered roller bearing                |
| FAG   | T4EE105              | d = 105     | D = 180      | T = 55     | Tapered roller bearing                |
| FAG   | 30221-A              | d = 105     | D = 190      | T = 39     | Tapered roller bearing                |
| FAG   | 30221-XL             | d = 105     | D = 190      | T = 39     | Tapered roller bearing                |
| FAG   | 32221-A              | d = 105     | D = 190      | T = 53     | Tapered roller bearing                |
| FAG   | 32221-H              | d = 105     | D = 190      | T = 53     | Tapered roller bearing                |
| FAG   | 32221-XL             | d = 105     | D = 190      | T = 53     | Tapered roller bearing                |
| FAG   | 32221-XL-S1          | d = 105     | D = 190      | T = 53     | Tapered roller bearing                |
| FAG   | 32221-XL>A           | d = 105     | D = 190      | T = 53     | Tapered roller bearing                |
| FAG   | 32221-XL>B           | d = 105     | D = 190      | T = 53     | Tapered roller bearing                |
| FAG   | 33221                | d = 105     | D = 190      | T = 68     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| KOYO  | 46T30221JR/70        | d = 105     | D = 190      | T = 88     | Tapered roller bearing                |
| KOYO  | 46T32221JR/95        | d = 105     | D = 190      | T = 115    | Tapered roller bearing                |
| FAG   | 30321-XL             | d = 105     | D = 225      | T = 53.5   | Tapered roller bearing                |
| FAG   | 31321-X              | d = 105     | D = 225      | T = 58     | Tapered roller bearing                |
| FAG   | 31321-X-XL           | d = 105     | D = 225      | T = 58     | Tapered roller bearing                |
| FAG   | 32321-A              | d = 105     | D = 225      | T = 81.5   | Tapered roller bearing                |
| KOYO  | 46T30321JR/91        | d = 105     | D = 225      | T = 116    | Tapered roller bearing                |
| KOYO  | 46T32321JR/133       | d = 105     | D = 225      | T = 170    | Tapered roller bearing                |
| FAG   | KL521949-L521910     | d = 107.95  | D = 146.05   | T = 21.433 | Tapered roller bearing                |
| FAG   | K48190-48120         | d = 107.95  | D = 161.925  | T = 34.925 | Tapered roller bearing                |
| FAG   | K56425-56650         | d = 107.95  | D = 165.1    | T = 36.512 | Tapered roller bearing                |
| FAG   | K56426-56650         | d = 107.95  | D = 165.1    | T = 36.512 | Tapered roller bearing                |
| FAG   | AK56425-56662-XL     | d = 107.95  | D = 168.275  | T = 36.512 | Tapered roller bearing                |
| FAG   | K936-932-XL          | d = 107.95  | D = 212.725  | T = 66.675 | Tapered roller bearing                |
| FAG   | KHH224340-HH224310   | d = 107.95  | D = 212.725  | T = 66.675 | Tapered roller bearing                |
| FAG   | K37431-A-37625       | d = 109.538 | D = 158.75   | T = 23.02  | Tapered roller bearing                |
| FAG   | K64432-64708         | d = 109.975 | D = 179.975  | T = 41.275 | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | KLM522549-LM522518   | d = 109.987 | D = 164.737  | T = 37.312 | Tapered roller bearing                |
| FAG   | K64433-64700         | d = 109.992 | D = 177.8    | T = 41.275 | Tapered roller bearing                |
| FAG   | 32922                | d = 110     | D = 150      | T = 25     | Tapered roller bearing                |
| FAG   | T4CB110              | d = 110     | D = 160      | T = 27     | Tapered roller bearing                |
| FAG   | T2CD110              | d = 110     | D = 160      | T = 33     | Tapered roller bearing                |
| FAG   | T2DD110              | d = 110     | D = 165      | T = 38     | Tapered roller bearing                |
| FAG   | 32022-X              | d = 110     | D = 170      | T = 38     | Tapered roller bearing                |
| FAG   | 32022-X-H            | d = 110     | D = 170      | T = 38     | Tapered roller bearing                |
| FAG   | 32022-X-XL           | d = 110     | D = 170      | T = 38     | Tapered roller bearing                |
| FAG   | 32022-X-XL-J30PC     | d = 110     | D = 170      | T = 38     | Tapered roller bearing                |
| FAG   | 32022-X-XL-P5        | d = 110     | D = 170      | T = 38     | Tapered roller bearing                |
| FAG   | 32022-X-XL>A         | d = 110     | D = 170      | T = 38     | Tapered roller bearing                |
| FAG   | 32022-X-XL>B         | d = 110     | D = 170      | T = 38     | Tapered roller bearing                |
| KOYO  | 46222                | d = 110     | D = 170      | T = 45     | Tapered roller bearing                |
| FAG   | 33022                | d = 110     | D = 170      | T = 47     | Tapered roller bearing                |
| FAG   | 33022-TVP            | d = 110     | D = 170      | T = 47     | Tapered roller bearing                |
| FAG   | T2EE110              | d = 110     | D = 175      | T = 47     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 33122                | d = 110     | D = 180      | T = 56     | Tapered roller bearing                |
| FAG   | 33122-XL             | d = 110     | D = 180      | T = 56     | Tapered roller bearing                |
| FAG   | 33122>A              | d = 110     | D = 180      | T = 56     | Tapered roller bearing                |
| KOYO  | 46322                | d = 110     | D = 180      | T = 56     | Tapered roller bearing                |
| KOYO  | 46322A               | d = 110     | D = 180      | T = 70     | Tapered roller bearing                |
| FAG   | T3FE110              | d = 110     | D = 190      | T = 58     | Tapered roller bearing                |
| FAG   | 30222-A              | d = 110     | D = 200      | T = 41     | Tapered roller bearing                |
| FAG   | 30222-A>A            | d = 110     | D = 200      | T = 41     | Tapered roller bearing                |
| FAG   | 30222-XL             | d = 110     | D = 200      | T = 41     | Tapered roller bearing                |
| FAG   | 32222-A              | d = 110     | D = 200      | T = 56     | Tapered roller bearing                |
| FAG   | 32222-A-P5           | d = 110     | D = 200      | T = 56     | Tapered roller bearing                |
| FAG   | 32222-H              | d = 110     | D = 200      | T = 56     | Tapered roller bearing                |
| FAG   | 32222-XL             | d = 110     | D = 200      | T = 56     | Tapered roller bearing                |
| FAG   | 32222-XL-J30PC       | d = 110     | D = 200      | T = 56     | Tapered roller bearing                |
| FAG   | 32222-XL-P5          | d = 110     | D = 200      | T = 56     | Tapered roller bearing                |
| FAG   | 32222-XL-S1          | d = 110     | D = 200      | T = 56     | Tapered roller bearing                |
| FAG   | 32222-XL>A           | d = 110     | D = 200      | T = 56     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation       | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------------|-------------|--------------|------------|---------------------------------------|
| KOYO  | 46T30222JR/74              | d = 110     | D = 200      | T = 92     | Tapered roller bearing                |
| KOYO  | 46T32222JR/101             | d = 110     | D = 200      | T = 121    | Tapered roller bearing                |
| FAG   | 30322-A                    | d = 110     | D = 240      | T = 54.5   | Tapered roller bearing                |
| FAG   | 30322-XL                   | d = 110     | D = 240      | T = 54.5   | Tapered roller bearing                |
| FAG   | 30322-XL-J30PC             | d = 110     | D = 240      | T = 54.5   | Tapered roller bearing                |
| FAG   | 31322-X                    | d = 110     | D = 240      | T = 63     | Tapered roller bearing                |
| FAG   | 31322-X-P5                 | d = 110     | D = 240      | T = 63     | Tapered roller bearing                |
| FAG   | 31322-X-XL                 | d = 110     | D = 240      | T = 63     | Tapered roller bearing                |
| FAG   | 31322-X-XL-J30PC           | d = 110     | D = 240      | T = 63     | Tapered roller bearing                |
| FAG   | 31322-X-XL-T51EF           | d = 110     | D = 240      | T = 63     | Tapered roller bearing                |
| FAG   | 32322-A                    | d = 110     | D = 240      | T = 84.5   | Tapered roller bearing                |
| KOYO  | 46T30322JR/93              | d = 110     | D = 240      | T = 118    | Tapered roller bearing                |
| KOYO  | 46T32322JR/142             | d = 110     | D = 240      | T = 181    | Tapered roller bearing                |
| FAG   | K67437-67675               | d = 111.125 | D = 171.45   | T = 34     | Tapered roller bearing                |
| FAG   | KH924045-H924010-XL-W215FD | d = 111.125 | D = 214.312  | T = 55.562 | Tapered roller bearing                |
| FAG   | K64450-64700               | d = 114.3   | D = 177.8    | T = 41.275 | Tapered roller bearing                |
| FAG   | K64450-64700-XL            | d = 114.3   | D = 177.8    | T = 41.275 | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation     | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|--------------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | K71450-71750-XL          | d = 114.3   | D = 190.5    | T = 47.625 | Tapered roller bearing                |
| FAG   | K938-932                 | d = 114.3   | D = 212.725  | T = 66.675 | Tapered roller bearing                |
| FAG   | K938-932-XL              | d = 114.3   | D = 212.725  | T = 66.675 | Tapered roller bearing                |
| FAG   | KHH224346-HH224310       | d = 114.3   | D = 212.725  | T = 66.675 | Tapered roller bearing                |
| FAG   | KHH224346-HH224310-W215D | d = 114.3   | D = 212.725  | T = 66.675 | Tapered roller bearing                |
| FAG   | K64452-A-64700           | d = 114.975 | D = 177.8    | T = 41.275 | Tapered roller bearing                |
| FAG   | K64452-A-64700-XL        | d = 114.975 | D = 177.8    | T = 41.275 | Tapered roller bearing                |
| FAG   | K71453-71750             | d = 115.087 | D = 190.5    | T = 47.625 | Tapered roller bearing                |
| FAG   | KHM124649-HM124618       | d = 119.957 | D = 195.262  | T = 53.975 | Tapered roller bearing                |
| FAG   | 32924                    | d = 120     | D = 165      | T = 29     | Tapered roller bearing                |
| FAG   | 32924-P5                 | d = 120     | D = 165      | T = 29     | Tapered roller bearing                |
| FAG   | 32924-XL-S1              | d = 120     | D = 165      | T = 29     | Tapered roller bearing                |
| FAG   | 32924-XL-W215FD          | d = 120     | D = 165      | T = 29     | Tapered roller bearing                |
| FAG   | KL724348-L724314         | d = 120     | D = 170      | T = 25.4   | Tapered roller bearing                |
| FAG   | T4CB120                  | d = 120     | D = 170      | T = 27     | Tapered roller bearing                |
| FAG   | T4CB120-XL               | d = 120     | D = 170      | T = 27     | Tapered roller bearing                |
| FAG   | T4CB120-XL-P6X-W215F     | d = 120     | D = 170      | T = 27     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | T4CB120-XL>A         | d = 120     | D = 170      | T = 27     | Tapered roller bearing                |
| FAG   | T4CB120-XL>B         | d = 120     | D = 170      | T = 27     | Tapered roller bearing                |
| FAG   | T2DC120              | d = 120     | D = 175      | T = 36     | Tapered roller bearing                |
| FAG   | 32024-X              | d = 120     | D = 180      | T = 38     | Tapered roller bearing                |
| FAG   | 32024-X-H            | d = 120     | D = 180      | T = 38     | Tapered roller bearing                |
| FAG   | 32024-X-XL           | d = 120     | D = 180      | T = 38     | Tapered roller bearing                |
| FAG   | 32024-X-XL-J30PC     | d = 120     | D = 180      | T = 38     | Tapered roller bearing                |
| FAG   | 32024-X-XL-P4        | d = 120     | D = 180      | T = 38     | Tapered roller bearing                |
| FAG   | 32024-X-XL-P5        | d = 120     | D = 180      | T = 38     | Tapered roller bearing                |
| FAG   | 32024-X-XL>A         | d = 120     | D = 180      | T = 38     | Tapered roller bearing                |
| FAG   | 32024-X-XL>B         | d = 120     | D = 180      | T = 38     | Tapered roller bearing                |
| FAG   | T2DD120              | d = 120     | D = 180      | T = 41     | Tapered roller bearing                |
| KOYO  | 46224                | d = 120     | D = 180      | T = 46     | Tapered roller bearing                |
| FAG   | 33024                | d = 120     | D = 180      | T = 48     | Tapered roller bearing                |
| FAG   | 33024-J30PC          | d = 120     | D = 180      | T = 48     | Tapered roller bearing                |
| FAG   | 33024-XL             | d = 120     | D = 180      | T = 48     | Tapered roller bearing                |
| KOYO  | 46224A               | d = 120     | D = 180      | T = 58     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | T2EE120              | d = 120     | D = 190      | T = 50     | Tapered roller bearing                |
| FAG   | T4FE120              | d = 120     | D = 200      | T = 58     | Tapered roller bearing                |
| FAG   | 33124                | d = 120     | D = 200      | T = 62     | Tapered roller bearing                |
| KOYO  | 46324                | d = 120     | D = 200      | T = 62     | Tapered roller bearing                |
| KOYO  | 46324A               | d = 120     | D = 200      | T = 78     | Tapered roller bearing                |
| KOYO  | 46324AS              | d = 120     | D = 200      | T = 100    | Tapered roller bearing                |
| FAG   | 30224-A              | d = 120     | D = 215      | T = 43.5   | Tapered roller bearing                |
| FAG   | 30224-H              | d = 120     | D = 215      | T = 43.5   | Tapered roller bearing                |
| FAG   | 30224-XL             | d = 120     | D = 215      | T = 43.5   | Tapered roller bearing                |
| FAG   | 30224-XL-P5          | d = 120     | D = 215      | T = 43.5   | Tapered roller bearing                |
| FAG   | 30224-XL-S1          | d = 120     | D = 215      | T = 43.5   | Tapered roller bearing                |
| FAG   | 32224-A              | d = 120     | D = 215      | T = 61.5   | Tapered roller bearing                |
| FAG   | 32224-H              | d = 120     | D = 215      | T = 61.5   | Tapered roller bearing                |
| FAG   | 32224-XL             | d = 120     | D = 215      | T = 61.5   | Tapered roller bearing                |
| FAG   | 32224-XL-J30PC       | d = 120     | D = 215      | T = 61.5   | Tapered roller bearing                |
| FAG   | 32224-XL-P5          | d = 120     | D = 215      | T = 61.5   | Tapered roller bearing                |
| FAG   | 32224-XL>A           | d = 120     | D = 215      | T = 61.5   | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| KOYO  | 46T30224JR/78        | d = 120     | D = 215      | T = 97     | Tapered roller bearing                |
| KOYO  | 46T32224JR/109       | d = 120     | D = 215      | T = 132    | Tapered roller bearing                |
| FAG   | 30324-A              | d = 120     | D = 260      | T = 59.5   | Tapered roller bearing                |
| FAG   | 30324-A>A            | d = 120     | D = 260      | T = 59.5   | Tapered roller bearing                |
| FAG   | 30324-XL             | d = 120     | D = 260      | T = 59.5   | Tapered roller bearing                |
| FAG   | 31324-X              | d = 120     | D = 260      | T = 68     | Tapered roller bearing                |
| FAG   | 31324-X-XL           | d = 120     | D = 260      | T = 68     | Tapered roller bearing                |
| FAG   | 31324-X-XL-J30PC     | d = 120     | D = 260      | T = 68     | Tapered roller bearing                |
| FAG   | 31324-X>A            | d = 120     | D = 260      | T = 68     | Tapered roller bearing                |
| FAG   | 32324                | d = 120     | D = 260      | T = 90.5   | Tapered roller bearing                |
| FAG   | 32324>A              | d = 120     | D = 260      | T = 90.5   | Tapered roller bearing                |
| KOYO  | 46T30324JR/101       | d = 120     | D = 260      | T = 128    | Tapered roller bearing                |
| KOYO  | 46T32324JR/145       | d = 120     | D = 260      | T = 188    | Tapered roller bearing                |
| FAG   | KL624549-L624510     | d = 120.65  | D = 160.338  | T = 21.433 | Tapered roller bearing                |
| FAG   | KL624549-L624510-H   | d = 120.65  | D = 160.338  | T = 21.433 | Tapered roller bearing                |
| FAG   | KL724349-L724310     | d = 120.65  | D = 166.688  | T = 25.4   | Tapered roller bearing                |
| FAG   | KL225842-L225810     | d = 120.65  | D = 169.862  | T = 25.4   | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | K48282-48220         | d = 120.65  | D = 182.563  | T = 39.688 | Tapered roller bearing                |
| FAG   | KHM624749-HM624710   | d = 120.65  | D = 190.5    | T = 46.038 | Tapered roller bearing                |
| FAG   | K67384-67322-XL      | d = 120.65  | D = 196.85   | T = 46.038 | Tapered roller bearing                |
| FAG   | K95475-95925         | d = 120.65  | D = 234.95   | T = 63.5   | Tapered roller bearing                |
| FAG   | KLL225749-LL225710   | d = 127     | D = 165.895  | T = 18.258 | Tapered roller bearing                |
| FAG   | KL225849-L225810     | d = 127     | D = 169.862  | T = 25.4   | Tapered roller bearing                |
| FAG   | K48290-48220         | d = 127     | D = 182.563  | T = 39.688 | Tapered roller bearing                |
| FAG   | K67388-67322         | d = 127     | D = 196.85   | T = 46.038 | Tapered roller bearing                |
| FAG   | K95500-95925         | d = 127     | D = 234.95   | T = 63.5   | Tapered roller bearing                |
| FAG   | K95500-95925-XL      | d = 127     | D = 234.95   | T = 63.5   | Tapered roller bearing                |
| FAG   | K95502-X-95925       | d = 127     | D = 234.95   | T = 63.5   | Tapered roller bearing                |
| FAG   | K799-792             | d = 128.588 | D = 206.375  | T = 47.626 | Tapered roller bearing                |
| FAG   | K95514-X-95905       | d = 129.967 | D = 230      | T = 63.5   | Tapered roller bearing                |
| FAG   | 32926                | d = 130     | D = 180      | T = 32     | Tapered roller bearing                |
| FAG   | 32926-P5             | d = 130     | D = 180      | T = 32     | Tapered roller bearing                |
| FAG   | 32926-XL             | d = 130     | D = 180      | T = 32     | Tapered roller bearing                |
| FAG   | T4CB130              | d = 130     | D = 185      | T = 29     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | T4CB130-P5           | d = 130     | D = 185      | T = 29     | Tapered roller bearing                |
| FAG   | T4CB130>A            | d = 130     | D = 185      | T = 29     | Tapered roller bearing                |
| FAG   | T2DC130              | d = 130     | D = 185      | T = 36     | Tapered roller bearing                |
| FAG   | T2DD130              | d = 130     | D = 190      | T = 41     | Tapered roller bearing                |
| FAG   | 32026-X              | d = 130     | D = 200      | T = 45     | Tapered roller bearing                |
| FAG   | 32026-X-H            | d = 130     | D = 200      | T = 45     | Tapered roller bearing                |
| FAG   | 32026-X-XL           | d = 130     | D = 200      | T = 45     | Tapered roller bearing                |
| FAG   | 32026-X-XL-J30PC     | d = 130     | D = 200      | T = 45     | Tapered roller bearing                |
| FAG   | 32026-X-XL-P5        | d = 130     | D = 200      | T = 45     | Tapered roller bearing                |
| FAG   | 32026-X-XL-S1        | d = 130     | D = 200      | T = 45     | Tapered roller bearing                |
| FAG   | 32026-X-XL>A         | d = 130     | D = 200      | T = 45     | Tapered roller bearing                |
| FAG   | 32026-X-XL>B         | d = 130     | D = 200      | T = 45     | Tapered roller bearing                |
| KOYO  | 46226                | d = 130     | D = 200      | T = 52     | Tapered roller bearing                |
| FAG   | 33026                | d = 130     | D = 200      | T = 55     | Tapered roller bearing                |
| KOYO  | 46226A               | d = 130     | D = 200      | T = 65     | Tapered roller bearing                |
| FAG   | T3EE130              | d = 130     | D = 210      | T = 58     | Tapered roller bearing                |
| KOYO  | 46326                | d = 130     | D = 210      | T = 64     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| KOYO  | 46326A               | d = 130     | D = 210      | T = 80     | Tapered roller bearing                |
| FAG   | 30226-A              | d = 130     | D = 230      | T = 43.75  | Tapered roller bearing                |
| FAG   | 30226-XL             | d = 130     | D = 230      | T = 43.75  | Tapered roller bearing                |
| FAG   | 32226-A              | d = 130     | D = 230      | T = 67.75  | Tapered roller bearing                |
| FAG   | 32226-H              | d = 130     | D = 230      | T = 67.75  | Tapered roller bearing                |
| FAG   | 32226-XL             | d = 130     | D = 230      | T = 67.75  | Tapered roller bearing                |
| FAG   | 32226-XL-J30PC       | d = 130     | D = 230      | T = 67.75  | Tapered roller bearing                |
| KOYO  | 46T30226JR/78.5      | d = 130     | D = 230      | T = 98     | Tapered roller bearing                |
| KOYO  | 46T32226JR/117.5     | d = 130     | D = 230      | T = 145    | Tapered roller bearing                |
| FAG   | 30326                | d = 130     | D = 280      | T = 63.75  | Tapered roller bearing                |
| FAG   | 30326-J30PC          | d = 130     | D = 280      | T = 63.75  | Tapered roller bearing                |
| FAG   | 30326-XL             | d = 130     | D = 280      | T = 63.75  | Tapered roller bearing                |
| FAG   | 30326-XL-J30PC       | d = 130     | D = 280      | T = 63.75  | Tapered roller bearing                |
| FAG   | 31326-X              | d = 130     | D = 280      | T = 72     | Tapered roller bearing                |
| FAG   | 31326-X-J30PC        | d = 130     | D = 280      | T = 72     | Tapered roller bearing                |
| FAG   | 31326-X-XL           | d = 130     | D = 280      | T = 72     | Tapered roller bearing                |
| FAG   | 31326-X-XL-J30PC     | d = 130     | D = 280      | T = 72     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation     | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|--------------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 32326>A                  | d = 130     | D = 280      | T = 98.75  | Tapered roller bearing                |
| KOYO  | 46T30326JR/107.5         | d = 130     | D = 280      | T = 137    | Tapered roller bearing                |
| FAG   | KLL327049-LL327010       | d = 133.35  | D = 173.038  | T = 19.05  | Tapered roller bearing                |
| FAG   | K48385-48320             | d = 133.35  | D = 190.5    | T = 39.688 | Tapered roller bearing                |
| FAG   | K67391-67322             | d = 133.35  | D = 196.85   | T = 46.038 | Tapered roller bearing                |
| FAG   | K67391-67322-XL          | d = 133.35  | D = 196.85   | T = 46.038 | Tapered roller bearing                |
| FAG   | K74525-74850             | d = 133.35  | D = 215.9    | T = 47.625 | Tapered roller bearing                |
| FAG   | K95525-95925             | d = 133.35  | D = 234.95   | T = 63.5   | Tapered roller bearing                |
| FAG   | K95525-95925-XL          | d = 133.35  | D = 234.95   | T = 63.5   | Tapered roller bearing                |
| FAG   | K95528-95925             | d = 133.35  | D = 234.95   | T = 63.5   | Tapered roller bearing                |
| FAG   | K95528-95925-XL          | d = 133.35  | D = 234.95   | T = 63.5   | Tapered roller bearing                |
| FAG   | K48393-48320             | d = 136.525 | D = 190.5    | T = 39.688 | Tapered roller bearing                |
| FAG   | KLM229139-LM229110       | d = 136.525 | D = 194.975  | T = 33     | Tapered roller bearing                |
| FAG   | K74537-74850             | d = 136.525 | D = 215.9    | T = 47.625 | Tapered roller bearing                |
| FAG   | AK896-892-XL             | d = 136.525 | D = 228.6    | T = 57.15  | Tapered roller bearing                |
| FAG   | KLL428349-LL428310-XL    | d = 139.7   | D = 180.975  | T = 21.433 | Tapered roller bearing                |
| FAG   | KLL428349-LL428310-XL-S1 | d = 139.7   | D = 180.975  | T = 21.433 | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation  | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|-----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | KLM328448-LM328410    | d = 139.7   | D = 187.325  | T = 28.575 | Tapered roller bearing                |
| FAG   | K74550-74845          | d = 139.7   | D = 214.975  | T = 47.625 | Tapered roller bearing                |
| FAG   | K74550-74850          | d = 139.7   | D = 215.9    | T = 47.625 | Tapered roller bearing                |
| FAG   | K74550-A-74850        | d = 139.7   | D = 215.9    | T = 47.625 | Tapered roller bearing                |
| FAG   | AK898-892-XL          | d = 139.7   | D = 228.6    | T = 57.15  | Tapered roller bearing                |
| FAG   | AK898-A-892-XL        | d = 139.7   | D = 228.6    | T = 57.15  | Tapered roller bearing                |
| FAG   | AK899-892-XL          | d = 139.7   | D = 228.6    | T = 57.15  | Tapered roller bearing                |
| FAG   | K82550-82950          | d = 139.7   | D = 241.3    | T = 57.15  | Tapered roller bearing                |
| FAG   | K99550-99100          | d = 139.7   | D = 254      | T = 66.675 | Tapered roller bearing                |
| FAG   | K99550-99100-XL       | d = 139.7   | D = 254      | T = 66.675 | Tapered roller bearing                |
| FAG   | KHH231649-HH231610    | d = 139.7   | D = 288.925  | T = 82.55  | Tapered roller bearing                |
| FAG   | KHH231649-HH231610-XL | d = 139.7   | D = 288.925  | T = 82.55  | Tapered roller bearing                |
| FAG   | KHH231649-HH231615    | d = 139.7   | D = 295.275  | T = 82.55  | Tapered roller bearing                |
| FAG   | KHH234031-HH234010    | d = 139.7   | D = 307.975  | T = 88.9   | Tapered roller bearing                |
| FAG   | 32928                 | d = 140     | D = 190      | T = 32     | Tapered roller bearing                |
| FAG   | 32928-P5              | d = 140     | D = 190      | T = 32     | Tapered roller bearing                |
| FAG   | 32928-XL              | d = 140     | D = 190      | T = 32     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 32928>A              | d = 140     | D = 190      | T = 32     | Tapered roller bearing                |
| FAG   | T4CB140              | d = 140     | D = 195      | T = 29     | Tapered roller bearing                |
| FAG   | T2DC140              | d = 140     | D = 200      | T = 39     | Tapered roller bearing                |
| FAG   | T2DD140              | d = 140     | D = 205      | T = 44     | Tapered roller bearing                |
| FAG   | 32028-X-H            | d = 140     | D = 210      | T = 45     | Tapered roller bearing                |
| FAG   | 32028-X-XL           | d = 140     | D = 210      | T = 45     | Tapered roller bearing                |
| FAG   | 32028-X-XL-P5        | d = 140     | D = 210      | T = 45     | Tapered roller bearing                |
| FAG   | 32028-X-XL-S1        | d = 140     | D = 210      | T = 45     | Tapered roller bearing                |
| FAG   | 32028-X-XL>A         | d = 140     | D = 210      | T = 45     | Tapered roller bearing                |
| KOYO  | 46228                | d = 140     | D = 210      | T = 53     | Tapered roller bearing                |
| FAG   | 33028                | d = 140     | D = 210      | T = 56     | Tapered roller bearing                |
| FAG   | 33028-H              | d = 140     | D = 210      | T = 56     | Tapered roller bearing                |
| KOYO  | 46228A               | d = 140     | D = 210      | T = 66     | Tapered roller bearing                |
| FAG   | T2ED140              | d = 140     | D = 215      | T = 53     | Tapered roller bearing                |
| FAG   | T4EE140              | d = 140     | D = 220      | T = 58     | Tapered roller bearing                |
| KOYO  | 46328                | d = 140     | D = 225      | T = 68     | Tapered roller bearing                |
| KOYO  | 46328A               | d = 140     | D = 225      | T = 85     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 30228-A              | d = 140     | D = 250      | T = 45.75  | Tapered roller bearing                |
| FAG   | 30228-XL             | d = 140     | D = 250      | T = 45.75  | Tapered roller bearing                |
| FAG   | 30228-XL-P5          | d = 140     | D = 250      | T = 45.75  | Tapered roller bearing                |
| FAG   | 30228-XL>A           | d = 140     | D = 250      | T = 45.75  | Tapered roller bearing                |
| FAG   | 32228-A              | d = 140     | D = 250      | T = 71.75  | Tapered roller bearing                |
| FAG   | 32228-A-P5           | d = 140     | D = 250      | T = 71.75  | Tapered roller bearing                |
| FAG   | 32228-XL             | d = 140     | D = 250      | T = 71.75  | Tapered roller bearing                |
| FAG   | 32228-XL-P5          | d = 140     | D = 250      | T = 71.75  | Tapered roller bearing                |
| KOYO  | 46T30228JR/82.5      | d = 140     | D = 250      | T = 102    | Tapered roller bearing                |
| KOYO  | 46T32228JR/125.5     | d = 140     | D = 250      | T = 153    | Tapered roller bearing                |
| FAG   | 30328-XL             | d = 140     | D = 300      | T = 67.75  | Tapered roller bearing                |
| FAG   | 30328-XL-J30PC       | d = 140     | D = 300      | T = 67.75  | Tapered roller bearing                |
| FAG   | 31328-X              | d = 140     | D = 300      | T = 77     | Tapered roller bearing                |
| FAG   | 31328-X-XL           | d = 140     | D = 300      | T = 77     | Tapered roller bearing                |
| FAG   | 31328-X-XL-J30PC     | d = 140     | D = 300      | T = 77     | Tapered roller bearing                |
| FAG   | 31328-X-XL-P5        | d = 140     | D = 300      | T = 77     | Tapered roller bearing                |
| FAG   | 32328-A              | d = 140     | D = 300      | T = 107.75 | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 32328-XL             | d = 140     | D = 300      | T = 107.75 | Tapered roller bearing                |
| KOYO  | 46T30328JR/115.5     | d = 140     | D = 300      | T = 145    | Tapered roller bearing                |
| FAG   | K36686-36620         | d = 142.875 | D = 193.675  | T = 28.575 | Tapered roller bearing                |
| FAG   | KLM229146-LM229110   | d = 142.875 | D = 194.975  | T = 33     | Tapered roller bearing                |
| FAG   | K48684-48620         | d = 142.875 | D = 200.025  | T = 41.275 | Tapered roller bearing                |
| FAG   | K48684-48620-Q3      | d = 142.875 | D = 200.025  | T = 41.275 | Tapered roller bearing                |
| FAG   | K48685-48620         | d = 142.875 | D = 200.025  | T = 41.275 | Tapered roller bearing                |
| FAG   | KLL529749-LL529710   | d = 146.05  | D = 188.12   | T = 22.225 | Tapered roller bearing                |
| FAG   | AK36690-36620-XL     | d = 146.05  | D = 193.675  | T = 28.575 | Tapered roller bearing                |
| FAG   | K36691-36620         | d = 146.05  | D = 193.675  | T = 28.575 | Tapered roller bearing                |
| FAG   | K82576-82931         | d = 146.05  | D = 236.538  | T = 57.15  | Tapered roller bearing                |
| FAG   | K99575-99100         | d = 146.05  | D = 254      | T = 66.675 | Tapered roller bearing                |
| FAG   | K107057-107105       | d = 146.05  | D = 268.288  | T = 74.612 | Tapered roller bearing                |
| FAG   | T4DB150              | d = 150     | D = 210      | T = 32     | Tapered roller bearing                |
| FAG   | 32930                | d = 150     | D = 210      | T = 38     | Tapered roller bearing                |
| FAG   | 32930-P5             | d = 150     | D = 210      | T = 38     | Tapered roller bearing                |
| FAG   | 32930-XL             | d = 150     | D = 210      | T = 38     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | T2DD150              | d = 150     | D = 215      | T = 44     | Tapered roller bearing                |
| FAG   | 32030-X              | d = 150     | D = 225      | T = 48     | Tapered roller bearing                |
| FAG   | 32030-X-H            | d = 150     | D = 225      | T = 48     | Tapered roller bearing                |
| FAG   | 32030-X-XL           | d = 150     | D = 225      | T = 48     | Tapered roller bearing                |
| FAG   | 32030-X-XL-J30PC     | d = 150     | D = 225      | T = 48     | Tapered roller bearing                |
| FAG   | 32030-X-XL-P5        | d = 150     | D = 225      | T = 48     | Tapered roller bearing                |
| FAG   | 32030-X-XL>A         | d = 150     | D = 225      | T = 48     | Tapered roller bearing                |
| FAG   | 32030-X-XL>B         | d = 150     | D = 225      | T = 48     | Tapered roller bearing                |
| FAG   | T2ED150              | d = 150     | D = 225      | T = 53     | Tapered roller bearing                |
| KOYO  | 46230                | d = 150     | D = 225      | T = 56     | Tapered roller bearing                |
| FAG   | 33030                | d = 150     | D = 225      | T = 59     | Tapered roller bearing                |
| FAG   | 33030-XL             | d = 150     | D = 225      | T = 59     | Tapered roller bearing                |
| FAG   | 33030-XL-J30PC       | d = 150     | D = 225      | T = 59     | Tapered roller bearing                |
| KOYO  | 46230A               | d = 150     | D = 225      | T = 70     | Tapered roller bearing                |
| FAG   | T3EE150              | d = 150     | D = 235      | T = 61     | Tapered roller bearing                |
| KOYO  | 46330                | d = 150     | D = 250      | T = 80     | Tapered roller bearing                |
| KOYO  | 46330A               | d = 150     | D = 250      | T = 100    | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 30230-A-P5           | d = 150     | D = 270      | T = 49     | Tapered roller bearing                |
| FAG   | 30230-A>A            | d = 150     | D = 270      | T = 49     | Tapered roller bearing                |
| FAG   | 30230-XL             | d = 150     | D = 270      | T = 49     | Tapered roller bearing                |
| FAG   | 30230-XL-J30PC       | d = 150     | D = 270      | T = 49     | Tapered roller bearing                |
| FAG   | 30230-XL-P5          | d = 150     | D = 270      | T = 49     | Tapered roller bearing                |
| FAG   | 30230-XL>A           | d = 150     | D = 270      | T = 49     | Tapered roller bearing                |
| FAG   | 32230-A-J30PC        | d = 150     | D = 270      | T = 77     | Tapered roller bearing                |
| FAG   | 32230-XL             | d = 150     | D = 270      | T = 77     | Tapered roller bearing                |
| FAG   | 32230-XL-J30PC       | d = 150     | D = 270      | T = 77     | Tapered roller bearing                |
| FAG   | 32230-XL-P5          | d = 150     | D = 270      | T = 77     | Tapered roller bearing                |
| FAG   | 32230-XL>A           | d = 150     | D = 270      | T = 77     | Tapered roller bearing                |
| KOYO  | 46T30230JR/87        | d = 150     | D = 270      | T = 109    | Tapered roller bearing                |
| KOYO  | 46T32230JR/130       | d = 150     | D = 270      | T = 164    | Tapered roller bearing                |
| FAG   | 30330-XL             | d = 150     | D = 320      | T = 72     | Tapered roller bearing                |
| FAG   | 30330-XL-J30PC       | d = 150     | D = 320      | T = 72     | Tapered roller bearing                |
| FAG   | 31330-X-XL           | d = 150     | D = 320      | T = 82     | Tapered roller bearing                |
| FAG   | 31330-X-XL-J30PC     | d = 150     | D = 320      | T = 82     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 31330-X-XL-P5        | d = 150     | D = 320      | T = 82     | Tapered roller bearing                |
| FAG   | 32330-A              | d = 150     | D = 320      | T = 114    | Tapered roller bearing                |
| FAG   | 32330-A>A            | d = 150     | D = 320      | T = 114    | Tapered roller bearing                |
| KOYO  | 46T30330JR/120       | d = 150     | D = 320      | T = 154    | Tapered roller bearing                |
| FAG   | KL630349-L630310     | d = 152.4   | D = 192.088  | T = 25     | Tapered roller bearing                |
| FAG   | K99600-99100         | d = 152.4   | D = 254      | T = 66.675 | Tapered roller bearing                |
| FAG   | K99600-99100-XL      | d = 152.4   | D = 254      | T = 66.675 | Tapered roller bearing                |
| FAG   | K450601-451212       | d = 152.4   | D = 307.975  | T = 88.9   | Tapered roller bearing                |
| FAG   | KHH234048-HH234010   | d = 152.4   | D = 307.975  | T = 88.9   | Tapered roller bearing                |
| FAG   | KHH234048-HH234018   | d = 152.4   | D = 317.5    | T = 88.9   | Tapered roller bearing                |
| FAG   | KH936340-H936316-XL  | d = 155.575 | D = 342.9    | T = 85.725 | Tapered roller bearing                |
| FAG   | KL432348-L432310     | d = 158.75  | D = 205.583  | T = 23.812 | Tapered roller bearing                |
| FAG   | K46780-46720         | d = 158.75  | D = 225.425  | T = 41.275 | Tapered roller bearing                |
| FAG   | T4DB160              | d = 160     | D = 220      | T = 32     | Tapered roller bearing                |
| FAG   | T4DB160-XL-W215FD    | d = 160     | D = 220      | T = 32     | Tapered roller bearing                |
| FAG   | 32932                | d = 160     | D = 220      | T = 38     | Tapered roller bearing                |
| FAG   | 32932-P5             | d = 160     | D = 220      | T = 38     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 32932-W215FD         | d = 160     | D = 220      | T = 38     | Tapered roller bearing                |
| FAG   | 32932-XL-W215FD      | d = 160     | D = 220      | T = 38     | Tapered roller bearing                |
| FAG   | T2DD160              | d = 160     | D = 225      | T = 44     | Tapered roller bearing                |
| FAG   | T2ED160              | d = 160     | D = 235      | T = 53     | Tapered roller bearing                |
| FAG   | 32032-X-XL           | d = 160     | D = 240      | T = 51     | Tapered roller bearing                |
| FAG   | 32032-X-XL-P5        | d = 160     | D = 240      | T = 51     | Tapered roller bearing                |
| FAG   | 32032-X-XL>A         | d = 160     | D = 240      | T = 51     | Tapered roller bearing                |
| KOYO  | 46232                | d = 160     | D = 240      | T = 60     | Tapered roller bearing                |
| KOYO  | 46232A               | d = 160     | D = 240      | T = 75     | Tapered roller bearing                |
| FAG   | T4EE160              | d = 160     | D = 245      | T = 61     | Tapered roller bearing                |
| FAG   | KHM133448-HM133416   | d = 160     | D = 252.413  | T = 63.5   | Tapered roller bearing                |
| KOYO  | 46332                | d = 160     | D = 270      | T = 86     | Tapered roller bearing                |
| KOYO  | 46332A               | d = 160     | D = 270      | T = 108    | Tapered roller bearing                |
| FAG   | 30232-P5             | d = 160     | D = 290      | T = 52     | Tapered roller bearing                |
| FAG   | 30232-XL             | d = 160     | D = 290      | T = 52     | Tapered roller bearing                |
| FAG   | 30232-XL-J30PC       | d = 160     | D = 290      | T = 52     | Tapered roller bearing                |
| FAG   | 30232-XL-W215FD      | d = 160     | D = 290      | T = 52     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 30232-XL>A           | d = 160     | D = 290      | T = 52     | Tapered roller bearing                |
| FAG   | 32232-A-P5           | d = 160     | D = 290      | T = 84     | Tapered roller bearing                |
| FAG   | 32232-A>A            | d = 160     | D = 290      | T = 84     | Tapered roller bearing                |
| FAG   | 32232-XL             | d = 160     | D = 290      | T = 84     | Tapered roller bearing                |
| FAG   | 32232-XL-J30PC       | d = 160     | D = 290      | T = 84     | Tapered roller bearing                |
| FAG   | 32232-XL>A           | d = 160     | D = 290      | T = 84     | Tapered roller bearing                |
| KOYO  | 46T30232JR/91        | d = 160     | D = 290      | T = 115    | Tapered roller bearing                |
| KOYO  | 46T32232JR/144       | d = 160     | D = 290      | T = 178    | Tapered roller bearing                |
| FAG   | 30332-A              | d = 160     | D = 340      | T = 75     | Tapered roller bearing                |
| FAG   | 32332                | d = 160     | D = 340      | T = 121    | Tapered roller bearing                |
| FAG   | 32332-XL             | d = 160     | D = 340      | T = 121    | Tapered roller bearing                |
| FAG   | KL433749-L433710     | d = 165.1   | D = 215.9    | T = 26.195 | Tapered roller bearing                |
| FAG   | K46790-46720         | d = 165.1   | D = 225.425  | T = 41.275 | Tapered roller bearing                |
| FAG   | K67780-67720         | d = 165.1   | D = 247.65   | T = 47.625 | Tapered roller bearing                |
| FAG   | KH936349-H936310-XL  | d = 168.275 | D = 330.2    | T = 85.725 | Tapered roller bearing                |
| FAG   | T4DB170              | d = 170     | D = 230      | T = 32     | Tapered roller bearing                |
| FAG   | 32934                | d = 170     | D = 230      | T = 38     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 32934-P5             | d = 170     | D = 230      | T = 38     | Tapered roller bearing                |
| FAG   | 32934-W215FD         | d = 170     | D = 230      | T = 38     | Tapered roller bearing                |
| FAG   | 32934-XL             | d = 170     | D = 230      | T = 38     | Tapered roller bearing                |
| FAG   | 32934-XL-W215FD      | d = 170     | D = 230      | T = 38     | Tapered roller bearing                |
| FAG   | T2DD170              | d = 170     | D = 235      | T = 44     | Tapered roller bearing                |
| FAG   | T2ED170              | d = 170     | D = 245      | T = 53     | Tapered roller bearing                |
| FAG   | T3EE170              | d = 170     | D = 255      | T = 61     | Tapered roller bearing                |
| FAG   | 32034-X              | d = 170     | D = 260      | T = 57     | Tapered roller bearing                |
| FAG   | 32034-X-XL           | d = 170     | D = 260      | T = 57     | Tapered roller bearing                |
| FAG   | 32034-X-XL-P5        | d = 170     | D = 260      | T = 57     | Tapered roller bearing                |
| FAG   | 32034-X-XL>A         | d = 170     | D = 260      | T = 57     | Tapered roller bearing                |
| KOYO  | 46234                | d = 170     | D = 260      | T = 67     | Tapered roller bearing                |
| KOYO  | 46234A               | d = 170     | D = 260      | T = 84     | Tapered roller bearing                |
| KOYO  | 46334                | d = 170     | D = 280      | T = 88     | Tapered roller bearing                |
| KOYO  | 46334A               | d = 170     | D = 280      | T = 110    | Tapered roller bearing                |
| FAG   | 30234-A>A            | d = 170     | D = 310      | T = 57     | Tapered roller bearing                |
| FAG   | 30234-XL             | d = 170     | D = 310      | T = 57     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 30234-XL-J30PC       | d = 170     | D = 310      | T = 57     | Tapered roller bearing                |
| FAG   | 32234-A>A            | d = 170     | D = 310      | T = 91     | Tapered roller bearing                |
| FAG   | 32234-XL             | d = 170     | D = 310      | T = 91     | Tapered roller bearing                |
| FAG   | 32234-XL-J30PC       | d = 170     | D = 310      | T = 91     | Tapered roller bearing                |
| KOYO  | 46T30234JR/97        | d = 170     | D = 310      | T = 125    | Tapered roller bearing                |
| KOYO  | 46T32234JR/152       | d = 170     | D = 310      | T = 192    | Tapered roller bearing                |
| FAG   | 30334-A              | d = 170     | D = 360      | T = 80     | Tapered roller bearing                |
| FAG   | 32334                | d = 170     | D = 360      | T = 127    | Tapered roller bearing                |
| FAG   | 32334-XL             | d = 170     | D = 360      | T = 127    | Tapered roller bearing                |
| FAG   | KL435049-L435010     | d = 171.45  | D = 222.25   | T = 25.4   | Tapered roller bearing                |
| FAG   | KL435049-L435010-XL  | d = 171.45  | D = 222.25   | T = 25.4   | Tapered roller bearing                |
| FAG   | K67786-67720         | d = 174.625 | D = 247.65   | T = 47.625 | Tapered roller bearing                |
| FAG   | KM236845-M236810     | d = 174.625 | D = 260.35   | T = 53.975 | Tapered roller bearing                |
| FAG   | KLL735449-LL735410   | d = 177.8   | D = 215.9    | T = 20.638 | Tapered roller bearing                |
| FAG   | K36990-36920         | d = 177.8   | D = 227.012  | T = 30.162 | Tapered roller bearing                |
| FAG   | K36990-36920-J33BB   | d = 177.8   | D = 227.012  | T = 30.162 | Tapered roller bearing                |
| FAG   | K36990-36920-XL      | d = 177.8   | D = 227.012  | T = 30.162 | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | K67790-67720-XL      | d = 177.8   | D = 247.65   | T = 47.625 | Tapered roller bearing                |
| FAG   | KM236849-M236810     | d = 177.8   | D = 260.35   | T = 53.975 | Tapered roller bearing                |
| FAG   | K280702-281200       | d = 177.8   | D = 304.8    | T = 66.675 | Tapered roller bearing                |
| FAG   | K470073-470133       | d = 177.8   | D = 339.725  | T = 90.488 | Tapered roller bearing                |
| FAG   | T4DB180              | d = 180     | D = 240      | T = 32     | Tapered roller bearing                |
| FAG   | T2DC180              | d = 180     | D = 240      | T = 39     | Tapered roller bearing                |
| FAG   | T2DD180              | d = 180     | D = 245      | T = 44     | Tapered roller bearing                |
| FAG   | 32936                | d = 180     | D = 250      | T = 45     | Tapered roller bearing                |
| FAG   | 32936-P5             | d = 180     | D = 250      | T = 45     | Tapered roller bearing                |
| FAG   | T2ED180              | d = 180     | D = 255      | T = 53     | Tapered roller bearing                |
| FAG   | T4EE180              | d = 180     | D = 265      | T = 61     | Tapered roller bearing                |
| FAG   | 32036-X-XL           | d = 180     | D = 280      | T = 64     | Tapered roller bearing                |
| FAG   | 32036-X-XL-J20AA     | d = 180     | D = 280      | T = 64     | Tapered roller bearing                |
| FAG   | 32036-X-XL-J30PC     | d = 180     | D = 280      | T = 64     | Tapered roller bearing                |
| FAG   | 32036-X-XL-P5        | d = 180     | D = 280      | T = 64     | Tapered roller bearing                |
| FAG   | 32036-X-XL-P5>A      | d = 180     | D = 280      | T = 64     | Tapered roller bearing                |
| FAG   | 32036-X-XL>A         | d = 180     | D = 280      | T = 64     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| KOYO  | 46236                | d = 180     | D = 280      | T = 74     | Tapered roller bearing                |
| KOYO  | 46236A               | d = 180     | D = 280      | T = 93     | Tapered roller bearing                |
| KOYO  | 46336                | d = 180     | D = 300      | T = 96     | Tapered roller bearing                |
| KOYO  | 46336A               | d = 180     | D = 300      | T = 120    | Tapered roller bearing                |
| FAG   | 30236-A>A            | d = 180     | D = 320      | T = 57     | Tapered roller bearing                |
| FAG   | 30236-XL             | d = 180     | D = 320      | T = 57     | Tapered roller bearing                |
| FAG   | 32236-A-P5           | d = 180     | D = 320      | T = 91     | Tapered roller bearing                |
| FAG   | 32236-A>A            | d = 180     | D = 320      | T = 91     | Tapered roller bearing                |
| FAG   | 32236-XL             | d = 180     | D = 320      | T = 91     | Tapered roller bearing                |
| FAG   | 32236-XL-J30PC       | d = 180     | D = 320      | T = 91     | Tapered roller bearing                |
| FAG   | 32236-XL>A           | d = 180     | D = 320      | T = 91     | Tapered roller bearing                |
| KOYO  | 46T30236JR/99        | d = 180     | D = 320      | T = 127    | Tapered roller bearing                |
| KOYO  | 46T32236JR/152       | d = 180     | D = 320      | T = 192    | Tapered roller bearing                |
| FAG   | 30336                | d = 180     | D = 380      | T = 83     | Tapered roller bearing                |
| FAG   | 32336                | d = 180     | D = 380      | T = 134    | Tapered roller bearing                |
| FAG   | KLM236749-LM236710-A | d = 184.15  | D = 235.229  | T = 34     | Tapered roller bearing                |
| FAG   | K67883-67820-XL      | d = 184.15  | D = 266.7    | T = 47.625 | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | K67884-67820         | d = 187.325 | D = 266.7    | T = 47.625 | Tapered roller bearing                |
| FAG   | K87737-87111         | d = 187.325 | D = 282.575  | T = 50.8   | Tapered roller bearing                |
| FAG   | KM239441-M239410     | d = 187.63  | D = 279.4    | T = 52.388 | Tapered roller bearing                |
| FAG   | KM239447-M239410     | d = 189.738 | D = 279.4    | T = 52.388 | Tapered roller bearing                |
| FAG   | T2DC190              | d = 190     | D = 255      | T = 41     | Tapered roller bearing                |
| FAG   | T4DB190              | d = 190     | D = 260      | T = 37     | Tapered roller bearing                |
| FAG   | 32938                | d = 190     | D = 260      | T = 45     | Tapered roller bearing                |
| FAG   | 32938-XL             | d = 190     | D = 260      | T = 45     | Tapered roller bearing                |
| FAG   | T2DD190              | d = 190     | D = 260      | T = 47     | Tapered roller bearing                |
| FAG   | T2ED190              | d = 190     | D = 270      | T = 56     | Tapered roller bearing                |
| FAG   | T3EE190              | d = 190     | D = 280      | T = 64     | Tapered roller bearing                |
| FAG   | 32038-X-XL           | d = 190     | D = 290      | T = 64     | Tapered roller bearing                |
| FAG   | 32038-X-XL-P5        | d = 190     | D = 290      | T = 64     | Tapered roller bearing                |
| FAG   | 32038-X-XL>A         | d = 190     | D = 290      | T = 64     | Tapered roller bearing                |
| KOYO  | 46238                | d = 190     | D = 290      | T = 75     | Tapered roller bearing                |
| KOYO  | 46238A               | d = 190     | D = 290      | T = 94     | Tapered roller bearing                |
| KOYO  | 46338                | d = 190     | D = 320      | T = 104    | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| KOYO  | 46338A               | d = 190     | D = 320      | T = 130    | Tapered roller bearing                |
| FAG   | 30238                | d = 190     | D = 340      | T = 60     | Tapered roller bearing                |
| FAG   | 30238-XL             | d = 190     | D = 340      | T = 60     | Tapered roller bearing                |
| FAG   | 30238-XL-J30PC       | d = 190     | D = 340      | T = 60     | Tapered roller bearing                |
| FAG   | 32238-A              | d = 190     | D = 340      | T = 97     | Tapered roller bearing                |
| FAG   | 32238-XL             | d = 190     | D = 340      | T = 97     | Tapered roller bearing                |
| FAG   | 32238-XL-J30PC       | d = 190     | D = 340      | T = 97     | Tapered roller bearing                |
| KOYO  | 46T30238JR/105       | d = 190     | D = 340      | T = 133    | Tapered roller bearing                |
| KOYO  | 46T32238JR/160       | d = 190     | D = 340      | T = 204    | Tapered roller bearing                |
| FAG   | 30338                | d = 190     | D = 400      | T = 86     | Tapered roller bearing                |
| FAG   | 32338                | d = 190     | D = 400      | T = 140    | Tapered roller bearing                |
| FAG   | KM239449-M239410     | d = 190.475 | D = 279.4    | T = 52.388 | Tapered roller bearing                |
| FAG   | K67885-67820-XL      | d = 190.5   | D = 266.7    | T = 47.625 | Tapered roller bearing                |
| FAG   | K87750-87111         | d = 190.5   | D = 282.575  | T = 50.8   | Tapered roller bearing                |
| FAG   | K470075-470128       | d = 190.5   | D = 327.025  | T = 90.488 | Tapered roller bearing                |
| FAG   | KLL639249-LL639210   | d = 196.85  | D = 241.3    | T = 23.813 | Tapered roller bearing                |
| FAG   | KL540049-L540010     | d = 196.85  | D = 254      | T = 28.575 | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | KL540049-L540010-XL  | d = 196.85  | D = 254      | T = 28.575 | Tapered roller bearing                |
| FAG   | KLM739749-LM739710   | d = 196.85  | D = 257.175  | T = 39.688 | Tapered roller bearing                |
| FAG   | K67981-67919         | d = 198.298 | D = 279.4    | T = 46.038 | Tapered roller bearing                |
| FAG   | K67981-67919-XL      | d = 198.298 | D = 279.4    | T = 46.038 | Tapered roller bearing                |
| FAG   | K67981-67920         | d = 198.298 | D = 282.575  | T = 46.038 | Tapered roller bearing                |
| FAG   | K67982-67920-XL      | d = 199.949 | D = 282.575  | T = 46.038 | Tapered roller bearing                |
| FAG   | T2DC200              | d = 200     | D = 265      | T = 41     | Tapered roller bearing                |
| FAG   | T4DB200              | d = 200     | D = 270      | T = 37     | Tapered roller bearing                |
| FAG   | T2DD200              | d = 200     | D = 270      | T = 47     | Tapered roller bearing                |
| FAG   | 32940-A              | d = 200     | D = 280      | T = 51     | Tapered roller bearing                |
| FAG   | 32940-A-J30PC        | d = 200     | D = 280      | T = 51     | Tapered roller bearing                |
| FAG   | 32940-A>A            | d = 200     | D = 280      | T = 51     | Tapered roller bearing                |
| FAG   | 32940-XL             | d = 200     | D = 280      | T = 51     | Tapered roller bearing                |
| FAG   | T2ED200              | d = 200     | D = 280      | T = 56     | Tapered roller bearing                |
| FAG   | T4EE200              | d = 200     | D = 290      | T = 64     | Tapered roller bearing                |
| FAG   | 32040-X              | d = 200     | D = 310      | T = 70     | Tapered roller bearing                |
| FAG   | 32040-X-XL           | d = 200     | D = 310      | T = 70     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 32040-X-XL-P5        | d = 200     | D = 310      | T = 70     | Tapered roller bearing                |
| FAG   | 32040-X-XL>A         | d = 200     | D = 310      | T = 70     | Tapered roller bearing                |
| FAG   | 32040-X>A            | d = 200     | D = 310      | T = 70     | Tapered roller bearing                |
| KOYO  | 46240                | d = 200     | D = 310      | T = 82     | Tapered roller bearing                |
| KOYO  | 46240A               | d = 200     | D = 310      | T = 103    | Tapered roller bearing                |
| KOYO  | 46340                | d = 200     | D = 340      | T = 112    | Tapered roller bearing                |
| KOYO  | 46340A               | d = 200     | D = 340      | T = 140    | Tapered roller bearing                |
| FAG   | 30240-XL             | d = 200     | D = 360      | T = 64     | Tapered roller bearing                |
| FAG   | 30240-XL-J30PC       | d = 200     | D = 360      | T = 64     | Tapered roller bearing                |
| FAG   | 32240-A-J30PC        | d = 200     | D = 360      | T = 104    | Tapered roller bearing                |
| FAG   | 32240-XL             | d = 200     | D = 360      | T = 104    | Tapered roller bearing                |
| FAG   | 32240-XL-J30PC       | d = 200     | D = 360      | T = 104    | Tapered roller bearing                |
| FAG   | 32240-XL-P5          | d = 200     | D = 360      | T = 104    | Tapered roller bearing                |
| FAG   | 32240-XL>A           | d = 200     | D = 360      | T = 104    | Tapered roller bearing                |
| KOYO  | 46T30240JR/110       | d = 200     | D = 360      | T = 142    | Tapered roller bearing                |
| KOYO  | 46T32240JR/174       | d = 200     | D = 360      | T = 218    | Tapered roller bearing                |
| FAG   | 32340-XL             | d = 200     | D = 420      | T = 146    | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation   | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|------------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | KLM241147-LM241110     | d = 200.025 | D = 276.225  | T = 42.862 | Tapered roller bearing                |
| FAG   | K93787-93125           | d = 200.025 | D = 317.5    | T = 63.5   | Tapered roller bearing                |
| FAG   | KLL641149-LL641110     | d = 203.2   | D = 261.142  | T = 28.575 | Tapered roller bearing                |
| FAG   | KLM241149-LM241110     | d = 203.2   | D = 276.225  | T = 42.862 | Tapered roller bearing                |
| FAG   | K93800-93125           | d = 203.2   | D = 317.5    | T = 63.5   | Tapered roller bearing                |
| FAG   | KLL641148-LL641111     | d = 203.479 | D = 261.142  | T = 28.575 | Tapered roller bearing                |
| FAG   | KLM241148-LM241110     | d = 203.987 | D = 276.225  | T = 42.862 | Tapered roller bearing                |
| FAG   | KLM241148-LM241111     | d = 203.987 | D = 276.225  | T = 42.862 | Tapered roller bearing                |
| FAG   | K67985-67920           | d = 206.375 | D = 282.575  | T = 46.038 | Tapered roller bearing                |
| FAG   | K67985-67920-XL        | d = 206.375 | D = 282.575  | T = 46.038 | Tapered roller bearing                |
| FAG   | K67985-67920-XL-W215FD | d = 206.375 | D = 282.575  | T = 46.038 | Tapered roller bearing                |
| FAG   | K67987-67920-XL        | d = 206.375 | D = 282.575  | T = 46.038 | Tapered roller bearing                |
| FAG   | K67989-67920           | d = 209.55  | D = 282.575  | T = 46.038 | Tapered roller bearing                |
| FAG   | K93825-93125           | d = 209.55  | D = 317.5    | T = 63.5   | Tapered roller bearing                |
| FAG   | KLM742745-LM742710     | d = 212.725 | D = 285.75   | T = 46.038 | Tapered roller bearing                |
| FAG   | KLM742745-LM742710-XL  | d = 212.725 | D = 285.75   | T = 46.038 | Tapered roller bearing                |
| FAG   | KLM742749-LM742710     | d = 215.9   | D = 285.75   | T = 46.038 | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation       | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | KLM742749-LM742710-Q3      | d = 215.9   | D = 285.75   | T = 46.038 | Tapered roller bearing                |
| FAG   | KLM742749-LM742710-XL      | d = 215.9   | D = 285.75   | T = 46.038 | Tapered roller bearing                |
| FAG   | KLM742749-LM742710-XL-Q3   | d = 215.9   | D = 285.75   | T = 46.038 | Tapered roller bearing                |
| FAG   | KLM742747-LM742710         | d = 216.408 | D = 285.75   | T = 46.038 | Tapered roller bearing                |
| FAG   | KLM742747-LM742710-J20AA   | d = 216.408 | D = 285.75   | T = 46.038 | Tapered roller bearing                |
| FAG   | KLM742747-LM742710-W215FD  | d = 216.408 | D = 285.75   | T = 46.038 | Tapered roller bearing                |
| FAG   | KLM742747-A-LM742710       | d = 216.713 | D = 285.75   | T = 46.038 | Tapered roller bearing                |
| FAG   | KLM742747-A-LM742710-J20AA | d = 216.713 | D = 285.75   | T = 46.038 | Tapered roller bearing                |
| FAG   | T4DB220                    | d = 220     | D = 290      | T = 37     | Tapered roller bearing                |
| FAG   | T2DD220                    | d = 220     | D = 290      | T = 47     | Tapered roller bearing                |
| FAG   | 32944-J30PC                | d = 220     | D = 300      | T = 51     | Tapered roller bearing                |
| FAG   | 32944-P5                   | d = 220     | D = 300      | T = 51     | Tapered roller bearing                |
| FAG   | 32944-XL                   | d = 220     | D = 300      | T = 51     | Tapered roller bearing                |
| FAG   | 32944-XL-J30PC             | d = 220     | D = 300      | T = 51     | Tapered roller bearing                |
| FAG   | 32944-XL-P5                | d = 220     | D = 300      | T = 51     | Tapered roller bearing                |
| FAG   | 32944>A                    | d = 220     | D = 300      | T = 51     | Tapered roller bearing                |
| FAG   | T2ED220                    | d = 220     | D = 300      | T = 56     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 32044-X              | d = 220     | D = 340      | T = 76     | Tapered roller bearing                |
| FAG   | 32044-X-XL           | d = 220     | D = 340      | T = 76     | Tapered roller bearing                |
| FAG   | 32044-X-XL-J30PC     | d = 220     | D = 340      | T = 76     | Tapered roller bearing                |
| FAG   | 32044-X-XL-P5        | d = 220     | D = 340      | T = 76     | Tapered roller bearing                |
| FAG   | 32044-X-XL>A         | d = 220     | D = 340      | T = 76     | Tapered roller bearing                |
| KOYO  | 46244                | d = 220     | D = 340      | T = 90     | Tapered roller bearing                |
| KOYO  | 46244A               | d = 220     | D = 340      | T = 113    | Tapered roller bearing                |
| KOYO  | 46344                | d = 220     | D = 370      | T = 120    | Tapered roller bearing                |
| KOYO  | 46344A               | d = 220     | D = 370      | T = 150    | Tapered roller bearing                |
| FAG   | 30244-A              | d = 220     | D = 400      | T = 72     | Tapered roller bearing                |
| FAG   | 30244-XL             | d = 220     | D = 400      | T = 72     | Tapered roller bearing                |
| FAG   | 30244-XL-J30PC       | d = 220     | D = 400      | T = 72     | Tapered roller bearing                |
| FAG   | 32244-XL             | d = 220     | D = 400      | T = 114    | Tapered roller bearing                |
| FAG   | 32244-XL-J30PC       | d = 220     | D = 400      | T = 114    | Tapered roller bearing                |
| FAG   | 32244-XL-P5          | d = 220     | D = 400      | T = 114    | Tapered roller bearing                |
| KOYO  | 46T30244JR/114       | d = 220     | D = 400      | T = 150    | Tapered roller bearing                |
| FAG   | 32344                | d = 220     | D = 460      | T = 154    | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation  | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration         |
|-------|-----------------------|-------------|--------------|------------|-----------------------------------------------|
| FAG   | 32344-XL              | d = 220     | D = 460      | T = 154    | Tapered roller bearing                        |
| FAG   | KLM245833-LM245810-XL | d = 220.878 | D = 317.5    | T = 47.625 | Tapered roller bearing                        |
| FAG   | KLM844049-LM844010    | d = 223.838 | D = 295.275  | T = 46.038 | Tapered roller bearing                        |
| FAG   | KLM844049-LM844010-XL | d = 223.838 | D = 295.275  | T = 46.038 | Tapered roller bearing                        |
| FAG   | AK544090-544116       | d = 228.6   | D = 295.275  | T = 33.338 | Tapered roller bearing                        |
| FAG   | AK544090-544118       | d = 228.6   | D = 300.038  | T = 33.338 | Tapered roller bearing                        |
| FAG   | K8573-8520            | d = 228.6   | D = 327.025  | T = 52.388 | Tapered roller bearing                        |
| FAG   | K96900-96140          | d = 228.6   | D = 355.6    | T = 68.263 | Tapered roller bearing                        |
| FAG   | K96900-96140-XL       | d = 228.6   | D = 355.6    | T = 68.263 | Tapered roller bearing                        |
| SKF   | 331945                | d = 228.6   | D = 488.95   | T = 254    | Double row tapered roller bearing, TDO design |
| FAG   | KLM245846-LM245810    | d = 230.188 | D = 317.5    | T = 47.625 | Tapered roller bearing                        |
| FAG   | KLL244549-LL244510    | d = 231.775 | D = 268.288  | T = 22.5   | Tapered roller bearing                        |
| FAG   | AK544091-544116       | d = 231.775 | D = 295.275  | T = 33.338 | Tapered roller bearing                        |
| FAG   | AK544091-544118       | d = 231.775 | D = 300.038  | T = 33.338 | Tapered roller bearing                        |
| FAG   | KLM245848-LM245810-XL | d = 231.775 | D = 317.5    | T = 47.625 | Tapered roller bearing                        |
| FAG   | KM246942-M246910      | d = 231.775 | D = 336.55   | T = 65.088 | Tapered roller bearing                        |
| FAG   | KLM545849-LM545810-Q3 | d = 234.95  | D = 314.325  | T = 49.212 | Tapered roller bearing                        |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation         | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|------------------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | KLM545849-LM545810-XL-W215FD | d = 234.95  | D = 314.325  | T = 49.212 | Tapered roller bearing                |
| FAG   | K8575-8520                   | d = 234.95  | D = 327.025  | T = 52.388 | Tapered roller bearing                |
| FAG   | KM246949-M246910             | d = 237.33  | D = 336.55   | T = 65.088 | Tapered roller bearing                |
| FAG   | T2DC240                      | d = 240     | D = 305      | T = 41     | Tapered roller bearing                |
| FAG   | T2DD240                      | d = 240     | D = 310      | T = 47     | Tapered roller bearing                |
| FAG   | T4EB240                      | d = 240     | D = 320      | T = 42     | Tapered roller bearing                |
| FAG   | 32948                        | d = 240     | D = 320      | T = 51     | Tapered roller bearing                |
| FAG   | 32948-XL                     | d = 240     | D = 320      | T = 51     | Tapered roller bearing                |
| FAG   | 32948-XL-J30PC               | d = 240     | D = 320      | T = 51     | Tapered roller bearing                |
| FAG   | 32948-XL-P5                  | d = 240     | D = 320      | T = 51     | Tapered roller bearing                |
| FAG   | 32948>A                      | d = 240     | D = 320      | T = 51     | Tapered roller bearing                |
| FAG   | T2EE240                      | d = 240     | D = 320      | T = 57     | Tapered roller bearing                |
| FAG   | 32048-X                      | d = 240     | D = 360      | T = 76     | Tapered roller bearing                |
| FAG   | 32048-X-XL                   | d = 240     | D = 360      | T = 76     | Tapered roller bearing                |
| FAG   | 32048-X-XL-J20AA             | d = 240     | D = 360      | T = 76     | Tapered roller bearing                |
| FAG   | 32048-X-XL-J30PC             | d = 240     | D = 360      | T = 76     | Tapered roller bearing                |
| FAG   | 32048-X-XL-P5                | d = 240     | D = 360      | T = 76     | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation  | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration         |
|-------|-----------------------|-------------|--------------|------------|-----------------------------------------------|
| FAG   | 32048-X>A             | d = 240     | D = 360      | T = 76     | Tapered roller bearing                        |
| KOYO  | 46248                 | d = 240     | D = 360      | T = 92     | Tapered roller bearing                        |
| KOYO  | 46248A                | d = 240     | D = 360      | T = 115    | Tapered roller bearing                        |
| KOYO  | 46348                 | d = 240     | D = 400      | T = 128    | Tapered roller bearing                        |
| KOYO  | 46348A                | d = 240     | D = 400      | T = 160    | Tapered roller bearing                        |
| FAG   | 30248                 | d = 240     | D = 440      | T = 79     | Tapered roller bearing                        |
| FAG   | 30248-XL              | d = 240     | D = 440      | T = 79     | Tapered roller bearing                        |
| FAG   | 32248-XL              | d = 240     | D = 440      | T = 127    | Tapered roller bearing                        |
| FAG   | 32248-XL-J30PC        | d = 240     | D = 440      | T = 127    | Tapered roller bearing                        |
| SKF   | BT2B 332931           | d = 240     | D = 480      | T = 220    | Double row tapered roller bearing, TDI design |
| FAG   | 30348                 | d = 240     | D = 500      | T = 105    | Tapered roller bearing                        |
| FAG   | 32348                 | d = 240     | D = 500      | T = 165    | Tapered roller bearing                        |
| FAG   | 32348-XL              | d = 240     | D = 500      | T = 165    | Tapered roller bearing                        |
| FAG   | K8578-8520            | d = 241.3   | D = 327.025  | T = 52.388 | Tapered roller bearing                        |
| FAG   | K923095-923175        | d = 241.3   | D = 444.5    | T = 101.6  | Tapered roller bearing                        |
| FAG   | KLL648434-LL648415    | d = 243.682 | D = 315.912  | T = 31.75  | Tapered roller bearing                        |
| FAG   | KLL648434-LL648415-XL | d = 243.682 | D = 315.912  | T = 31.75  | Tapered roller bearing                        |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation  | Inside (mm) | Outside (mm) | Axial (mm)  | Recorded construction / configuration |
|-------|-----------------------|-------------|--------------|-------------|---------------------------------------|
| FAG   | K28880-28820-XL       | d = 247.65  | D = 304.8    | T = 22.225  | Tapered roller bearing                |
| FAG   | KM348449-M348410      | d = 247.65  | D = 346.075  | T = 63.5    | Tapered roller bearing                |
| FAG   | KHH249949-HH249910    | d = 247.65  | D = 406.4    | T = 115.888 | Tapered roller bearing                |
| FAG   | KHH249949-HH249910-XL | d = 247.65  | D = 406.4    | T = 115.888 | Tapered roller bearing                |
| FAG   | KLL648449-LL648415    | d = 254     | D = 315.912  | T = 31.75   | Tapered roller bearing                |
| FAG   | K29875-29820          | d = 254     | D = 323.85   | T = 22.225  | Tapered roller bearing                |
| FAG   | KM349549-M349510      | d = 257.175 | D = 342.9    | T = 57.15   | Tapered roller bearing                |
| FAG   | T2DC260               | d = 260     | D = 325      | T = 41      | Tapered roller bearing                |
| FAG   | T2DD260               | d = 260     | D = 330      | T = 47      | Tapered roller bearing                |
| FAG   | T4DB260               | d = 260     | D = 340      | T = 42      | Tapered roller bearing                |
| FAG   | 32952                 | d = 260     | D = 360      | T = 63.5    | Tapered roller bearing                |
| FAG   | 32952-XL              | d = 260     | D = 360      | T = 63.5    | Tapered roller bearing                |
| FAG   | 32952-XL-J30PC        | d = 260     | D = 360      | T = 63.5    | Tapered roller bearing                |
| FAG   | 32952-XL-P5           | d = 260     | D = 360      | T = 63.5    | Tapered roller bearing                |
| FAG   | 32052-X-XL            | d = 260     | D = 400      | T = 87      | Tapered roller bearing                |
| FAG   | 32052-X-XL-J30PC      | d = 260     | D = 400      | T = 87      | Tapered roller bearing                |
| FAG   | 32052-X-XL-P5         | d = 260     | D = 400      | T = 87      | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration         |
|-------|----------------------|-------------|--------------|------------|-----------------------------------------------|
| FAG   | 32052-X>A            | d = 260     | D = 400      | T = 87     | Tapered roller bearing                        |
| KOYO  | 46252                | d = 260     | D = 400      | T = 104    | Tapered roller bearing                        |
| KOYO  | 46252A               | d = 260     | D = 400      | T = 130    | Tapered roller bearing                        |
| KOYO  | 46352                | d = 260     | D = 440      | T = 144    | Tapered roller bearing                        |
| KOYO  | 46352A               | d = 260     | D = 440      | T = 180    | Tapered roller bearing                        |
| FAG   | 30252-A              | d = 260     | D = 480      | T = 89     | Tapered roller bearing                        |
| FAG   | 30252-XL             | d = 260     | D = 480      | T = 89     | Tapered roller bearing                        |
| FAG   | 32252-XL             | d = 260     | D = 480      | T = 137    | Tapered roller bearing                        |
| FAG   | 32252-XL-J30PC       | d = 260     | D = 480      | T = 137    | Tapered roller bearing                        |
| FAG   | 32252>A              | d = 260     | D = 480      | T = 137    | Tapered roller bearing                        |
| SKF   | BT2B 328130          | d = 260     | D = 480      | T = 284    | Double row tapered roller bearing, TDO design |
| FAG   | 30352-XL             | d = 260     | D = 540      | T = 113    | Tapered roller bearing                        |
| FAG   | 32352                | d = 260     | D = 540      | T = 176    | Tapered roller bearing                        |
| FAG   | K134102-134143       | d = 260.35  | D = 365.125  | T = 58.738 | Tapered roller bearing                        |
| FAG   | K435102-435165-XL    | d = 260.35  | D = 419.1    | T = 85.725 | Tapered roller bearing                        |
| FAG   | K29880-29820         | d = 266.7   | D = 323.85   | T = 22.225 | Tapered roller bearing                        |
| FAG   | KLL352149-LL352110   | d = 279.4   | D = 317.5    | T = 24.384 | Tapered roller bearing                        |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | K722110-722185       | d = 279.4   | D = 469.9    | T = 95.25  | Tapered roller bearing                |
| FAG   | KLM654642-LM654610   | d = 279.982 | D = 380.898  | T = 65.088 | Tapered roller bearing                |
| FAG   | T4EB280              | d = 280     | D = 370      | T = 48     | Tapered roller bearing                |
| FAG   | 32956-XL             | d = 280     | D = 380      | T = 63.5   | Tapered roller bearing                |
| FAG   | 32956-XL-J30PC       | d = 280     | D = 380      | T = 63.5   | Tapered roller bearing                |
| FAG   | 32956-XL-P5          | d = 280     | D = 380      | T = 63.5   | Tapered roller bearing                |
| FAG   | 32056-X              | d = 280     | D = 420      | T = 87     | Tapered roller bearing                |
| FAG   | 32056-X-XL           | d = 280     | D = 420      | T = 87     | Tapered roller bearing                |
| FAG   | 32056-X-XL-P5        | d = 280     | D = 420      | T = 87     | Tapered roller bearing                |
| FAG   | 32056-X>A            | d = 280     | D = 420      | T = 87     | Tapered roller bearing                |
| KOYO  | 46256                | d = 280     | D = 420      | T = 106    | Tapered roller bearing                |
| KOYO  | 46256A               | d = 280     | D = 420      | T = 133    | Tapered roller bearing                |
| KOYO  | 46356                | d = 280     | D = 460      | T = 146    | Tapered roller bearing                |
| KOYO  | 46356A               | d = 280     | D = 460      | T = 183    | Tapered roller bearing                |
| FAG   | 30256                | d = 280     | D = 500      | T = 89     | Tapered roller bearing                |
| FAG   | 32256-P5             | d = 280     | D = 500      | T = 137    | Tapered roller bearing                |
| FAG   | 32256-XL             | d = 280     | D = 500      | T = 137    | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|----------------------|-------------|--------------|------------|---------------------------------------|
| FAG   | 32256-XL-J30PC       | d = 280     | D = 500      | T = 137    | Tapered roller bearing                |
| FAG   | 30356-XL             | d = 280     | D = 580      | T = 119    | Tapered roller bearing                |
| FAG   | 32356                | d = 280     | D = 580      | T = 187    | Tapered roller bearing                |
| FAG   | KLM654649-LM654610   | d = 285.75  | D = 380.898  | T = 65.088 | Tapered roller bearing                |
| FAG   | T4EB300              | d = 300     | D = 400      | T = 52     | Tapered roller bearing                |
| FAG   | 32960                | d = 300     | D = 420      | T = 76     | Tapered roller bearing                |
| FAG   | 32960-XL             | d = 300     | D = 420      | T = 76     | Tapered roller bearing                |
| FAG   | 32960-XL-J30PC       | d = 300     | D = 420      | T = 76     | Tapered roller bearing                |
| FAG   | 32960-XL-P5          | d = 300     | D = 420      | T = 76     | Tapered roller bearing                |
| FAG   | 32960>A              | d = 300     | D = 420      | T = 76     | Tapered roller bearing                |
| FAG   | 32060-X              | d = 300     | D = 460      | T = 100    | Tapered roller bearing                |
| FAG   | 32060-X-XL           | d = 300     | D = 460      | T = 100    | Tapered roller bearing                |
| FAG   | 32060-X-XL-J30PC     | d = 300     | D = 460      | T = 100    | Tapered roller bearing                |
| KOYO  | 46260                | d = 300     | D = 460      | T = 118    | Tapered roller bearing                |
| KOYO  | 46260A               | d = 300     | D = 460      | T = 148    | Tapered roller bearing                |
| KOYO  | 46360                | d = 300     | D = 500      | T = 160    | Tapered roller bearing                |
| KOYO  | 46360A               | d = 300     | D = 500      | T = 200    | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm)  | Recorded construction / configuration         |
|-------|----------------------|-------------|--------------|-------------|-----------------------------------------------|
| KOYO  | 46360D               | d = 300     | D = 500      | T = 200     | Tapered roller bearing                        |
| FAG   | 30260-XL             | d = 300     | D = 540      | T = 96      | Tapered roller bearing                        |
| FAG   | 32260                | d = 300     | D = 540      | T = 149     | Tapered roller bearing                        |
| FAG   | 32260-J30PC          | d = 300     | D = 540      | T = 149     | Tapered roller bearing                        |
| FAG   | 32260-XL             | d = 300     | D = 540      | T = 149     | Tapered roller bearing                        |
| FAG   | 32260-XL-P5          | d = 300     | D = 540      | T = 149     | Tapered roller bearing                        |
| SKF   | BT2B 332504/HA2      | d = 300.038 | D = 422.275  | T = 174.625 | Double row tapered roller bearing, TDO design |
| FAG   | KL357049-L357010     | d = 304.8   | D = 393.7    | T = 50.8    | Tapered roller bearing                        |
| FAG   | KL357049-L357010-Q3  | d = 304.8   | D = 393.7    | T = 50.8    | Tapered roller bearing                        |
| FAG   | T4EB320-XL           | d = 320     | D = 420      | T = 53      | Tapered roller bearing                        |
| FAG   | 32964                | d = 320     | D = 440      | T = 76      | Tapered roller bearing                        |
| FAG   | 32964-XL             | d = 320     | D = 440      | T = 76      | Tapered roller bearing                        |
| FAG   | 32964-XL-J30PC       | d = 320     | D = 440      | T = 76      | Tapered roller bearing                        |
| FAG   | 32964-XL-P5          | d = 320     | D = 440      | T = 76      | Tapered roller bearing                        |
| FAG   | 32964-XL>A           | d = 320     | D = 440      | T = 76      | Tapered roller bearing                        |
| FAG   | 32964-XL>B           | d = 320     | D = 440      | T = 76      | Tapered roller bearing                        |
| FAG   | 32064-X-XL           | d = 320     | D = 480      | T = 100     | Tapered roller bearing                        |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration         |
|-------|----------------------|-------------|--------------|------------|-----------------------------------------------|
| FAG   | 32064-X-XL-P5        | d = 320     | D = 480      | T = 100    | Tapered roller bearing                        |
| KOYO  | 46264                | d = 320     | D = 480      | T = 121    | Tapered roller bearing                        |
| KOYO  | 46264A               | d = 320     | D = 480      | T = 151    | Tapered roller bearing                        |
| KOYO  | 46364                | d = 320     | D = 540      | T = 176    | Tapered roller bearing                        |
| KOYO  | 46364A               | d = 320     | D = 540      | T = 220    | Tapered roller bearing                        |
| FAG   | 30264-XL             | d = 320     | D = 580      | T = 104    | Tapered roller bearing                        |
| FAG   | 32264                | d = 320     | D = 580      | T = 159    | Tapered roller bearing                        |
| FAG   | 32264-XL             | d = 320     | D = 580      | T = 159    | Tapered roller bearing                        |
| FAG   | 32264-XL-J30PC       | d = 320     | D = 580      | T = 159    | Tapered roller bearing                        |
| FAG   | KLL758744-LL758715   | d = 323.85  | D = 381      | T = 23.575 | Tapered roller bearing                        |
| FAG   | KL860049-L860010-XL  | d = 330.2   | D = 415.925  | T = 47.625 | Tapered roller bearing                        |
| FAG   | 32968-XL             | d = 340     | D = 460      | T = 76     | Tapered roller bearing                        |
| FAG   | 32968-XL-J30PC       | d = 340     | D = 460      | T = 76     | Tapered roller bearing                        |
| SKF   | BT2B 332830          | d = 340     | D = 460      | T = 160    | Double row tapered roller bearing, TDO design |
| KOYO  | 46268                | d = 340     | D = 520      | T = 133    | Tapered roller bearing                        |
| KOYO  | 46268A               | d = 340     | D = 520      | T = 165    | Tapered roller bearing                        |
| KOYO  | 46368                | d = 340     | D = 580      | T = 190    | Tapered roller bearing                        |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation    | Inside (mm) | Outside (mm) | Axial (mm)  | Recorded construction / configuration         |
|-------|-------------------------|-------------|--------------|-------------|-----------------------------------------------|
| KOYO  | 46368A                  | d = 340     | D = 580      | T = 238     | Tapered roller bearing                        |
| FAG   | KLM361649-LM361610-XL   | d = 342.9   | D = 450.85   | T = 66.675  | Tapered roller bearing                        |
| FAG   | KLM361649-A-LM361610-XL | d = 343.154 | D = 450.85   | T = 66.675  | Tapered roller bearing                        |
| FAG   | KL163149-L163110-XL     | d = 355.6   | D = 444.5    | T = 60.325  | Tapered roller bearing                        |
| FAG   | K231400-231975          | d = 355.6   | D = 501.65   | T = 74.612  | Tapered roller bearing                        |
| FAG   | 32972-XL                | d = 360     | D = 480      | T = 76      | Tapered roller bearing                        |
| FAG   | 32972-XL-J30PC          | d = 360     | D = 480      | T = 76      | Tapered roller bearing                        |
| FAG   | 32972-XL-P5             | d = 360     | D = 480      | T = 76      | Tapered roller bearing                        |
| SKF   | BT2B 332831             | d = 360     | D = 480      | T = 160     | Double row tapered roller bearing, TDO design |
| KOYO  | 46272                   | d = 360     | D = 540      | T = 134     | Tapered roller bearing                        |
| KOYO  | 46272A                  | d = 360     | D = 540      | T = 169     | Tapered roller bearing                        |
| KOYO  | 46372                   | d = 360     | D = 600      | T = 192     | Tapered roller bearing                        |
| KOYO  | 46372A                  | d = 360     | D = 600      | T = 240     | Tapered roller bearing                        |
| FAG   | KLL562749-LL562710      | d = 361.95  | D = 406.4    | T = 23.812  | Tapered roller bearing                        |
| SKF   | BT2B 332603/HA1         | d = 368.249 | D = 523.875  | T = 214.312 | Double row tapered roller bearing, TDO design |
| FAG   | K231462-231975          | d = 371.475 | D = 501.65   | T = 74.612  | Tapered roller bearing                        |
| FAG   | KLL264648-LL264610      | d = 374.65  | D = 431.8    | T = 28.575  | Tapered roller bearing                        |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm)  | Recorded construction / configuration         |
|-------|----------------------|-------------|--------------|-------------|-----------------------------------------------|
| FAG   | 32976-XL             | d = 380     | D = 520      | T = 87      | Tapered roller bearing                        |
| FAG   | 32076-XL             | d = 380     | D = 560      | T = 112     | Tapered roller bearing                        |
| KOYO  | 46276                | d = 380     | D = 560      | T = 135     | Tapered roller bearing                        |
| KOYO  | 46276A               | d = 380     | D = 560      | T = 171     | Tapered roller bearing                        |
| KOYO  | 46376                | d = 380     | D = 620      | T = 194     | Tapered roller bearing                        |
| KOYO  | 46376A               | d = 380     | D = 620      | T = 243     | Tapered roller bearing                        |
| FAG   | KLL365348-LL365310   | d = 384.175 | D = 441.325  | T = 28.575  | Tapered roller bearing                        |
| SKF   | 331197 A             | d = 384.175 | D = 546.1    | T = 222.25  | Double row tapered roller bearing, TDO design |
| FAG   | 32980-XL             | d = 400     | D = 540      | T = 87      | Tapered roller bearing                        |
| FAG   | 32980-XL-P5          | d = 400     | D = 540      | T = 87      | Tapered roller bearing                        |
| SKF   | BT2-8143/HA1         | d = 400     | D = 540      | T = 170     | Double row tapered roller bearing, TDO design |
| KOYO  | 46280                | d = 400     | D = 600      | T = 148     | Tapered roller bearing                        |
| KOYO  | 46280A               | d = 400     | D = 600      | T = 185     | Tapered roller bearing                        |
| KOYO  | 46380                | d = 400     | D = 650      | T = 200     | Tapered roller bearing                        |
| KOYO  | 46380A               | d = 400     | D = 650      | T = 250     | Tapered roller bearing                        |
| SKF   | 331656               | d = 415.925 | D = 590.55   | T = 244.475 | Double row tapered roller bearing, TDO design |
| FAG   | 32984-XL             | d = 420     | D = 560      | T = 87      | Tapered roller bearing                        |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm)  | Recorded construction / configuration         |
|-------|----------------------|-------------|--------------|-------------|-----------------------------------------------|
| FAG   | 32084-XL             | d = 420     | D = 620      | T = 125     | Tapered roller bearing                        |
| KOYO  | 46284                | d = 420     | D = 620      | T = 150     | Tapered roller bearing                        |
| KOYO  | 46284A               | d = 420     | D = 620      | T = 188     | Tapered roller bearing                        |
| KOYO  | 46384                | d = 420     | D = 700      | T = 224     | Tapered roller bearing                        |
| KOYO  | 46384A               | d = 420     | D = 700      | T = 280     | Tapered roller bearing                        |
| SKF   | BT2B 332604/HA1      | d = 431.8   | D = 571.5    | T = 155.575 | Double row tapered roller bearing, TDO design |
| FAG   | F-563822.03.TR1      | d = 440     | D = 540      | T = 46      | Tapered roller bearing                        |
| KOYO  | 46288                | d = 440     | D = 650      | T = 157     | Tapered roller bearing                        |
| KOYO  | 46288A               | d = 440     | D = 650      | T = 196     | Tapered roller bearing                        |
| KOYO  | 46388                | d = 440     | D = 720      | T = 226     | Tapered roller bearing                        |
| KOYO  | 46388A               | d = 440     | D = 720      | T = 283     | Tapered roller bearing                        |
| FAG   | K80176-80217         | d = 447.675 | D = 552.45   | T = 44.45   | Tapered roller bearing                        |
| FAG   | K80176-80217-XL      | d = 447.675 | D = 552.45   | T = 44.45   | Tapered roller bearing                        |
| FAG   | K80180-80217-XL      | d = 457.2   | D = 552.45   | T = 44.45   | Tapered roller bearing                        |
| FAG   | Z-535809.TR1         | d = 460     | D = 620      | T = 100     | Tapered roller bearing                        |
| KOYO  | 46292                | d = 460     | D = 680      | T = 163     | Tapered roller bearing                        |
| KOYO  | 46292A               | d = 460     | D = 680      | T = 204     | Tapered roller bearing                        |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm)  | Recorded construction / configuration         |
|-------|----------------------|-------------|--------------|-------------|-----------------------------------------------|
| KOYO  | 46392                | d = 460     | D = 760      | T = 240     | Tapered roller bearing                        |
| KOYO  | 46392A               | d = 460     | D = 760      | T = 300     | Tapered roller bearing                        |
| SKF   | BT2-8215             | d = 464     | D = 615      | T = 150     | Double row tapered roller bearing, TDI design |
| SKF   | 331657               | d = 479.425 | D = 679.45   | T = 276.225 | Double row tapered roller bearing, TDO design |
| KOYO  | 46296                | d = 480     | D = 700      | T = 165     | Tapered roller bearing                        |
| KOYO  | 46296A               | d = 480     | D = 700      | T = 206     | Tapered roller bearing                        |
| FAG   | F-573682.TR1         | d = 480     | D = 720      | T = 135     | Tapered roller bearing                        |
| KOYO  | 46396                | d = 480     | D = 790      | T = 248     | Tapered roller bearing                        |
| KOYO  | 46396A               | d = 480     | D = 790      | T = 310     | Tapered roller bearing                        |
| FAG   | K243190-243250-XL    | d = 482.6   | D = 634.873  | T = 80.962  | Tapered roller bearing                        |
| FAG   | K243196-243250-XL    | d = 498.475 | D = 634.873  | T = 80.962  | Tapered roller bearing                        |
| SKF   | 331605 B             | d = 498.475 | D = 634.873  | T = 177.8   | Double row tapered roller bearing, TDO design |
| FAG   | Z-565783.TR1         | d = 500     | D = 620      | T = 56      | Tapered roller bearing                        |
| FAG   | F-809489.TR1         | d = 500     | D = 650      | T = 82      | Tapered roller bearing                        |
| FAG   | Z-565803.TR1         | d = 500     | D = 670      | T = 85      | Tapered roller bearing                        |
| KOYO  | 462/500              | d = 500     | D = 720      | T = 167     | Tapered roller bearing                        |
| KOYO  | 462/500A             | d = 500     | D = 720      | T = 209     | Tapered roller bearing                        |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm)  | Recorded construction / configuration         |
|-------|----------------------|-------------|--------------|-------------|-----------------------------------------------|
| KOYO  | 463/500              | d = 500     | D = 830      | T = 264     | Tapered roller bearing                        |
| KOYO  | 463/500A             | d = 500     | D = 830      | T = 330     | Tapered roller bearing                        |
| SKF   | BT2B 332605 A/HA1    | d = 501.65  | D = 711.2    | T = 292.1   | Double row tapered roller bearing, TDO design |
| FAG   | F-807079.TR1         | d = 530     | D = 670      | T = 100     | Tapered roller bearing                        |
| KOYO  | 462/530              | d = 530     | D = 780      | T = 185     | Tapered roller bearing                        |
| KOYO  | 462/530A             | d = 530     | D = 780      | T = 231     | Tapered roller bearing                        |
| KOYO  | 463/530              | d = 530     | D = 870      | T = 272     | Tapered roller bearing                        |
| KOYO  | 463/530A             | d = 530     | D = 870      | T = 340     | Tapered roller bearing                        |
| SKF   | BT2B 332446          | d = 536.575 | D = 761.873  | T = 311.15  | Double row tapered roller bearing, TDO design |
| SKF   | 331640 A             | d = 558.8   | D = 736.6    | T = 225.425 | Double row tapered roller bearing, TDO design |
| FAG   | F-809572.TR1         | d = 560     | D = 680      | T = 60      | Tapered roller bearing                        |
| KOYO  | 462/560              | d = 560     | D = 820      | T = 195     | Tapered roller bearing                        |
| KOYO  | 462/560A             | d = 560     | D = 820      | T = 244     | Tapered roller bearing                        |
| KOYO  | 463/560              | d = 560     | D = 920      | T = 280     | Tapered roller bearing                        |
| KOYO  | 463/560A             | d = 560     | D = 920      | T = 350     | Tapered roller bearing                        |
| FAG   | K680235-680270       | d = 596.9   | D = 685.8    | T = 31.75   | Tapered roller bearing                        |
| FAG   | F-807072.TR1         | d = 600     | D = 740      | T = 80      | Tapered roller bearing                        |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation     | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration |
|-------|--------------------------|-------------|--------------|------------|---------------------------------------|
| KOYO  | 462/600                  | d = 600     | D = 870      | T = 200    | Tapered roller bearing                |
| KOYO  | 462/600A                 | d = 600     | D = 870      | T = 250    | Tapered roller bearing                |
| KOYO  | 463/600                  | d = 600     | D = 980      | T = 300    | Tapered roller bearing                |
| KOYO  | 463/600A                 | d = 600     | D = 980      | T = 388    | Tapered roller bearing                |
| FAG   | F-573263.TR1             | d = 630     | D = 850      | T = 107    | Tapered roller bearing                |
| FAG   | Z-523871.TR1             | d = 630     | D = 850      | T = 108    | Tapered roller bearing                |
| KOYO  | 462/630                  | d = 630     | D = 920      | T = 212    | Tapered roller bearing                |
| KOYO  | 462/630A                 | d = 630     | D = 920      | T = 265    | Tapered roller bearing                |
| KOYO  | 463/630                  | d = 630     | D = 1030     | T = 315    | Tapered roller bearing                |
| KOYO  | 463/630A                 | d = 630     | D = 1030     | T = 389    | Tapered roller bearing                |
| FAG   | Z-507596.TR1             | d = 670     | D = 820      | T = 88     | Tapered roller bearing                |
| KOYO  | 462/670                  | d = 670     | D = 980      | T = 230    | Tapered roller bearing                |
| KOYO  | 462/670A                 | d = 670     | D = 980      | T = 288    | Tapered roller bearing                |
| KOYO  | 463/670                  | d = 670     | D = 1090     | T = 336    | Tapered roller bearing                |
| KOYO  | 463/670A                 | d = 670     | D = 1090     | T = 392    | Tapered roller bearing                |
| FAG   | KLL481448-LL481411       | d = 673.1   | D = 793.75   | T = 66.675 | Tapered roller bearing                |
| FAG   | KLL481448-LL481411-J30PC | d = 673.1   | D = 793.75   | T = 66.675 | Tapered roller bearing                |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm)  | Recorded construction / configuration         |
|-------|----------------------|-------------|--------------|-------------|-----------------------------------------------|
| FAG   | F-679925.TR1         | d = 710     | D = 900      | T = 80      | Tapered roller bearing                        |
| KOYO  | 462/710              | d = 710     | D = 1030     | T = 236     | Tapered roller bearing                        |
| KOYO  | 462/710A             | d = 710     | D = 1030     | T = 295     | Tapered roller bearing                        |
| KOYO  | 463/710              | d = 710     | D = 1150     | T = 345     | Tapered roller bearing                        |
| KOYO  | 463/710A             | d = 710     | D = 1150     | T = 393     | Tapered roller bearing                        |
| SKF   | BT2B 328028/HA1      | d = 711.2   | D = 914.4    | T = 190.5   | Double row tapered roller bearing, TDO design |
| SKF   | 331554 A             | d = 723.9   | D = 914.4    | T = 187.325 | Double row tapered roller bearing, TDO design |
| SKF   | BT2B 331554 B/HA1    | d = 723.9   | D = 914.4    | T = 187.325 | Double row tapered roller bearing, TDO design |
| FAG   | Z-543060.TR1         | d = 749.3   | D = 990.6    | T = 159.5   | Tapered roller bearing                        |
| FAG   | F-562256.TR1         | d = 750     | D = 910      | T = 90      | Tapered roller bearing                        |
| KOYO  | 462/750              | d = 750     | D = 1090     | T = 250     | Tapered roller bearing                        |
| KOYO  | 462/750A             | d = 750     | D = 1090     | T = 313     | Tapered roller bearing                        |
| KOYO  | 463/750              | d = 750     | D = 1220     | T = 365     | Tapered roller bearing                        |
| KOYO  | 463/750A             | d = 750     | D = 1220     | T = 395     | Tapered roller bearing                        |
| FAG   | F-630161.01.TR1      | d = 800     | D = 1000     | T = 80      | Tapered roller bearing                        |
| KOYO  | 462/800              | d = 800     | D = 1150     | T = 258     | Tapered roller bearing                        |
| KOYO  | 462/800A             | d = 800     | D = 1150     | T = 323     | Tapered roller bearing                        |

# Tapered roller bearings

Tapered roller bearings

T is the recorded complete tapered assembly width. It is not the cone width B or cup width C; a matching envelope is not proof that cone and cup components can be mixed.

| Brand | Complete designation | Inside (mm) | Outside (mm) | Axial (mm) | Recorded construction / configuration         |
|-------|----------------------|-------------|--------------|------------|-----------------------------------------------|
| KOYO  | 463/800              | d = 800     | D = 1280     | T = 375    | Tapered roller bearing                        |
| KOYO  | 463/800A             | d = 800     | D = 1280     | T = 397    | Tapered roller bearing                        |
| FAG   | F-601300.TR1         | d = 850     | D = 1030     | T = 90     | Tapered roller bearing                        |
| KOYO  | 462/850              | d = 850     | D = 1220     | T = 272    | Tapered roller bearing                        |
| KOYO  | 462/850A             | d = 850     | D = 1220     | T = 340    | Tapered roller bearing                        |
| KOYO  | 463/850              | d = 850     | D = 1360     | T = 400    | Tapered roller bearing                        |
| KOYO  | 463/850A             | d = 850     | D = 1360     | T = 500    | Tapered roller bearing                        |
| FAG   | Z-538340.TR1         | d = 900     | D = 1180     | T = 122.5  | Tapered roller bearing                        |
| KOYO  | 462/900              | d = 900     | D = 1280     | T = 280    | Tapered roller bearing                        |
| KOYO  | 462/900A             | d = 900     | D = 1280     | T = 350    | Tapered roller bearing                        |
| SKF   | BT2B 332501/HA5      | d = 914.4   | D = 1066.8   | T = 139.7  | Double row tapered roller bearing, TDO design |
| FAG   | Z-549029.01.TR1      | d = 930     | D = 1060     | T = 92     | Tapered roller bearing                        |
| FAG   | F-693840.TR1         | d = 950     | D = 1250     | T = 125    | Tapered roller bearing                        |
| KOYO  | 462/950              | d = 950     | D = 1360     | T = 300    | Tapered roller bearing                        |
| KOYO  | 462/950A             | d = 950     | D = 1360     | T = 375    | Tapered roller bearing                        |
| FAG   | F-693839.TR1         | d = 1000    | D = 1300     | T = 161    | Tapered roller bearing                        |
| SKF   | BT2B 332780/HA5      | d = 1160    | D = 1540     | T = 400    | Double row tapered roller bearing, TDO design |